
AWS Data Wrangler

Release 1.5.0

Igor Tavares

Jun 14, 2020

CONTENTS

1	Read The Docs	3
1.1	What is AWS Data Wrangler?	3
1.2	Install	3
1.3	API Reference	6
	Index	113


```
>>> pip install awswrangler
```

```
import awswrangler as wr
import pandas as pd

df = pd.DataFrame({"id": [1, 2], "value": ["foo", "boo"]})

# Storing data on Data Lake
wr.s3.to_parquet(
    df=df,
    path="s3://bucket/dataset/",
    dataset=True,
    database="my_db",
    table="my_table"
)

# Retrieving the data directly from Amazon S3
df = wr.s3.read_parquet("s3://bucket/dataset/", dataset=True)

# Retrieving the data from Amazon Athena
df = wr.athena.read_sql_query("SELECT * FROM my_table", database="my_db")

# Get Redshift connection (SQLAlchemy) from Glue and retrieving data from Redshift_
↳ Spectrum
engine = wr.catalog.get_engine("my-redshift-connection")
df = wr.db.read_sql_query("SELECT * FROM external_schema.my_table", con=engine)

# Creating QuickSight Data Source and Dataset to reflect our new table
wr.quicksight.create_athena_data_source("athena-source", allowed_to_manage=["username
↳"])
wr.quicksight.create_athena_dataset(
    name="my-dataset",
    database="my_db",
    table="my_table",
    data_source_name="athena-source",
    allowed_to_manage=["username"]
)

# Get MySQL connection (SQLAlchemy) from Glue Catalog and LOAD the data into MySQL
engine = wr.catalog.get_engine("my-mysql-connection")
wr.db.to_sql(df, engine, schema="test", name="my_table")

# Get PostgreSQL connection (SQLAlchemy) from Glue Catalog and LOAD the data into_
↳ PostgreSQL
engine = wr.catalog.get_engine("my-postgresql-connection")
wr.db.to_sql(df, engine, schema="test", name="my_table")
```


READ THE DOCS

1.1 What is AWS Data Wrangler?

An [open-source](#) Python package that extends the power of [Pandas](#) library to AWS connecting **DataFrames** and AWS data related services (**Amazon Redshift**, **AWS Glue**, **Amazon Athena**, **Amazon EMR**, **Amazon QuickSight**, etc).

Built on top of other open-source projects like [Pandas](#), [Apache Arrow](#), [Boto3](#), [s3fs](#), [SQLAlchemy](#), [Psycopg2](#) and [PyMySQL](#), it offers abstracted functions to execute usual ETL tasks like load/unload data from **Data Lakes**, **Data Warehouses** and **Databases**.

Check our [tutorials](#) or the [list of functionalities](#).

1.2 Install

AWS Data Wrangler runs with Python 3.6, 3.7 and 3.8 and on several platforms (AWS Lambda, AWS Glue Python Shell, EMR, EC2, on-premises, Amazon SageMaker, local, etc).

Some good practices for most of the methods bellow are:

- Use new and individual Virtual Environments for each project ([venv](#)).
- On Notebooks, always restart your kernel after installations.

1.2.1 PyPI (pip)

```
>>> pip install awswrangler
```

1.2.2 Conda

```
>>> conda install -c conda-forge awswrangler
```

1.2.3 AWS Lambda Layer

- 1 - Go to [GitHub's release section](#) and download the layer zip related to the desired version.
- 2 - Go to the AWS Lambda Panel, open the layer section (left side) and click **create layer**.
- 3 - Set name and python version, upload your fresh downloaded zip file and press **create** to create the layer.
- 4 - Go to your Lambda and select your new layer!

1.2.4 AWS Glue Wheel

Note: AWS Data Wrangler has compiled dependencies (C/C++) so there is only support for Glue Python Shell, **not** for Glue PySpark.

- 1 - Go to [GitHub's release page](#) and download the wheel file (.whl) related to the desired version.
- 2 - Upload the wheel file to any Amazon S3 location.
- 3 - Go to your Glue Python Shell job and point to the new file on S3.

1.2.5 Amazon SageMaker Notebook

Run this command in any Python 3 notebook paragraph and then make sure to **restart the kernel** before import the **aws wrangler** package.

```
>>> !pip install aws wrangler
```

1.2.6 Amazon SageMaker Notebook Lifecycle

Open SageMaker console, go to the lifecycle section and use the follow snippet to configure AWS Data Wrangler for all compatible SageMaker kernels ([Reference](#)).

```
#!/bin/bash

set -e

# OVERVIEW
# This script installs a single pip package in all SageMaker conda environments,
# apart from the JupyterSystemEnv which
# is a system environment reserved for Jupyter.
# Note this may timeout if the package installations in all environments take longer
# than 5 mins, consider using
# "nohup" to run this as a background process in that case.

sudo -u ec2-user -i <<'EOF'

# PARAMETERS
PACKAGE=aws wrangler

# Note that "base" is special environment name, include it there as well.
for env in base /home/ec2-user/anaconda3/envs/*; do
    source /home/ec2-user/anaconda3/bin/activate $(basename "$env")
```

(continues on next page)

(continued from previous page)

```

if [ $env = 'JupyterSystemEnv' ]; then
    continue
fi
nohup pip install --upgrade "$PACKAGE" &
source /home/ec2-user/anaconda3/bin/deactivate
done
EOF

```

1.2.7 EMR Cluster

Even not being a distributed library, AWS Data Wrangler could be a good helper to complement Big Data pipelines.

- Configure Python 3 as the default interpreter for PySpark under your cluster configuration

```

[
  {
    "Classification": "spark-env",
    "Configurations": [
      {
        "Classification": "export",
        "Properties": {
          "PYSPARK_PYTHON": "/usr/bin/python3"
        }
      }
    ]
  }
]

```

- Keep the bootstrap script above on S3 and reference it on your cluster.

```

#!/usr/bin/env bash
set -ex

sudo pip-3.6 install awswrangler

```

Note: Make sure to freeze the Wrangler version in the bootstrap for productive environments (e.g. `awswrangler==1.0.0`)

1.2.8 From Source

```

>>> git clone https://github.com/aws-labs/aws-data-wrangler.git
>>> cd aws-data-wrangler
>>> pip install .

```

1.3 API Reference

1.3.1 Amazon S3

<code>copy_objects(paths, source_path, target_path)</code>	Copy a list of S3 objects to another S3 directory.
<code>delete_objects(path[, use_threads, ...])</code>	Delete Amazon S3 objects from a received S3 prefix or list of S3 objects paths.
<code>describe_objects(path[, wait_time, ...])</code>	Describe Amazon S3 objects from a received S3 prefix or list of S3 objects paths.
<code>does_object_exist(path[, boto3_session])</code>	Check if object exists on S3.
<code>get_bucket_region(bucket[, boto3_session])</code>	Get bucket region name.
<code>list_directories(path[, boto3_session])</code>	List Amazon S3 objects from a prefix.
<code>list_objects(path[, suffix, boto3_session])</code>	List Amazon S3 objects from a prefix.
<code>merge_datasets(source_path, target_path[, ...])</code>	Merge a source dataset into a target dataset.
<code>read_csv(path[, use_threads, boto3_session, ...])</code>	Read CSV file(s) from from a received S3 prefix or list of S3 objects paths.
<code>read_fwf(path[, use_threads, boto3_session, ...])</code>	Read fixed-width formatted file(s) from from a received S3 prefix or list of S3 objects paths.
<code>read_json(path[, use_threads, ...])</code>	Read JSON file(s) from from a received S3 prefix or list of S3 objects paths.
<code>read_parquet(path[, filters, columns, ...])</code>	Read Apache Parquet file(s) from from a received S3 prefix or list of S3 objects paths.
<code>read_parquet_metadata(path[, dtype, ...])</code>	Read Apache Parquet file(s) metadata from from a received S3 prefix or list of S3 objects paths.
<code>read_parquet_table(table, database[, ...])</code>	Read Apache Parquet table registered on AWS Glue Catalog.
<code>size_objects(path[, wait_time, use_threads, ...])</code>	Get the size (ContentLength) in bytes of Amazon S3 objects from a received S3 prefix or list of S3 objects paths.
<code>store_parquet_metadata(path, database, table)</code>	Infer and store parquet metadata on AWS Glue Catalog.
<code>to_csv(df, path[, sep, index, columns, ...])</code>	Write CSV file or dataset on Amazon S3.
<code>to_json(df, path[, boto3_session, ...])</code>	Write JSON file on Amazon S3.
<code>to_parquet(df, path[, index, compression, ...])</code>	Write Parquet file or dataset on Amazon S3.
<code>wait_objects_exist(paths[, delay, ...])</code>	Wait Amazon S3 objects exist.
<code>wait_objects_not_exist(paths[, delay, ...])</code>	Wait Amazon S3 objects not exist.

aws wrangler.s3.copy_objects

`aws wrangler.s3.copy_objects` (*paths*: *List[str]*, *source_path*: *str*, *target_path*: *str*, *replace_filenames*: *Optional[Dict[str, str]] = None*, *use_threads*: *bool = True*, *boto3_session*: *Optional[boto3.session.Session] = None*) → *List[str]*

Copy a list of S3 objects to another S3 directory.

Note: In case of *use_threads=True* the number of threads that will be spawned will be get from `os.cpu_count()`.

Parameters

- **paths** (*List[str]*) – List of S3 objects paths (e.g. `[s3://bucket/dir0/key0, s3://bucket/dir0/key1]`).

- **source_path** (*str*,) – S3 Path for the source directory.
- **target_path** (*str*,) – S3 Path for the target directory.
- **replace_filenames** (*Dict[str, str]*, *optional*) – e.g. {"old_name.csv": "new_name.csv", "old_name2.csv": "new_name2.csv"}
- **use_threads** (*bool*) – True to enable concurrent requests, False to disable multiple threads. If enabled `os.cpu_count()` will be used as the max number of threads.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if `boto3_session` receive None.

Returns List of new objects paths.

Return type List[str]

Examples

```
>>> import awswrangler as wr
>>> wr.s3.copy_objects(
...     paths=["s3://bucket0/dir0/key0", "s3://bucket0/dir0/key1"])
...     source_path="s3://bucket0/dir0/",
...     target_path="s3://bucket1/dir1/",
... )
["s3://bucket1/dir1/key0", "s3://bucket1/dir1/key1"]
```

awswrangler.s3.delete_objects

`awswrangler.s3.delete_objects` (*path*: Union[str, List[str]], *use_threads*: bool = True, *boto3_session*: Optional[boto3.session.Session] = None) → None

Delete Amazon S3 objects from a received S3 prefix or list of S3 objects paths.

Note: In case of `use_threads=True` the number of threads that will be spawned will be get from `os.cpu_count()`.

Parameters

- **path** (Union[str, List[str]]) – S3 prefix (e.g. `s3://bucket/prefix`) or list of S3 objects paths (e.g. [`s3://bucket/key0`, `s3://bucket/key1`]).
- **use_threads** (*bool*) – True to enable concurrent requests, False to disable multiple threads. If enabled `os.cpu_count()` will be used as the max number of threads.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if `boto3_session` receive None.

Returns None.

Return type None

Examples

```
>>> import awswrangler as wr
>>> wr.s3.delete_objects(['s3://bucket/key0', 's3://bucket/key1']) # Delete both
↳objects
>>> wr.s3.delete_objects('s3://bucket/prefix') # Delete all objects under the
↳received prefix
```

awswrangler.s3.describe_objects

`awswrangler.s3.describe_objects` (*path*: Union[str, List[str]], *wait_time*: Union[int, float, None] = None, *use_threads*: bool = True, *boto3_session*: Optional[boto3.session.Session] = None) → Dict[str, Dict[str, Any]]

Describe Amazon S3 objects from a received S3 prefix or list of S3 objects paths.

Fetch attributes like ContentLength, DeleteMarker, LastModified, ContentType, etc The full list of attributes can be explored under the boto3 head_object documentation: https://boto3.amazonaws.com/v1/documentation/api/latest/reference/services/s3.html#S3.Client.head_object

Note: In case of *use_threads=True* the number of threads that will be spawned will be get from `os.cpu_count()`.

Parameters

- **path** (Union[str, List[str]]) – S3 prefix (e.g. s3://bucket/prefix) or list of S3 objects paths (e.g. [s3://bucket/key0, s3://bucket/key1]).
- **wait_time** (Union[int, float], optional) – How much time (seconds) should Wrangler try to reach this objects. Very useful to overcome eventual consistence issues. *None* means only a single try will be done.
- **use_threads** (bool) – True to enable concurrent requests, False to disable multiple threads. If enabled `os.cpu_count()` will be used as the max number of threads.
- **boto3_session** (boto3.Session(), optional) – Boto3 Session. The default boto3 session will be used if `boto3_session` receive *None*.

Returns Return a dictionary of objects returned from `head_objects` where the key is the object path. The response object can be explored here: https://boto3.amazonaws.com/v1/documentation/api/latest/reference/services/s3.html#S3.Client.head_object

Return type Dict[str, Dict[str, Any]]

Examples

```
>>> import awswrangler as wr
>>> descs0 = wr.s3.describe_objects(['s3://bucket/key0', 's3://bucket/key1']) #
↳Describe both objects
>>> descs1 = wr.s3.describe_objects('s3://bucket/prefix') # Describe all objects
↳under the prefix
>>> descs2 = wr.s3.describe_objects('s3://bucket/prefix', wait_time=30) #
↳Overcoming eventual consistence issues
```

aws wrangler.s3.does_object_exist

`aws wrangler.s3.does_object_exist` (*path: str, boto3_session: Optional[boto3.session.Session] = None*) → bool

Check if object exists on S3.

Parameters

- **path** (*str*) – S3 path (e.g. `s3://bucket/key`).
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if `boto3_session` receive None.

Returns True if exists, False otherwise.

Return type bool

Examples

Using the default boto3 session

```
>>> import aws wrangler as wr
>>> wr.s3.does_object_exist('s3://bucket/key_real')
True
>>> wr.s3.does_object_exist('s3://bucket/key_unreal')
False
```

Using a custom boto3 session

```
>>> import boto3
>>> import aws wrangler as wr
>>> wr.s3.does_object_exist('s3://bucket/key_real', boto3_session=boto3.Session())
True
>>> wr.s3.does_object_exist('s3://bucket/key_unreal', boto3_session=boto3.
↳ Session())
False
```

aws wrangler.s3.get_bucket_region

`aws wrangler.s3.get_bucket_region` (*bucket: str, boto3_session: Optional[boto3.session.Session] = None*) → str

Get bucket region name.

Parameters

- **bucket** (*str*) – Bucket name.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if `boto3_session` receive None.

Returns Region code (e.g. 'us-east-1').

Return type str

Examples

Using the default boto3 session

```
>>> import awswrangler as wr
>>> region = wr.s3.get_bucket_region('bucket-name')
```

Using a custom boto3 session

```
>>> import boto3
>>> import awswrangler as wr
>>> region = wr.s3.get_bucket_region('bucket-name', boto3_session=boto3.Session())
```

awswrangler.s3.list_directories

`awswrangler.s3.list_directories` (*path: str, boto3_session: Optional[boto3.session.Session] = None*) → List[str]

List Amazon S3 objects from a prefix.

Parameters

- **path** (*str*) – S3 path (e.g. `s3://bucket/prefix`).
- **boto3_session** (*boto3.Session(), optional*) – Boto3 Session. The default boto3 session will be used if `boto3_session` receive `None`.

Returns List of objects paths.

Return type List[str]

Examples

Using the default boto3 session

```
>>> import awswrangler as wr
>>> wr.s3.list_objects('s3://bucket/prefix/')
['s3://bucket/prefix/dir0', 's3://bucket/prefix/dir1', 's3://bucket/prefix/dir2']
```

Using a custom boto3 session

```
>>> import boto3
>>> import awswrangler as wr
>>> wr.s3.list_objects('s3://bucket/prefix/', boto3_session=boto3.Session())
['s3://bucket/prefix/dir0', 's3://bucket/prefix/dir1', 's3://bucket/prefix/dir2']
```

awswrangler.s3.list_objects

`awswrangler.s3.list_objects` (*path: str, suffix: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None*) → List[str]

List Amazon S3 objects from a prefix.

Parameters

- **path** (*str*) – S3 path (e.g. `s3://bucket/prefix`).
- **suffix** (*str, optional*) – Suffix for filtering S3 keys.

- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns List of objects paths.

Return type List[str]

Examples

Using the default boto3 session

```
>>> import awswrangler as wr
>>> wr.s3.list_objects('s3://bucket/prefix')
['s3://bucket/prefix0', 's3://bucket/prefix1', 's3://bucket/prefix2']
```

Using a custom boto3 session

```
>>> import boto3
>>> import awswrangler as wr
>>> wr.s3.list_objects('s3://bucket/prefix', boto3_session=boto3.Session())
['s3://bucket/prefix0', 's3://bucket/prefix1', 's3://bucket/prefix2']
```

awswrangler.s3.merge_datasets

`awswrangler.s3.merge_datasets` (*source_path: str, target_path: str, mode: str = 'append', use_threads: bool = True, boto3_session: Optional[boto3.session.Session] = None*) → List[str]

Merge a source dataset into a target dataset.

Note: If you are merging tables (S3 datasets + Glue Catalog metadata), remember that you will also need to update your partitions metadata in some cases. (e.g. `wr.athena.repair_table(table='...', database='...')`)

Note: In case of `use_threads=True` the number of threads that will be spawned will be get from `os.cpu_count()`.

Parameters

- **source_path** (*str*,) – S3 Path for the source directory.
- **target_path** (*str*,) – S3 Path for the target directory.
- **mode** (*str, optional*) – `append` (Default), `overwrite`, `overwrite_partitions`.
- **use_threads** (*bool*) – True to enable concurrent requests, False to disable multiple threads. If enabled `os.cpu_count()` will be used as the max number of threads.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns List of new objects paths.

Return type List[str]

Examples

```
>>> import awswrangler as wr
>>> wr.s3.merge_datasets(
...     source_path="s3://bucket0/dir0/",
...     target_path="s3://bucket1/dir1/",
...     mode="append"
... )
["s3://bucket1/dir1/key0", "s3://bucket1/dir1/key1"]
```

awswrangler.s3.read_csv

`awswrangler.s3.read_csv` (*path*: Union[str, List[str]], *use_threads*: bool = True, *boto3_session*: Optional[boto3.session.Session] = None, *s3_additional_kwargs*: Optional[Dict[str, str]] = None, *chunksize*: Optional[int] = None, *dataset*: bool = False, ***pandas_kwargs*) → Union[pandas.core.frame.DataFrame, Iterator[pandas.core.frame.DataFrame]]

Read CSV file(s) from from a received S3 prefix or list of S3 objects paths.

Note: For partial and gradual reading use the argument `chunksize` instead of `iterator`.

Note: In case of `use_threads=True` the number of threads that will be spawned will be get from `os.cpu_count()`.

Parameters

- **path** (Union[str, List[str]]) – S3 prefix (e.g. `s3://bucket/prefix`) or list of S3 objects paths (e.g. `[s3://bucket/key0, s3://bucket/key1]`).
- **use_threads** (bool) – True to enable concurrent requests, False to disable multiple threads. If enabled `os.cpu_count()` will be used as the max number of threads.
- **boto3_session** (boto3.Session(), optional) – Boto3 Session. The default boto3 session will be used if `boto3_session` receive None.
- **s3_additional_kwargs** – Forward to s3fs, useful for server side encryption <https://s3fs.readthedocs.io/en/latest/#serverside-encryption>
- **chunksize** (int, optional) – If specified, return an generator where chunksize is the number of rows to include in each chunk.
- **dataset** (bool) – If `True` read a CSV dataset instead of simple file(s) loading all the related partitions as columns.
- **pandas_kwargs** – keyword arguments forwarded to `pandas.read_csv()`. https://pandas.pydata.org/pandas-docs/stable/reference/api/pandas.read_csv.html

Returns Pandas DataFrame or a Generator in case of `chunksize != None`.

Return type Union[pandas.DataFrame, Generator[pandas.DataFrame, None, None]]

Examples

Reading all CSV files under a prefix

```
>>> import awswrangler as wr
>>> df = wr.s3.read_csv(path='s3://bucket/prefix/')
```

Reading all CSV files under a prefix encrypted with a KMS key

```
>>> import awswrangler as wr
>>> df = wr.s3.read_csv(
...     path='s3://bucket/prefix/',
...     s3_additional_kwargs={
...         'ServerSideEncryption': 'aws:kms',
...         'SSEKMSKeyId': 'YOUR_KMY_KEY_ARN'
...     }
... )
```

Reading all CSV files from a list

```
>>> import awswrangler as wr
>>> df = wr.s3.read_csv(path=['s3://bucket/filename0.csv', 's3://bucket/filename1.
↪ csv'])
```

Reading in chunks of 100 lines

```
>>> import awswrangler as wr
>>> dfs = wr.s3.read_csv(path=['s3://bucket/filename0.csv', 's3://bucket/
↪ filename1.csv'], chunksize=100)
>>> for df in dfs:
>>>     print(df) # 100 lines Pandas DataFrame
```

awswrangler.s3.read_fwf

`awswrangler.s3.read_fwf` (*path*: Union[str, List[str]], *use_threads*: bool = True, *boto3_session*: Optional[boto3.session.Session] = None, *s3_additional_kwargs*: Optional[Dict[str, str]] = None, *chunksize*: Optional[int] = None, *dataset*: bool = False, ***pandas_kwargs*) → Union[pandas.core.frame.DataFrame, Iterator[pandas.core.frame.DataFrame]]

Read fixed-width formatted file(s) from a received S3 prefix or list of S3 objects paths.

Note: For partial and gradual reading use the argument `chunksize` instead of `iterator`.

Note: In case of `use_threads=True` the number of threads that will be spawned will be get from `os.cpu_count()`.

Parameters

- **path** (Union[str, List[str]]) – S3 prefix (e.g. `s3://bucket/prefix`) or list of S3 objects paths (e.g. `[s3://bucket/key0, s3://bucket/key1]`).
- **use_threads** (bool) – True to enable concurrent requests, False to disable multiple threads. If enabled `os.cpu_count()` will be used as the max number of threads.

- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if `boto3_session` receive `None`.
- **s3_additional_kwargs** – Forward to `s3fs`, useful for server side encryption <https://s3fs.readthedocs.io/en/latest/#serverside-encryption>
- **chunksize** (*int*, *optional*) – If specified, return an generator where `chunksize` is the number of rows to include in each chunk.
- **dataset** (*bool*) – If `True` read a FWF dataset instead of simple file(s) loading all the related partitions as columns.
- **pandas_kwargs** – keyword arguments forwarded to `pandas.read_fwf()`. https://pandas.pydata.org/pandas-docs/stable/reference/api/pandas.read_fwf.html

Returns Pandas DataFrame or a Generator in case of `chunksize != None`.

Return type Union[pandas.DataFrame, Generator[pandas.DataFrame, None, None]]

Examples

Reading all fixed-width formatted (FWF) files under a prefix

```
>>> import awswrangler as wr
>>> df = wr.s3.read_fwf(path='s3://bucket/prefix/')
```

Reading all fixed-width formatted (FWF) files under a prefix encrypted with a KMS key

```
>>> import awswrangler as wr
>>> df = wr.s3.read_fwf(
...     path='s3://bucket/prefix/',
...     s3_additional_kwargs={
...         'ServerSideEncryption': 'aws:kms',
...         'SSEKMSKeyId': 'YOUR_KMY_KEY_ARN'
...     }
... )
```

Reading all fixed-width formatted (FWF) files from a list

```
>>> import awswrangler as wr
>>> df = wr.s3.read_fwf(path=['s3://bucket/filename0.txt', 's3://bucket/filename1.
↪txt'])
```

Reading in chunks of 100 lines

```
>>> import awswrangler as wr
>>> dfs = wr.s3.read_fwf(path=['s3://bucket/filename0.txt', 's3://bucket/
↪filename1.txt'], chunksize=100)
>>> for df in dfs:
>>>     print(df) # 100 lines Pandas DataFrame
```

aws wrangler.s3.read_json

```
aws wrangler.s3.read_json(path: Union[str, List[str]], use_threads: bool = True,
                           boto3_session: Optional[boto3.session.Session] = None,
                           s3_additional_kwargs: Optional[Dict[str, str]] = None, chunksize: Optional[int] = None, dataset: bool = False, **pandas_kwargs) → Union[pandas.core.frame.DataFrame, Iterator[pandas.core.frame.DataFrame]]
```

Read JSON file(s) from from a received S3 prefix or list of S3 objects paths.

Note: For partial and gradual reading use the argument `chunksize` instead of `iterator`.

Note: In case of `use_threads=True` the number of threads that will be spawned will be get from `os.cpu_count()`.

Parameters

- **path** (`Union[str, List[str]]`) – S3 prefix (e.g. `s3://bucket/prefix`) or list of S3 objects paths (e.g. `[s3://bucket/key0, s3://bucket/key1]`).
- **use_threads** (`bool`) – True to enable concurrent requests, False to disable multiple threads. If enabled `os.cpu_count()` will be used as the max number of threads.
- **boto3_session** (`boto3.Session()`, *optional*) – Boto3 Session. The default boto3 session will be used if `boto3_session` receive None.
- **s3_additional_kwargs** – Forward to s3fs, useful for server side encryption <https://s3fs.readthedocs.io/en/latest/#serverside-encryption>
- **chunksize** (`int`, *optional*) – If specified, return an generator where chunksize is the number of rows to include in each chunk.
- **dataset** (`bool`) – If `True` read a JSON dataset instead of simple file(s) loading all the related partitions as columns. If `True`, the `lines=True` will be assumed by default.
- **pandas_kwargs** – keyword arguments forwarded to `pandas.read_json()`. https://pandas.pydata.org/pandas-docs/stable/reference/api/pandas.read_json.html

Returns Pandas DataFrame or a Generator in case of `chunksize != None`.

Return type Union[pandas.DataFrame, Generator[pandas.DataFrame, None, None]]

Examples

Reading all JSON files under a prefix

```
>>> import aws wrangler as wr
>>> df = wr.s3.read_json(path='s3://bucket/prefix/')
```

Reading all JSON files under a prefix encrypted with a KMS key

```
>>> import aws wrangler as wr
>>> df = wr.s3.read_json(
...     path='s3://bucket/prefix/',
...     s3_additional_kwargs={
...         'ServerSideEncryption': 'aws:kms',
```

(continues on next page)

(continued from previous page)

```
...     'SSEKMSKeyId': 'YOUR_KMY_KEY_ARN'
...   }
... )
```

Reading all JSON files from a list

```
>>> import awswrangler as wr
>>> df = wr.s3.read_json(path=['s3://bucket/filename0.json', 's3://bucket/
↳ filename1.json'])
```

Reading in chunks of 100 lines

```
>>> import awswrangler as wr
>>> dfs = wr.s3.read_json(path=['s3://bucket/filename0.json', 's3://bucket/
↳ filename1.json'], chunksize=100)
>>> for df in dfs:
>>>     print(df) # 100 lines Pandas DataFrame
```

awswrangler.s3.read_parquet

```
awswrangler.s3.read_parquet(path: Union[str, List[str]], filters: Union[List[Tuple],
List[List[Tuple]], None] = None, columns: Optional[List[str]] = None, validate_schema: bool = True,
chunked: Union[bool, int] = False, dataset: bool = False, categories: List[str] = None, use_threads: bool =
True, boto3_session: Optional[boto3.session.Session] = None, s3_additional_kwargs: Optional[Dict[str, str]]
= None) → Union[pandas.core.frame.DataFrame, Iterator[pandas.core.frame.DataFrame]]
```

Read Apache Parquet file(s) from a received S3 prefix or list of S3 objects paths.

The concept of Dataset goes beyond the simple idea of files and enable more complex features like partitioning and catalog integration (AWS Glue Catalog).

Note: Batching (*chunked* argument) (Memory Friendly):

Will enable the function to return a Iterable of DataFrames instead of a regular DataFrame.

There are two batching strategies on Wrangler:

- If **chunked=True**, a new DataFrame will be returned for each file in your path/dataset.
- If **chunked=INTEGER**, Wrangler will iterate on the data by number of rows equal the received INTEGER.

P.S. chunked=True is faster and uses less memory while *chunked=INTEGER* is more precise in number of rows for each DataFrame.

Note: In case of *use_threads=True* the number of threads that will be spawned will be get from `os.cpu_count()`.

Parameters

- **path** (*Union[str, List[str]]*) – S3 prefix (e.g. `s3://bucket/prefix`) or list of S3 objects paths (e.g. `[s3://bucket/key0, s3://bucket/key1]`).

- **filters** (*Union[List[Tuple], List[List[Tuple]]*, *optional*) – List of filters to apply on PARTITION columns (PUSH-DOWN filter), like `[['x', '=', 0], ...]`. Ignored if `dataset=False`.
- **columns** (*List[str]*, *optional*) – Names of columns to read from the file(s).
- **validate_schema** – Check that individual file schemas are all the same / compatible. Schemas within a folder prefix should all be the same. Disable if you have schemas that are different and want to disable this check.
- **chunked** (*Union[int, bool]*) – If passed will split the data in a Iterable of DataFrames (Memory friendly). If `True` wrangler will iterate on the data by files in the most efficient way without guarantee of chunksize. If an `INTEGER` is passed Wrangler will iterate on the data by number of rows igual the received `INTEGER`.
- **dataset** (*bool*) – If `True` read a parquet dataset instead of simple file(s) loading all the related partitions as columns.
- **categories** (*List[str]*, *optional*) – List of columns names that should be returned as `pandas.Categorical`. Recommended for memory restricted environments.
- **use_threads** (*bool*) – True to enable concurrent requests, False to disable multiple threads. If enabled `os.cpu_count()` will be used as the max number of threads.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if `boto3_session` receive `None`.
- **s3_additional_kwargs** – Forward to s3fs, useful for server side encryption <https://s3fs.readthedocs.io/en/latest/#serverside-encryption>

Returns Pandas DataFrame or a Generator in case of `chunked=True`.

Return type `Union[pandas.DataFrame, Generator[pandas.DataFrame, None, None]]`

Examples

Reading all Parquet files under a prefix

```
>>> import awswrangler as wr
>>> df = wr.s3.read_parquet(path='s3://bucket/prefix/')
```

Reading all Parquet files under a prefix encrypted with a KMS key

```
>>> import awswrangler as wr
>>> df = wr.s3.read_parquet(
...     path='s3://bucket/prefix/',
...     s3_additional_kwargs={
...         'ServerSideEncryption': 'aws:kms',
...         'SSEKMSKeyId': 'YOUR_KMY_KEY_ARN'
...     }
... )
```

Reading all Parquet files from a list

```
>>> import awswrangler as wr
>>> df = wr.s3.read_parquet(path=['s3://bucket/filename0.parquet', 's3://bucket/
↪filename1.parquet'])
```

Reading in chunks (Chunk by file)

```
>>> import awswrangler as wr
>>> dfs = wr.s3.read_parquet(path=['s3://bucket/filename0.csv', 's3://bucket/
↳ filename1.csv'], chunked=True)
>>> for df in dfs:
>>>     print(df) # Smaller Pandas DataFrame
```

Reading in chunks (Chunk by 1MM rows)

```
>>> import awswrangler as wr
>>> dfs = wr.s3.read_parquet(path=['s3://bucket/filename0.csv', 's3://bucket/
↳ filename1.csv'], chunked=1_000_000)
>>> for df in dfs:
>>>     print(df) # 1MM Pandas DataFrame
```

awswrangler.s3.read_parquet_metadata

`awswrangler.s3.read_parquet_metadata` (*path*: Union[str, List[str]], *dtype*: Optional[Dict[str, str]] = None, *sampling*: float = 1.0, *dataset*: bool = False, *use_threads*: bool = True, *boto3_session*: Optional[boto3.session.Session] = None) → Tuple[Dict[str, str], Optional[Dict[str, str]]]

Read Apache Parquet file(s) metadata from from a received S3 prefix or list of S3 objects paths.

The concept of Dataset goes beyond the simple idea of files and enable more complex features like partitioning and catalog integration (AWS Glue Catalog).

Note: In case of *use_threads=True* the number of threads that will be spawned will be get from `os.cpu_count()`.

Parameters

- **path** (Union[str, List[str]]) – S3 prefix (e.g. s3://bucket/prefix) or list of S3 objects paths (e.g. [s3://bucket/key0, s3://bucket/key1]).
- **dtype** (Dict[str, str], optional) – Dictionary of columns names and Athena/Glue types to be casted. Useful when you have columns with undetermined data types as partitions columns. (e.g. {'col name': 'bigint', 'col2 name': 'int'})
- **sampling** (float) – Random sample ratio of files that will have the metadata inspected. Must be $0.0 < sampling \leq 1.0$. The higher, the more accurate. The lower, the faster.
- **dataset** (bool) – If True read a parquet dataset instead of simple file(s) loading all the related partitions as columns.
- **use_threads** (bool) – True to enable concurrent requests, False to disable multiple threads. If enabled `os.cpu_count()` will be used as the max number of threads.
- **boto3_session** (boto3.Session(), optional) – Boto3 Session. The default boto3 session will be used if `boto3_session` receive None.

Returns `columns_types`: Dictionary with keys as column names and vales as data types (e.g. {'col0': 'bigint', 'col1': 'double'}). / `partitions_types`: Dictionary with keys as partition names and values as data types (e.g. {'col2': 'date'}).

Return type Tuple[Dict[str, str], Optional[Dict[str, str]]]

Examples

Reading all Parquet files (with partitions) metadata under a prefix

```
>>> import awswrangler as wr
>>> columns_types, partitions_types = wr.s3.read_parquet_metadata(path='s3://
↳bucket/prefix/', dataset=True)
```

Reading all Parquet files metadata from a list

```
>>> import awswrangler as wr
>>> columns_types, partitions_types = wr.s3.read_parquet_metadata(path=[
...     's3://bucket/filename0.parquet',
...     's3://bucket/filename1.parquet'
... ])
```

awswrangler.s3.read_parquet_table

```
awswrangler.s3.read_parquet_table(table: str, database: str, filters: Union[List[Tuple],
List[List[Tuple]], None] = None, columns: Optional[List[str]] = None, categories: List[str] = None,
chunked: Union[bool, int] = False, use_threads: bool = True, boto3_session: Optional[boto3.session.Session]
= None, s3_additional_kwargs: Optional[Dict[str, str]] = None) → Union[pandas.core.frame.DataFrame, Iterator[pandas.core.frame.DataFrame]]
```

Read Apache Parquet table registered on AWS Glue Catalog.

Note: Batching (*chunked* argument) (Memory Friendly):

Will enable the function to return a Iterable of DataFrames instead of a regular DataFrame.

There are two batching strategies on Wrangler:

- If **chunked=True**, a new DataFrame will be returned for each file in your path/dataset.
- If **chunked=INTEGER**, Wrangler will paginate through files slicing and concatenating to return DataFrames with the number of row equal the received INTEGER.

P.S. chunked=True if faster and uses less memory while *chunked=INTEGER* is more precise in number of rows for each DataFrame.

Note: In case of *use_threads=True* the number of threads that will be spawned will be get from `os.cpu_count()`.

Parameters

- **table** (*str*) – AWS Glue Catalog table name.
- **database** (*str*) – AWS Glue Catalog database name.
- **filters** (*Union[List[Tuple], List[List[Tuple]], optional*) – List of filters to apply, like `[('x', '=', 0), ...]`.
- **columns** (*List[str], optional*) – Names of columns to read from the file(s).

- **categories** (*List[str], optional*) – List of columns names that should be returned as `pandas.Categorical`. Recommended for memory restricted environments.
- **chunked** (*bool*) – If `True` will break the data in smaller DataFrames (Non deterministic number of lines). Otherwise return a single DataFrame with the whole data.
- **use_threads** (*bool*) – `True` to enable concurrent requests, `False` to disable multiple threads. If enabled `os.cpu_count()` will be used as the max number of threads.
- **boto3_session** (*boto3.Session(), optional*) – Boto3 Session. The default boto3 session will be used if `boto3_session` receive `None`.
- **s3_additional_kwargs** – Forward to s3fs, useful for server side encryption <https://s3fs.readthedocs.io/en/latest/#serverside-encryption>

Returns Pandas DataFrame or a Generator in case of `chunked=True`.

Return type Union[pandas.DataFrame, Generator[pandas.DataFrame, None, None]]

Examples

Reading Parquet Table

```
>>> import awswrangler as wr
>>> df = wr.s3.read_parquet_table(database='...', table='...')
```

Reading Parquet Table encrypted

```
>>> import awswrangler as wr
>>> df = wr.s3.read_parquet_table(
...     database='...',
...     table='...'
...     s3_additional_kwargs={
...         'ServerSideEncryption': 'aws:kms',
...         'SSEKMSKeyId': 'YOUR_KMY_KEY_ARN'
...     }
... )
```

Reading Parquet Table in chunks (Chunk by file)

```
>>> import awswrangler as wr
>>> dfs = wr.s3.read_parquet_table(database='...', table='...', chunked=True)
>>> for df in dfs:
>>>     print(df) # Smaller Pandas DataFrame
```

Reading in chunks (Chunk by 1MM rows)

```
>>> import awswrangler as wr
>>> dfs = wr.s3.read_parquet(path=['s3://bucket/filename0.csv', 's3://bucket/
↪filename1.csv'], chunked=1_000_000)
>>> for df in dfs:
>>>     print(df) # 1MM Pandas DataFrame
```


aws wrangler.s3.size_objects

`aws wrangler.s3.size_objects` (*path*: Union[str, List[str]], *wait_time*: Union[int, float, None] = None, *use_threads*: bool = True, *boto3_session*: Optional[boto3.session.Session] = None) → Dict[str, Optional[int]]

Get the size (ContentLength) in bytes of Amazon S3 objects from a received S3 prefix or list of S3 objects paths.

Note: In case of *use_threads=True* the number of threads that will be spawned will be get from `os.cpu_count()`.

Parameters

- **path** (Union[str, List[str]]) – S3 prefix (e.g. `s3://bucket/prefix`) or list of S3 objects paths (e.g. [`s3://bucket/key0`, `s3://bucket/key1`]).
- **wait_time** (Union[int, float], optional) – How much time (seconds) should Wrangler try to reach this objects. Very useful to overcome eventual consistence issues. *None* means only a single try will be done.
- **use_threads** (bool) – True to enable concurrent requests, False to disable multiple threads. If enabled `os.cpu_count()` will be used as the max number of threads.
- **boto3_session** (boto3.Session(), optional) – Boto3 Session. The default boto3 session will be used if *boto3_session* receive *None*.

Returns Dictionary where the key is the object path and the value is the object size.

Return type Dict[str, Optional[int]]

Examples

```
>>> import aws wrangler as wr
>>> sizes0 = wr.s3.size_objects(['s3://bucket/key0', 's3://bucket/key1']) # Get
↳ the sizes of both objects
>>> sizes1 = wr.s3.size_objects('s3://bucket/prefix') # Get the sizes of all
↳ objects under the received prefix
>>> sizes2 = wr.s3.size_objects('s3://bucket/prefix', wait_time=30) # Overcoming
↳ eventual consistence issues
```

aws wrangler.s3.store_parquet_metadata

```
aws wrangler.s3.store_parquet_metadata (path: str, database: str, table: str, dtype: Optional[Dict[str, str]] = None, sampling: float = 1.0, dataset: bool = False, use_threads: bool = True, description: Optional[str] = None, parameters: Optional[Dict[str, str]] = None, columns_comments: Optional[Dict[str, str]] = None, compression: Optional[str] = None, mode: str = 'overwrite', catalog_versioning: bool = False, regular_partitions: bool = True, projection_enabled: bool = False, projection_types: Optional[Dict[str, str]] = None, projection_ranges: Optional[Dict[str, str]] = None, projection_values: Optional[Dict[str, str]] = None, projection_intervals: Optional[Dict[str, str]] = None, projection_digits: Optional[Dict[str, str]] = None, boto3_session: Optional[boto3.session.Session] = None) → Tuple[Dict[str, str], Optional[Dict[str, str]], Optional[Dict[str, List[str]]]]
```

Infer and store parquet metadata on AWS Glue Catalog.

Infer Apache Parquet file(s) metadata from from a received S3 prefix or list of S3 objects paths And then stores it on AWS Glue Catalog including all inferred partitions (No need of 'MCSK REPAIR TABLE')

The concept of Dataset goes beyond the simple idea of files and enable more complex features like partitioning and catalog integration (AWS Glue Catalog).

Note: On *append* mode, the *parameters* will be upsert on an existing table.

Note: In case of *use_threads=True* the number of threads that will be spawned will be get from *os.cpu_count()*.

Parameters

- **path** (*Union[str, List[str]]*) – S3 prefix (e.g. *s3://bucket/prefix*) or list of S3 objects paths (e.g. [*s3://bucket/key0*, *s3://bucket/key1*]).
- **database** (*str*) – Glue/Athena catalog: Database name.
- **table** (*str*) – Glue/Athena catalog: Table name.
- **dtype** (*Dict[str, str], optional*) – Dictionary of columns names and Athena/Glue types to be casted. Useful when you have columns with undetermined data types as partitions columns. (e.g. {'col name': 'bigint', 'col2 name': 'int'})
- **sampling** (*float*) – Random sample ratio of files that will have the metadata inspected. Must be *0.0 < sampling <= 1.0*. The higher, the more accurate. The lower, the faster.
- **dataset** (*bool*) – If True read a parquet dataset instead of simple file(s) loading all the related partitions as columns.
- **use_threads** (*bool*) – True to enable concurrent requests, False to disable multiple threads. If enabled *os.cpu_count()* will be used as the max number of threads.
- **description** (*str, optional*) – Glue/Athena catalog: Table description
- **parameters** (*Dict[str, str], optional*) – Glue/Athena catalog: Key/value pairs to tag the table.

- **columns_comments** (*Dict[str, str], optional*) – Glue/Athena catalog: Columns names and the related comments (e.g. {'col0': 'Column 0.', 'col1': 'Column 1.', 'col2': 'Partition.'}).
- **compression** (*str, optional*) – Compression style (None, snappy, gzip, etc).
- **mode** (*str*) – 'overwrite' to recreate any possible existing table or 'append' to keep any possible existing table.
- **catalog_versioning** (*bool*) – If True and *mode*="overwrite", creates an archived version of the table catalog before updating it.
- **regular_partitions** (*bool*) – Create regular partitions (Non projected partitions) on Glue Catalog. Disable when you will work only with Partition Projection. Keep enabled even when working with projections is useful to keep Redshift Spectrum working with the regular partitions.
- **projection_enabled** (*bool*) – Enable Partition Projection on Athena (<https://docs.aws.amazon.com/athena/latest/ug/partition-projection.html>)
- **projection_types** (*Optional[Dict[str, str]]*) – Dictionary of partitions names and Athena projections types. Valid types: "enum", "integer", "date", "injected" <https://docs.aws.amazon.com/athena/latest/ug/partition-projection-supported-types.html> (e.g. {'col_name': 'enum', 'col2_name': 'integer'})
- **projection_ranges** (*Optional[Dict[str, str]]*) – Dictionary of partitions names and Athena projections ranges. <https://docs.aws.amazon.com/athena/latest/ug/partition-projection-supported-types.html> (e.g. {'col_name': '0,10', 'col2_name': '-1,8675309'})
- **projection_values** (*Optional[Dict[str, str]]*) – Dictionary of partitions names and Athena projections values. <https://docs.aws.amazon.com/athena/latest/ug/partition-projection-supported-types.html> (e.g. {'col_name': 'A,B,Unknown', 'col2_name': 'foo,boo,bar'})
- **projection_intervals** (*Optional[Dict[str, str]]*) – Dictionary of partitions names and Athena projections intervals. <https://docs.aws.amazon.com/athena/latest/ug/partition-projection-supported-types.html> (e.g. {'col_name': '1', 'col2_name': '5'})
- **projection_digits** (*Optional[Dict[str, str]]*) – Dictionary of partitions names and Athena projections digits. <https://docs.aws.amazon.com/athena/latest/ug/partition-projection-supported-types.html> (e.g. {'col_name': '1', 'col2_name': '2'})
- **boto3_session** (*boto3.Session(), optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns The metadata used to create the Glue Table. *columns_types*: Dictionary with keys as column names and vales as data types (e.g. {'col0': 'bigint', 'col1': 'double'}). / *partitions_types*: Dictionary with keys as partition names and values as data types (e.g. {'col2': 'date'}). / *partitions_values*: Dictionary with keys as S3 path locations and values as a list of partitions values as str (e.g. {'s3://bucket/prefix/y=2020/m=10/': ['2020', '10']}).

Return type Tuple[Dict[str, str], Optional[Dict[str, str]], Optional[Dict[str, List[str]]]]

Examples

Reading all Parquet files metadata under a prefix

```
>>> import awswrangler as wr
>>> columns_types, partitions_types, partitions_values = wr.s3.store_parquet_
↳ metadata(
...     path='s3://bucket/prefix/',
...     database='...',
...     table='...',
...     dataset=True
... )
```

awswrangler.s3.to_csv

`awswrangler.s3.to_csv` (*df*: `pandas.core.frame.DataFrame`, *path*: `str`, *sep*: `str` = `'`, *index*: `bool` = `True`, *columns*: `Optional[List[str]]` = `None`, *use_threads*: `bool` = `True`, *boto3_session*: `Optional[boto3.session.Session]` = `None`, *s3_additional_kwargs*: `Optional[Dict[str, str]]` = `None`, *sanitize_columns*: `bool` = `False`, *dataset*: `bool` = `False`, *partition_cols*: `Optional[List[str]]` = `None`, *mode*: `Optional[str]` = `None`, *catalog_versioning*: `bool` = `False`, *database*: `Optional[str]` = `None`, *table*: `Optional[str]` = `None`, *dtype*: `Optional[Dict[str, str]]` = `None`, *description*: `Optional[str]` = `None`, *parameters*: `Optional[Dict[str, str]]` = `None`, *columns_comments*: `Optional[Dict[str, str]]` = `None`, *regular_partitions*: `bool` = `True`, *projection_enabled*: `bool` = `False`, *projection_types*: `Optional[Dict[str, str]]` = `None`, *projection_ranges*: `Optional[Dict[str, str]]` = `None`, *projection_values*: `Optional[Dict[str, str]]` = `None`, *projection_intervals*: `Optional[Dict[str, str]]` = `None`, *projection_digits*: `Optional[Dict[str, str]]` = `None`, ***pandas_kwargs*) → `Dict[str, Union[List[str], Dict[str, List[str]]]]`

Write CSV file or dataset on Amazon S3.

The concept of Dataset goes beyond the simple idea of files and enable more complex features like partitioning, casting and catalog integration (Amazon Athena/AWS Glue Catalog).

Note: If *dataset=True* The table name and all column names will be automatically sanitized using *wr.catalog.sanitize_table_name* and *wr.catalog.sanitize_column_name*. Please, pass *sanitize_columns=True* to force the same behaviour for *dataset=False*.

Note: On *append* mode, the *parameters* will be upsert on an existing table.

Note: In case of *use_threads=True* the number of threads that will be spawned will be get from `os.cpu_count()`.

Parameters

- **df** (`pandas.DataFrame`) – Pandas DataFrame <https://pandas.pydata.org/pandas-docs/stable/reference/api/pandas.DataFrame.html>
- **path** (`str`) – Amazon S3 path (e.g. `s3://bucket/filename.csv`).
- **sep** (`str`) – String of length 1. Field delimiter for the output file.

- **index** (*bool*) – Write row names (index).
- **columns** (*List[str], optional*) – Columns to write.
- **use_threads** (*bool*) – True to enable concurrent requests, False to disable multiple threads. If enabled `os.cpu_count()` will be used as the max number of threads.
- **boto3_session** (*boto3.Session(), optional*) – Boto3 Session. The default boto3 Session will be used if `boto3_session` receive None.
- **s3_additional_kwargs** – Forward to s3fs, useful for server side encryption <https://s3fs.readthedocs.io/en/latest/#serverside-encryption>
- **sanitize_columns** (*bool*) – True to sanitize columns names or False to keep it as is. True value is forced if `dataset=True`.
- **dataset** (*bool*) – If True store a parquet dataset instead of a single file. If True, enable all follow arguments: `partition_cols`, `mode`, `database`, `table`, `description`, `parameters`, `columns_comments`, .
- **partition_cols** (*List[str], optional*) – List of column names that will be used to create partitions. Only takes effect if `dataset=True`.
- **mode** (*str, optional*) – `append` (Default), `overwrite`, `overwrite_partitions`. Only takes effect if `dataset=True`.
- **catalog_versioning** (*bool*) – If True and `mode="overwrite"`, creates an archived version of the table catalog before updating it.
- **database** (*str, optional*) – Glue/Athena catalog: Database name.
- **table** (*str, optional*) – Glue/Athena catalog: Table name.
- **dtype** (*Dict[str, str], optional*) – Dictionary of columns names and Athena/Glue types to be casted. Useful when you have columns with undetermined or mixed data types. (e.g. `{'col name': 'bigint', 'col2 name': 'int'}`)
- **description** (*str, optional*) – Glue/Athena catalog: Table description
- **parameters** (*Dict[str, str], optional*) – Glue/Athena catalog: Key/value pairs to tag the table.
- **columns_comments** (*Dict[str, str], optional*) – Glue/Athena catalog: Columns names and the related comments (e.g. `{'col0': 'Column 0.', 'col1': 'Column 1.', 'col2': 'Partition.'}`).
- **regular_partitions** (*bool*) – Create regular partitions (Non projected partitions) on Glue Catalog. Disable when you will work only with Partition Projection. Keep enabled even when working with projections is useful to keep Redshift Spectrum working with the regular partitions.
- **projection_enabled** (*bool*) – Enable Partition Projection on Athena (<https://docs.aws.amazon.com/athena/latest/ug/partition-projection.html>)
- **projection_types** (*Optional[Dict[str, str]]*) – Dictionary of partitions names and Athena projections types. Valid types: `"enum"`, `"integer"`, `"date"`, `"injected"` <https://docs.aws.amazon.com/athena/latest/ug/partition-projection-supported-types.html> (e.g. `{'col_name': 'enum', 'col2_name': 'integer'}`)
- **projection_ranges** (*Optional[Dict[str, str]]*) – Dictionary of partitions names and Athena projections ranges. <https://docs.aws.amazon.com/athena/latest/ug/partition-projection-supported-types.html> (e.g. `{'col_name': '0,10', 'col2_name': '-1,8675309'}`)

- **projection_values** (*Optional[Dict[str, str]]*) – Dictionary of partitions names and Athena projections values. <https://docs.aws.amazon.com/athena/latest/ug/partition-projection-supported-types.html> (e.g. {'col_name': 'A,B,Unknown', 'col2_name': 'foo,boo,bar'})
- **projection_intervals** (*Optional[Dict[str, str]]*) – Dictionary of partitions names and Athena projections intervals. <https://docs.aws.amazon.com/athena/latest/ug/partition-projection-supported-types.html> (e.g. {'col_name': '1', 'col2_name': '5'})
- **projection_digits** (*Optional[Dict[str, str]]*) – Dictionary of partitions names and Athena projections digits. <https://docs.aws.amazon.com/athena/latest/ug/partition-projection-supported-types.html> (e.g. {'col_name': '1', 'col2_name': '2'})
- **pandas_kwargs** – keyword arguments forwarded to `pandas.DataFrame.to_csv()` https://pandas.pydata.org/pandas-docs/stable/reference/api/pandas.DataFrame.to_csv.html

Returns None.

Return type None

Examples

Writing single file

```
>>> import awswrangler as wr
>>> import pandas as pd
>>> wr.s3.to_csv(
...     df=pd.DataFrame({'col': [1, 2, 3]}),
...     path='s3://bucket/prefix/my_file.csv',
... )
{
    'paths': ['s3://bucket/prefix/my_file.csv'],
    'partitions_values': {}
}
```

Writing single file encrypted with a KMS key

```
>>> import awswrangler as wr
>>> import pandas as pd
>>> wr.s3.to_csv(
...     df=pd.DataFrame({'col': [1, 2, 3]}),
...     path='s3://bucket/prefix/my_file.csv',
...     s3_additional_kwargs={
...         'ServerSideEncryption': 'aws:kms',
...         'SSEKMSKeyId': 'YOUR_KMY_KEY_ARN'
...     }
... )
{
    'paths': ['s3://bucket/prefix/my_file.csv'],
    'partitions_values': {}
}
```

Writing partitioned dataset

```
>>> import awswrangler as wr
>>> import pandas as pd
>>> wr.s3.to_csv(
...     df=pd.DataFrame({
```

(continues on next page)

(continued from previous page)

```

...     'col': [1, 2, 3],
...     'col2': ['A', 'A', 'B']
...   }},
...   path='s3://bucket/prefix',
...   dataset=True,
...   partition_cols=['col2']
... )
{
  'paths': ['s3://.../col2=A/x.csv', 's3://.../col2=B/y.csv'],
  'partitions_values': {
    's3://.../col2=A/': ['A'],
    's3://.../col2=B/': ['B']
  }
}

```

Writing dataset to S3 with metadata on Athena/Glue Catalog.

```

>>> import awswrangler as wr
>>> import pandas as pd
>>> wr.s3.to_csv(
...     df=pd.DataFrame({
...         'col': [1, 2, 3],
...         'col2': ['A', 'A', 'B']
...     }),
...     path='s3://bucket/prefix',
...     dataset=True,
...     partition_cols=['col2'],
...     database='default', # Athena/Glue database
...     table='my_table' # Athena/Glue table
... )
{
  'paths': ['s3://.../col2=A/x.csv', 's3://.../col2=B/y.csv'],
  'partitions_values': {
    's3://.../col2=A/': ['A'],
    's3://.../col2=B/': ['B']
  }
}

```

Writing dataset casting empty column data type

```

>>> import awswrangler as wr
>>> import pandas as pd
>>> wr.s3.to_csv(
...     df=pd.DataFrame({
...         'col': [1, 2, 3],
...         'col2': ['A', 'A', 'B'],
...         'col3': [None, None, None]
...     }),
...     path='s3://bucket/prefix',
...     dataset=True,
...     database='default', # Athena/Glue database
...     table='my_table' # Athena/Glue table
...     dtype={'col3': 'date'}
... )
{
  'paths': ['s3://.../x.csv'],
  'partitions_values': {}
}

```

(continues on next page)

(continued from previous page)

}

awswrangler.s3.to_json

`awswrangler.s3.to_json(df: pandas.core.frame.DataFrame, path: str, boto3_session: Optional[boto3.session.Session] = None, s3_additional_kwargs: Optional[Dict[str, str]] = None, **pandas_kwargs) → None`

Write JSON file on Amazon S3.

Parameters

- **df** (*pandas.DataFrame*) – Pandas DataFrame <https://pandas.pydata.org/pandas-docs/stable/reference/api/pandas.DataFrame.html>
- **path** (*str*) – Amazon S3 path (e.g. `s3://bucket/filename.csv`).
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 Session will be used if boto3_session receive None.
- **s3_additional_kwargs** – Forward to s3fs, useful for server side encryption <https://s3fs.readthedocs.io/en/latest/#serverside-encryption>
- **pandas_kwargs** – keyword arguments forwarded to `pandas.DataFrame.to_csv()` https://pandas.pydata.org/pandas-docs/stable/reference/api/pandas.DataFrame.to_json.html

Returns None.

Return type None

Examples

Writing JSON file

```
>>> import awswrangler as wr
>>> import pandas as pd
>>> wr.s3.to_json(
...     df=pd.DataFrame({'col': [1, 2, 3]}),
...     path='s3://bucket/filename.json',
... )
```

Writing CSV file encrypted with a KMS key

```
>>> import awswrangler as wr
>>> import pandas as pd
>>> wr.s3.to_json(
...     df=pd.DataFrame({'col': [1, 2, 3]}),
...     path='s3://bucket/filename.json',
...     s3_additional_kwargs={
...         'ServerSideEncryption': 'aws:kms',
...         'SSEKMSKeyId': 'YOUR_KMY_KEY_ARN'
...     }
... )
```


awswrangler.s3.to_parquet

```
awswrangler.s3.to_parquet(df: pandas.core.frame.DataFrame, path: str, index: bool = False,
                           compression: Optional[str] = 'snappy', use_threads: bool =
                               True, boto3_session: Optional[boto3.session.Session] = None,
                           s3_additional_kwargs: Optional[Dict[str, str]] = None, sanitize_columns:
                               bool = False, dataset: bool = False, partition_cols:
                               Optional[List[str]] = None, mode: Optional[str] = None, catalog_versioning:
                               bool = False, database: Optional[str] = None, table: Optional[str] = None,
                               dtype: Optional[Dict[str, str]] = None, description: Optional[str] = None,
                               parameters: Optional[Dict[str, str]] = None, columns_comments:
                               Optional[Dict[str, str]] = None, regular_partitions: bool = True,
                               projection_enabled: bool = False, projection_types:
                               Optional[Dict[str, str]] = None, projection_ranges:
                               Optional[Dict[str, str]] = None, projection_values:
                               Optional[Dict[str, str]] = None, projection_intervals:
                               Optional[Dict[str, str]] = None, projection_digits:
                               Optional[Dict[str, str]] = None) → Dict[str,
                               Union[List[str], Dict[str, List[str]]]]
```

Write Parquet file or dataset on Amazon S3.

The concept of Dataset goes beyond the simple idea of files and enable more complex features like partitioning, casting and catalog integration (Amazon Athena/AWS Glue Catalog).

Note: If *dataset=True* The table name and all column names will be automatically sanitized using *wr.catalog.sanitize_table_name* and *wr.catalog.sanitize_column_name*. Please, pass *sanitize_columns=True* to force the same behaviour for *dataset=False*.

Note: On *append* mode, the *parameters* will be upsert on an existing table.

Note: In case of *use_threads=True* the number of threads that will be spawned will be get from *os.cpu_count()*.

Parameters

- **df** (*pandas.DataFrame*) – Pandas DataFrame <https://pandas.pydata.org/pandas-docs/stable/reference/api/pandas.DataFrame.html>
- **path** (*str*) – S3 path (for file e.g. *s3://bucket/prefix/filename.parquet*) (for dataset e.g. *s3://bucket/prefix*).
- **index** (*bool*) – True to store the DataFrame index in file, otherwise False to ignore it.
- **compression** (*str, optional*) – Compression style (None, snappy, gzip).
- **use_threads** (*bool*) – True to enable concurrent requests, False to disable multiple threads. If enabled *os.cpu_count()* will be used as the max number of threads.
- **boto3_session** (*boto3.Session(), optional*) – Boto3 Session. The default boto3 session will be used if *boto3_session* receive None.
- **s3_additional_kwargs** – Forward to s3fs, useful for server side encryption <https://s3fs.readthedocs.io/en/latest/#serverside-encryption>
- **sanitize_columns** (*bool*) – True to sanitize columns names or False to keep it as is. True value is forced if *dataset=True*.

- **dataset** (*bool*) – If True store a parquet dataset instead of a single file. If True, enable all follow arguments: `partition_cols`, `mode`, `database`, `table`, `description`, `parameters`, `columns_comments`, .
- **partition_cols** (*List[str], optional*) – List of column names that will be used to create partitions. Only takes effect if `dataset=True`.
- **mode** (*str, optional*) – `append` (Default), `overwrite`, `overwrite_partitions`. Only takes effect if `dataset=True`.
- **catalog_versioning** (*bool*) – If True and `mode="overwrite"`, creates an archived version of the table catalog before updating it.
- **database** (*str, optional*) – Glue/Athena catalog: Database name.
- **table** (*str, optional*) – Glue/Athena catalog: Table name.
- **dtype** (*Dict[str, str], optional*) – Dictionary of columns names and Athena/Glue types to be casted. Useful when you have columns with undetermined or mixed data types. (e.g. `{'col name': 'bigint', 'col2 name': 'int'}`)
- **description** (*str, optional*) – Glue/Athena catalog: Table description
- **parameters** (*Dict[str, str], optional*) – Glue/Athena catalog: Key/value pairs to tag the table.
- **columns_comments** (*Dict[str, str], optional*) – Glue/Athena catalog: Columns names and the related comments (e.g. `{'col0': 'Column 0.', 'col1': 'Column 1.', 'col2': 'Partition.'}`).
- **regular_partitions** (*bool*) – Create regular partitions (Non projected partitions) on Glue Catalog. Disable when you will work only with Partition Projection. Keep enabled even when working with projections is useful to keep Redshift Spectrum working with the regular partitions.
- **projection_enabled** (*bool*) – Enable Partition Projection on Athena (<https://docs.aws.amazon.com/athena/latest/ug/partition-projection.html>)
- **projection_types** (*Optional[Dict[str, str]]*) – Dictionary of partitions names and Athena projections types. Valid types: "enum", "integer", "date", "injected" <https://docs.aws.amazon.com/athena/latest/ug/partition-projection-supported-types.html> (e.g. `{'col_name': 'enum', 'col2_name': 'integer'}`)
- **projection_ranges** (*Optional[Dict[str, str]]*) – Dictionary of partitions names and Athena projections ranges. <https://docs.aws.amazon.com/athena/latest/ug/partition-projection-supported-types.html> (e.g. `{'col_name': '0,10', 'col2_name': '-1,8675309'}`)
- **projection_values** (*Optional[Dict[str, str]]*) – Dictionary of partitions names and Athena projections values. <https://docs.aws.amazon.com/athena/latest/ug/partition-projection-supported-types.html> (e.g. `{'col_name': 'A,B,Unknown', 'col2_name': 'foo,boo,bar'}`)
- **projection_intervals** (*Optional[Dict[str, str]]*) – Dictionary of partitions names and Athena projections intervals. <https://docs.aws.amazon.com/athena/latest/ug/partition-projection-supported-types.html> (e.g. `{'col_name': '1', 'col2_name': '5'}`)
- **projection_digits** (*Optional[Dict[str, str]]*) – Dictionary of partitions names and Athena projections digits. <https://docs.aws.amazon.com/athena/latest/ug/partition-projection-supported-types.html> (e.g. `{'col_name': '1', 'col2_name': '2'}`)

Returns Dictionary with: 'paths': List of all stored files paths on S3. 'partitions_values': Dictionary of partitions added with keys as S3 path locations and values as a list of partitions values as str.

Return type Dict[str, Union[List[str], Dict[str, List[str]]]]

Examples

Writing single file

```
>>> import awswrangler as wr
>>> import pandas as pd
>>> wr.s3.to_parquet(
...     df=pd.DataFrame({'col': [1, 2, 3]}),
...     path='s3://bucket/prefix/my_file.parquet',
... )
{
  'paths': ['s3://bucket/prefix/my_file.parquet'],
  'partitions_values': {}
}
```

Writing single file encrypted with a KMS key

```
>>> import awswrangler as wr
>>> import pandas as pd
>>> wr.s3.to_parquet(
...     df=pd.DataFrame({'col': [1, 2, 3]}),
...     path='s3://bucket/prefix/my_file.parquet',
...     s3_additional_kwargs={
...         'ServerSideEncryption': 'aws:kms',
...         'SSEKMSKeyId': 'YOUR_KMY_KEY_ARN'
...     }
... )
{
  'paths': ['s3://bucket/prefix/my_file.parquet'],
  'partitions_values': {}
}
```

Writing partitioned dataset

```
>>> import awswrangler as wr
>>> import pandas as pd
>>> wr.s3.to_parquet(
...     df=pd.DataFrame({
...         'col': [1, 2, 3],
...         'col2': ['A', 'A', 'B']
...     }),
...     path='s3://bucket/prefix',
...     dataset=True,
...     partition_cols=['col2']
... )
{
  'paths': ['s3://.../col2=A/x.parquet', 's3://.../col2=B/y.parquet'],
  'partitions_values': {
    's3://.../col2=A/': ['A'],
    's3://.../col2=B/': ['B']
  }
}
```

Writing dataset to S3 with metadata on Athena/Glue Catalog.

```
>>> import awswrangler as wr
>>> import pandas as pd
>>> wr.s3.to_parquet(
...     df=pd.DataFrame({
...         'col': [1, 2, 3],
...         'col2': ['A', 'A', 'B']
...     }),
...     path='s3://bucket/prefix',
...     dataset=True,
...     partition_cols=['col2'],
...     database='default', # Athena/Glue database
...     table='my_table' # Athena/Glue table
... )
{
  'paths': ['s3://.../col2=A/x.parquet', 's3://.../col2=B/y.parquet'],
  'partitions_values': {
    's3://.../col2=A/': ['A'],
    's3://.../col2=B/': ['B']
  }
}
```

Writing dataset casting empty column data type

```
>>> import awswrangler as wr
>>> import pandas as pd
>>> wr.s3.to_parquet(
...     df=pd.DataFrame({
...         'col': [1, 2, 3],
...         'col2': ['A', 'A', 'B'],
...         'col3': [None, None, None]
...     }),
...     path='s3://bucket/prefix',
...     dataset=True,
...     database='default', # Athena/Glue database
...     table='my_table' # Athena/Glue table
...     dtype={'col3': 'date'}
... )
{
  'paths': ['s3://.../x.parquet'],
  'partitions_values': {}
}
```

awswrangler.s3.wait_objects_exist

`awswrangler.s3.wait_objects_exist` (*paths*: List[str], *delay*: Union[int, float, None] = None, *max_attempts*: Optional[int] = None, *use_threads*: bool = True, *boto3_session*: Optional[boto3.session.Session] = None) → None

Wait Amazon S3 objects exist.

Polls S3.Client.head_object() every 5 seconds (default) until a successful state is reached. An error is returned after 20 (default) failed checks. <https://boto3.amazonaws.com/v1/documentation/api/latest/reference/services/s3.html#S3.Waiter.ObjectExists>

Note: In case of `use_threads=True` the number of threads that will be spawned will be get from `os.cpu_count()`.

Parameters

- **paths** (*List[str]*) – List of S3 objects paths (e.g. [s3://bucket/key0, s3://bucket/key1]).
- **delay** (*Union[int, float]*, *optional*) – The amount of time in seconds to wait between attempts. Default: 5
- **max_attempts** (*int*, *optional*) – The maximum number of attempts to be made. Default: 20
- **use_threads** (*bool*) – True to enable concurrent requests, False to disable multiple threads. If enabled `os.cpu_count()` will be used as the max number of threads.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if `boto3_session` receive None.

Returns None.

Return type None

Examples

```
>>> import awswrangler as wr
>>> wr.s3.wait_objects_exist(['s3://bucket/key0', 's3://bucket/key1']) # wait_
↳ both objects
```

awswrangler.s3.wait_objects_not_exist

`awswrangler.s3.wait_objects_not_exist` (*paths: List[str]*, *delay: Union[int, float, None] = None*, *max_attempts: Optional[int] = None*, *use_threads: bool = True*, *boto3_session: Optional[boto3.session.Session] = None*) → None

Wait Amazon S3 objects not exist.

Polls `S3.Client.head_object()` every 5 seconds (default) until a successful state is reached. An error is returned after 20 (default) failed checks. <https://boto3.amazonaws.com/v1/documentation/api/latest/reference/services/s3.html#S3.Waiter.ObjectNotExists>

Note: In case of `use_threads=True` the number of threads that will be spawned will be get from `os.cpu_count()`.

Parameters

- **paths** (*List[str]*) – List of S3 objects paths (e.g. [s3://bucket/key0, s3://bucket/key1]).
- **delay** (*Union[int, float]*, *optional*) – The amount of time in seconds to wait between attempts. Default: 5
- **max_attempts** (*int*, *optional*) – The maximum number of attempts to be made. Default: 20
- **use_threads** (*bool*) – True to enable concurrent requests, False to disable multiple threads. If enabled `os.cpu_count()` will be used as the max number of threads.

- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns None.

Return type None

Examples

```
>>> import awswrangler as wr
>>> wr.s3.wait_objects_not_exist(['s3://bucket/key0', 's3://bucket/key1']) #_
↪ wait both objects not exist
```

1.3.2 AWS Glue Catalog

<code>add_csv_partitions(database, table, ..., ...)</code>	Add partitions (metadata) to a CSV Table in the AWS Glue Catalog.
<code>add_parquet_partitions(database, table, ...)</code>	Add partitions (metadata) to a Parquet Table in the AWS Glue Catalog.
<code>create_csv_table(database, table, path, ...)</code>	Create a CSV Table (Metadata Only) in the AWS Glue Catalog.
<code>create_database(name[, description, ...])</code>	Create a database in AWS Glue Catalog.
<code>create_parquet_table(database, table, path, ...)</code>	Create a Parquet Table (Metadata Only) in the AWS Glue Catalog.
<code>databases([limit, catalog_id, boto3_session])</code>	Get a Pandas DataFrame with all listed databases.
<code>delete_database(name[, catalog_id, ...])</code>	Create a database in AWS Glue Catalog.
<code>delete_table_if_exists(database, table[, ...])</code>	Delete Glue table if exists.
<code>does_table_exist(database, table[, ...])</code>	Check if the table exists.
<code>drop_duplicated_columns(df)</code>	Drop all repeated columns (duplicated names).
<code>extract_athena_types(df[, index, ...])</code>	Extract columns and partitions types (Amazon Athena) from Pandas DataFrame.
<code>get_columns_comments(database, table[, ...])</code>	Get all columns comments.
<code>get_csv_partitions(database, table[, ...])</code>	Get all partitions from a Table in the AWS Glue Catalog.
<code>get_databases([catalog_id, boto3_session])</code>	Get an iterator of databases.
<code>get_engine(connection[, catalog_id, ...])</code>	Return a SQLAlchemy Engine from a Glue Catalog Connection.
<code>get_parquet_partitions(database, table[, ...])</code>	Get all partitions from a Table in the AWS Glue Catalog.
<code>get_table_description(database, table[, ...])</code>	Get table description.
<code>get_table_location(database, table[, ...])</code>	Get table's location on Glue catalog.
<code>get_table_parameters(database, table[, ...])</code>	Get all parameters.
<code>get_table_types(database, table[, boto3_session])</code>	Get all columns and types from a table.
<code>get_tables([catalog_id, database, ...])</code>	Get an iterator of tables.
<code>overwrite_table_parameters(parameters, ...)</code>	Overwrite all existing parameters.
<code>sanitize_column_name(column)</code>	Convert the column name to be compatible with Amazon Athena.
<code>sanitize_dataframe_columns_names(df)</code>	Normalize all columns names to be compatible with Amazon Athena.

continues on next page

Table 2 – continued from previous page

<code>sanitize_table_name(table)</code>	Convert the table name to be compatible with Amazon Athena.
<code>search_tables(text[, catalog_id, boto3_session])</code>	Get Pandas DataFrame of tables filtered by a search string.
<code>table(database, table[, catalog_id, ...])</code>	Get table details as Pandas DataFrame.
<code>tables([limit, catalog_id, database, ...])</code>	Get a DataFrame with tables filtered by a search term, prefix, suffix.
<code>upsert_table_parameters(parameters, ..., ...)</code>	Insert or Update the received parameters.

awswrangler.catalog.add_csv_partitions

`awswrangler.catalog.add_csv_partitions` (*database: str, table: str, partitions_values: Dict[str, List[str]], compression: Optional[str] = None, sep: str = ',', boto3_session: Optional[boto3.session.Session] = None*) → None

Add partitions (metadata) to a CSV Table in the AWS Glue Catalog.

Parameters

- **database** (*str*) – Database name.
- **table** (*str*) – Table name.
- **partitions_values** (*Dict[str, List[str]]*) – Dictionary with keys as S3 path locations and values as a list of partitions values as str (e.g. {'s3://bucket/prefix/y=2020/m=10/': ['2020', '10']}).
- **compression** (*str, optional*) – Compression style (None, gzip, etc).
- **sep** (*str*) – String of length 1. Field delimiter for the output file.
- **boto3_session** (*boto3.Session(), optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns None.

Return type None

Examples

```
>>> import awswrangler as wr
>>> wr.catalog.add_csv_partitions(
...     database='default',
...     table='my_table',
...     partitions_values={
...         's3://bucket/prefix/y=2020/m=10/': ['2020', '10'],
...         's3://bucket/prefix/y=2020/m=11/': ['2020', '11'],
...         's3://bucket/prefix/y=2020/m=12/': ['2020', '12']
...     }
... )
```

awswrangler.catalog.add_parquet_partitions

`awswrangler.catalog.add_parquet_partitions` (*database: str, table: str, partitions_values: Dict[str, List[str]], compression: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None*) → None

Add partitions (metadata) to a Parquet Table in the AWS Glue Catalog.

Parameters

- **database** (*str*) – Database name.
- **table** (*str*) – Table name.
- **partitions_values** (*Dict[str, List[str]]*) – Dictionary with keys as S3 path locations and values as a list of partitions values as str (e.g. {'s3://bucket/prefix/y=2020/m=10/': ['2020', '10']}).
- **compression** (*str, optional*) – Compression style (None, snappy, gzip, etc).
- **boto3_session** (*boto3.Session(), optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns None.

Return type None

Examples

```
>>> import awswrangler as wr
>>> wr.catalog.add_parquet_partitions(
...     database='default',
...     table='my_table',
...     partitions_values={
...         's3://bucket/prefix/y=2020/m=10/': ['2020', '10'],
...         's3://bucket/prefix/y=2020/m=11/': ['2020', '11'],
...         's3://bucket/prefix/y=2020/m=12/': ['2020', '12']
...     }
... )
```


aws wrangler.catalog.create_csv_table

```
aws wrangler.catalog.create_csv_table(database: str, table: str, path: str, columns_types:
    Dict[str, str], partitions_types: Optional[Dict[str, str]]
    = None, compression: Optional[str] = None, description: Optional[str] = None, parameters: Op-
    tional[Dict[str, str]] = None, columns_comments: Op-
    tional[Dict[str, str]] = None, mode: str = 'over-
    write', catalog_versioning: bool = False, sep: str
    = ',', boto3_session: Optional[boto3.session.Session]
    = None, projection_enabled: bool = False, projec-
    tion_types: Optional[Dict[str, str]] = None, projec-
    tion_ranges: Optional[Dict[str, str]] = None, projec-
    tion_values: Optional[Dict[str, str]] = None, projec-
    tion_intervals: Optional[Dict[str, str]] = None, projec-
    tion_digits: Optional[Dict[str, str]] = None) → None
```

Create a CSV Table (Metadata Only) in the AWS Glue Catalog.

<https://docs.aws.amazon.com/athena/latest/ug/data-types.html>

Parameters

- **database** (*str*) – Database name.
- **table** (*str*) – Table name.
- **path** (*str*) – Amazon S3 path (e.g. s3://bucket/prefix/).
- **columns_types** (*Dict[str, str]*) – Dictionary with keys as column names and vales as data types (e.g. {'col0': 'bigint', 'col1': 'double'}).
- **partitions_types** (*Dict[str, str], optional*) – Dictionary with keys as partition names and values as data types (e.g. {'col2': 'date'}).
- **compression** (*str, optional*) – Compression style (None, gzip, etc).
- **description** (*str, optional*) – Table description
- **parameters** (*Dict[str, str], optional*) – Key/value pairs to tag the table.
- **columns_comments** (*Dict[str, str], optional*) – Columns names and the related comments (e.g. {'col0': 'Column 0.', 'col1': 'Column 1.', 'col2': 'Partition.'}).
- **mode** (*str*) – 'overwrite' to recreate any possible axisting table or 'append' to keep any possible axisting table.
- **catalog_versioning** (*bool*) – If True and *mode*="overwrite", creates an archived version of the table catalog before updating it.
- **sep** (*str*) – String of length 1. Field delimiter for the output file.
- **projection_enabled** (*bool*) – Enable Partition Projection on Athena (<https://docs.aws.amazon.com/athena/latest/ug/partition-projection.html>)
- **projection_types** (*Optional[Dict[str, str]]*) – Dictionary of partitions names and Athena projections types. Valid types: "enum", "integer", "date", "injected" <https://docs.aws.amazon.com/athena/latest/ug/partition-projection-supported-types.html> (e.g. {'col_name': 'enum', 'col2_name': 'integer'})
- **projection_ranges** (*Optional[Dict[str, str]]*) – Dictionary of partitions names and Athena projections ranges. <https://docs.aws.amazon.com/athena/latest/ug/partition-projection-supported-types.html> (e.g. {'col_name': '0,10', 'col2_name': '-1,8675309'})

- **projection_values** (*Optional[Dict[str, str]]*) – Dictionary of partitions names and Athena projections values. <https://docs.aws.amazon.com/athena/latest/ug/partition-projection-supported-types.html> (e.g. {'col_name': 'A,B,Unknown', 'col2_name': 'foo,boo,bar'})
- **projection_intervals** (*Optional[Dict[str, str]]*) – Dictionary of partitions names and Athena projections intervals. <https://docs.aws.amazon.com/athena/latest/ug/partition-projection-supported-types.html> (e.g. {'col_name': '1', 'col2_name': '5'})
- **projection_digits** (*Optional[Dict[str, str]]*) – Dictionary of partitions names and Athena projections digits. <https://docs.aws.amazon.com/athena/latest/ug/partition-projection-supported-types.html> (e.g. {'col_name': '1', 'col2_name': '2'})
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns None.

Return type None

Examples

```
>>> import awswrangler as wr
>>> wr.catalog.create_csv_table(
...     database='default',
...     table='my_table',
...     path='s3://bucket/prefix/',
...     columns_types={'col0': 'bigint', 'col1': 'double'},
...     partitions_types={'col2': 'date'},
...     compression='gzip',
...     description='My own table!',
...     parameters={'source': 'postgresql'},
...     columns_comments={'col0': 'Column 0.', 'col1': 'Column 1.', 'col2':
→ 'Partition.'}
... )
```

awswrangler.catalog.create_database

`awswrangler.catalog.create_database` (*name: str, description: Optional[str] = None, catalog_id: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None*) → None

Create a database in AWS Glue Catalog.

Parameters

- **name** (*str*) – Database name.
- **description** (*str, optional*) – A Description for the Database.
- **catalog_id** (*str, optional*) – The ID of the Data Catalog from which to retrieve Databases. If none is provided, the AWS account ID is used by default.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns None.

Return type None

Examples

```
>>> import awswrangler as wr
>>> wr.catalog.create_database(
...     name='awswrangler_test'
... )
```

awswrangler.catalog.create_parquet_table

```
awswrangler.catalog.create_parquet_table(database: str, table: str, path: str,
                                         columns_types: Dict[str, str], partitions_types:
                                         Optional[Dict[str, str]] = None, compression:
                                         Optional[str] = None, description:
                                         Optional[str] = None, parameters:
                                         Optional[Dict[str, str]] = None, columns_comments:
                                         Optional[Dict[str, str]] = None, mode: str =
                                         'overwrite', catalog_versioning: bool = False,
                                         projection_enabled: bool = False, projection_types:
                                         Optional[Dict[str, str]] = None, projection_ranges:
                                         Optional[Dict[str, str]] =
                                         None, projection_values: Optional[Dict[str,
                                         str]] = None, projection_intervals:
                                         Optional[Dict[str, str]] = None, projection_digits:
                                         Optional[Dict[str, str]] = None, boto3_session:
                                         Optional[boto3.session.Session] = None) →
                                         None
```

Create a Parquet Table (Metadata Only) in the AWS Glue Catalog.

<https://docs.aws.amazon.com/athena/latest/ug/data-types.html>

Parameters

- **database** (*str*) – Database name.
- **table** (*str*) – Table name.
- **path** (*str*) – Amazon S3 path (e.g. s3://bucket/prefix/).
- **columns_types** (*Dict[str, str]*) – Dictionary with keys as column names and values as data types (e.g. {'col0': 'bigint', 'col1': 'double'}).
- **partitions_types** (*Dict[str, str], optional*) – Dictionary with keys as partition names and values as data types (e.g. {'col2': 'date'}).
- **compression** (*str, optional*) – Compression style (None, snappy, gzip, etc).
- **description** (*str, optional*) – Table description
- **parameters** (*Dict[str, str], optional*) – Key/value pairs to tag the table.
- **columns_comments** (*Dict[str, str], optional*) – Columns names and the related comments (e.g. {'col0': 'Column 0.', 'col1': 'Column 1.', 'col2': 'Partition.'}).
- **mode** (*str*) – 'overwrite' to recreate any possible existing table or 'append' to keep any possible existing table.
- **catalog_versioning** (*bool*) – If True and mode="overwrite", creates an archived version of the table catalog before updating it.

- **projection_enabled** (*bool*) – Enable Partition Projection on Athena (<https://docs.aws.amazon.com/athena/latest/ug/partition-projection.html>)
- **projection_types** (*Optional[Dict[str, str]]*) – Dictionary of partitions names and Athena projections types. Valid types: “enum”, “integer”, “date”, “injected” <https://docs.aws.amazon.com/athena/latest/ug/partition-projection-supported-types.html> (e.g. {'col_name': 'enum', 'col2_name': 'integer'})
- **projection_ranges** (*Optional[Dict[str, str]]*) – Dictionary of partitions names and Athena projections ranges. <https://docs.aws.amazon.com/athena/latest/ug/partition-projection-supported-types.html> (e.g. {'col_name': '0,10', 'col2_name': '-1,8675309'})
- **projection_values** (*Optional[Dict[str, str]]*) – Dictionary of partitions names and Athena projections values. <https://docs.aws.amazon.com/athena/latest/ug/partition-projection-supported-types.html> (e.g. {'col_name': 'A,B,Unknown', 'col2_name': 'foo,boo,bar'})
- **projection_intervals** (*Optional[Dict[str, str]]*) – Dictionary of partitions names and Athena projections intervals. <https://docs.aws.amazon.com/athena/latest/ug/partition-projection-supported-types.html> (e.g. {'col_name': '1', 'col2_name': '5'})
- **projection_digits** (*Optional[Dict[str, str]]*) – Dictionary of partitions names and Athena projections digits. <https://docs.aws.amazon.com/athena/latest/ug/partition-projection-supported-types.html> (e.g. {'col_name': '1', 'col2_name': '2'})
- **boto3_session** (*boto3.Session(), optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns None.

Return type None

Examples

```
>>> import awswrangler as wr
>>> wr.catalog.create_parquet_table(
...     database='default',
...     table='my_table',
...     path='s3://bucket/prefix/',
...     columns_types={'col0': 'bigint', 'col1': 'double'},
...     partitions_types={'col2': 'date'},
...     compression='snappy',
...     description='My own table!',
...     parameters={'source': 'postgresql'},
...     columns_comments={'col0': 'Column 0.', 'col1': 'Column 1.', 'col2':
↪ 'Partition.'}
... )
```

awswrangler.catalog.databases

`awswrangler.catalog.databases` (*limit*: *int* = 100, *catalog_id*: *Optional[str]* = None, *boto3_session*: *Optional[boto3.session.Session]* = None) → `pandas.core.frame.DataFrame`

Get a Pandas DataFrame with all listed databases.

Parameters

- **limit** (*int*, *optional*) – Max number of tables to be returned.
- **catalog_id** (*str*, *optional*) – The ID of the Data Catalog from which to retrieve Databases. If none is provided, the AWS account ID is used by default.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if `boto3_session` receive None.

Returns Pandas DataFrame filled by formatted infos.

Return type `pandas.DataFrame`

Examples

```
>>> import awswrangler as wr
>>> df_dbs = wr.catalog.databases()
```

awswrangler.catalog.delete_database

`awswrangler.catalog.delete_database` (*name*: *str*, *catalog_id*: *Optional[str]* = None, *boto3_session*: *Optional[boto3.session.Session]* = None) → None

Create a database in AWS Glue Catalog.

Parameters

- **name** (*str*) – Database name.
- **catalog_id** (*str*, *optional*) – The ID of the Data Catalog from which to retrieve Databases. If none is provided, the AWS account ID is used by default.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if `boto3_session` receive None.

Returns None.

Return type None

Examples

```
>>> import awswrangler as wr
>>> wr.catalog.delete_database(
...     name='awswrangler_test'
... )
```

`awswrangler.catalog.delete_table_if_exists`

`awswrangler.catalog.delete_table_if_exists` (*database: str, table: str, boto3_session: Optional[boto3.session.Session] = None*) → bool

Delete Glue table if exists.

Parameters

- **database** (*str*) – Database name.
- **table** (*str*) – Table name.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns True if deleted, otherwise False.

Return type bool

Examples

```
>>> import awswrangler as wr
>>> wr.catalog.delete_table_if_exists(database='default', name='my_table') #_
↳deleted
True
>>> wr.catalog.delete_table_if_exists(database='default', name='my_table') #_
↳Nothing to be deleted
False
```

`awswrangler.catalog.does_table_exist`

`awswrangler.catalog.does_table_exist` (*database: str, table: str, boto3_session: Optional[boto3.session.Session] = None*)

Check if the table exists.

Parameters

- **database** (*str*) – Database name.
- **table** (*str*) – Table name.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns True if exists, otherwise False.

Return type bool

Examples

```
>>> import awswrangler as wr
>>> wr.catalog.does_table_exist(database='default', name='my_table')
```

awswrangler.catalog.drop_duplicated_columns

`awswrangler.catalog.drop_duplicated_columns` (*df*: `pandas.core.frame.DataFrame`) → `pandas.core.frame.DataFrame`

Drop all repeated columns (duplicated names).

Note: This transformation will run *inplace* and will make changes in the original `DataFrame`.

Note: It is different from Panda's `drop_duplicates()` function which considers the column values. `wr.catalog.drop_duplicated_columns()` will deduplicate by column name.

Parameters *df* (`pandas.DataFrame`) – Original Pandas `DataFrame`.

Returns Pandas `DataFrame` without duplicated columns.

Return type `pandas.DataFrame`

Examples

```
>>> import awswrangler as wr
>>> df = pd.DataFrame({"A": [1, 2], "B": [3, 4]})
>>> df.columns = ["A", "A"]
>>> wr.catalog.drop_duplicated_columns(df=df)
   A
0  1
1  2
```

awswrangler.catalog.extract_athena_types

`awswrangler.catalog.extract_athena_types` (*df*: `pandas.core.frame.DataFrame`, *index*: `bool` = `False`, *partition_cols*: `Optional[List[str]]` = `None`, *dtype*: `Optional[Dict[str, str]]` = `None`, *file_format*: `str` = `'parquet'`) → `Tuple[Dict[str, str], Dict[str, str]]`

Extract columns and partitions types (Amazon Athena) from Pandas `DataFrame`.

<https://docs.aws.amazon.com/athena/latest/ug/data-types.html>

Parameters

- **df** (`pandas.DataFrame`) – Pandas `DataFrame`.
- **index** (`bool`) – Should consider the `DataFrame` index as a column?
- **partition_cols** (`List[str]`, *optional*) – List of partitions names.

- **dtype** (*Dict[str, str], optional*) – Dictionary of columns names and Athena/Glue types to be casted. Useful when you have columns with undetermined or mixed data types. (e.g. {'col name': 'bigint', 'col2 name': 'int'})
- **file_format** (*str, optional*) – File format to be considered to place the index column: "parquet" | "csv".

Returns `columns_types`: Dictionary with keys as column names and values as data types (e.g. {'col0': 'bigint', 'col1': 'double'}). / `partitions_types`: Dictionary with keys as partition names and values as data types (e.g. {'col2': 'date'}).

Return type `Tuple[Dict[str, str], Optional[Dict[str, str]]]`

Examples

```
>>> import awswrangler as wr
>>> columns_types, partitions_types = wr.catalog.extract_athena_types(
...     df=df, index=False, partition_cols=["par0", "par1"], file_format="csv"
... )
```

awswrangler.catalog.get_columns_comments

`awswrangler.catalog.get_columns_comments` (*database: str, table: str, catalog_id: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None*) → `Dict[str, str]`

Get all columns comments.

Parameters

- **database** (*str*) – Database name.
- **table** (*str*) – Table name.
- **catalog_id** (*str, optional*) – The ID of the Data Catalog from which to retrieve Databases. If none is provided, the AWS account ID is used by default.
- **boto3_session** (*boto3.Session(), optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Columns comments. e.g. {"col1": "foo boo bar"}.

Return type `Dict[str, str]`

Examples

```
>>> import awswrangler as wr
>>> pars = wr.catalog.get_table_parameters(database="...", table="...")
```


awswrangler.catalog.get_csv_partitions

`awswrangler.catalog.get_csv_partitions` (*database: str, table: str, expression: Optional[str] = None, catalog_id: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None*) → Dict[str, List[str]]

Get all partitions from a Table in the AWS Glue Catalog.

Expression argument instructions: https://boto3.amazonaws.com/v1/documentation/api/latest/reference/services/glue.html#Glue.Client.get_partitions

Parameters

- **database** (*str*) – Database name.
- **table** (*str*) – Table name.
- **expression** (*str, optional*) – An expression that filters the partitions to be returned.
- **catalog_id** (*str, optional*) – The ID of the Data Catalog from which to retrieve Databases. If none is provided, the AWS account ID is used by default.
- **boto3_session** (*boto3.Session(), optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns `partitions_values`: Dictionary with keys as S3 path locations and values as a list of partitions values as str (e.g. {'s3://bucket/prefix/y=2020/m=10/': ['2020', '10']}).

Return type Dict[str, List[str]]

Examples

Fetch all partitions

```
>>> import awswrangler as wr
>>> wr.catalog.get_csv_partitions(
...     database='default',
...     table='my_table',
... )
{
  's3://bucket/prefix/y=2020/m=10/': ['2020', '10'],
  's3://bucket/prefix/y=2020/m=11/': ['2020', '11'],
  's3://bucket/prefix/y=2020/m=12/': ['2020', '12']
}
```

Filtering partitions

```
>>> import awswrangler as wr
>>> wr.catalog.get_csv_partitions(
...     database='default',
...     table='my_table',
...     expression='m=10'
... )
{
  's3://bucket/prefix/y=2020/m=10/': ['2020', '10']
}
```

aws wrangler.catalog.get_databases

`aws wrangler.catalog.get_databases` (*catalog_id*: *Optional[str] = None*, *boto3_session*: *Optional[boto3.session.Session] = None*) → *Iterator[Dict[str, Any]]*

Get an iterator of databases.

Parameters

- **catalog_id** (*str*, *optional*) – The ID of the Data Catalog from which to retrieve Databases. If none is provided, the AWS account ID is used by default.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Iterator of Databases.

Return type *Iterator[Dict[str, Any]]*

Examples

```
>>> import aws wrangler as wr
>>> dbs = wr.catalog.get_databases()
```

aws wrangler.catalog.get_engine

`aws wrangler.catalog.get_engine` (*connection*: *str*, *catalog_id*: *Optional[str] = None*, *boto3_session*: *Optional[boto3.session.Session] = None*) → *sqlalchemy.engine.base.Engine*

Return a SQLAlchemy Engine from a Glue Catalog Connection.

Only Redshift, PostgreSQL and MySQL are supported.

Parameters

- **connection** (*str*) – Connection name.
- **catalog_id** (*str*, *optional*) – The ID of the Data Catalog from which to retrieve Databases. If none is provided, the AWS account ID is used by default.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns SQLAlchemy Engine.

Return type *sqlalchemy.engine.Engine*

Examples

```
>>> import aws wrangler as wr
>>> res = wr.catalog.get_engine(name='my_connection')
```

awswrangler.catalog.get_parquet_partitions

```
awswrangler.catalog.get_parquet_partitions(database: str, table: str, expression:
Optional[str] = None, catalog_id: Op-
tional[str] = None, boto3_session: Op-
tional[boto3.session.Session] = None) →
Dict[str, List[str]]
```

Get all partitions from a Table in the AWS Glue Catalog.

Expression argument instructions: https://boto3.amazonaws.com/v1/documentation/api/latest/reference/services/glue.html#Glue.Client.get_partitions

Parameters

- **database** (*str*) – Database name.
- **table** (*str*) – Table name.
- **expression** (*str*, *optional*) – An expression that filters the partitions to be returned.
- **catalog_id** (*str*, *optional*) – The ID of the Data Catalog from which to retrieve Databases. If none is provided, the AWS account ID is used by default.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns partitions_values: Dictionary with keys as S3 path locations and values as a list of partitions values as str (e.g. {'s3://bucket/prefix/y=2020/m=10/': ['2020', '10']}).

Return type Dict[str, List[str]]

Examples

Fetch all partitions

```
>>> import awswrangler as wr
>>> wr.catalog.get_parquet_partitions(
...     database='default',
...     table='my_table',
... )
{
  's3://bucket/prefix/y=2020/m=10/': ['2020', '10'],
  's3://bucket/prefix/y=2020/m=11/': ['2020', '11'],
  's3://bucket/prefix/y=2020/m=12/': ['2020', '12']
}
```

Filtering partitions

```
>>> import awswrangler as wr
>>> wr.catalog.get_parquet_partitions(
...     database='default',
...     table='my_table',
...     expression='m=10'
... )
{
  's3://bucket/prefix/y=2020/m=10/': ['2020', '10']
}
```

awswrangler.catalog.get_table_description

```
awswrangler.catalog.get_table_description(database: str, table: str, catalog_id: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None) → str
```

Get table description.

Parameters

- **database** (*str*) – Database name.
- **table** (*str*) – Table name.
- **catalog_id** (*str*, *optional*) – The ID of the Data Catalog from which to retrieve Databases. If none is provided, the AWS account ID is used by default.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Description.

Return type str

Examples

```
>>> import awswrangler as wr
>>> desc = wr.catalog.get_table_description(database="...", table="...")
```

awswrangler.catalog.get_table_location

```
awswrangler.catalog.get_table_location(database: str, table: str, boto3_session: Optional[boto3.session.Session] = None) → str
```

Get table's location on Glue catalog.

Parameters

- **database** (*str*) – Database name.
- **table** (*str*) – Table name.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Table's location.

Return type str

Examples

```
>>> import awswrangler as wr
>>> wr.catalog.get_table_location(database='default', name='my_table')
's3://bucket/prefix/'
```

awswrangler.catalog.get_table_parameters

```
awswrangler.catalog.get_table_parameters(database: str, table: str, catalog_id: Op-
                                         tional[str] = None, boto3_session: Op-
                                         tional[boto3.session.Session] = None) →
                                         Dict[str, str]
```

Get all parameters.

Parameters

- **database** (*str*) – Database name.
- **table** (*str*) – Table name.
- **catalog_id** (*str*, *optional*) – The ID of the Data Catalog from which to retrieve Databases. If none is provided, the AWS account ID is used by default.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Dictionary of parameters.

Return type Dict[str, str]

Examples

```
>>> import awswrangler as wr
>>> pars = wr.catalog.get_table_parameters(database="...", table="...")
```

awswrangler.catalog.get_table_types

```
awswrangler.catalog.get_table_types(database: str, table: str, boto3_session: Op-
                                     tional[boto3.session.Session] = None) → Op-
                                     tional[Dict[str, str]]
```

Get all columns and types from a table.

Parameters

- **database** (*str*) – Database name.
- **table** (*str*) – Table name.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns If table exists, a dictionary like { 'col name': 'col data type' }. Otherwise None.

Return type Optional[Dict[str, str]]

Examples

```
>>> import awswrangler as wr
>>> wr.catalog.get_table_types(database='default', name='my_table')
{'col0': 'int', 'col1': double}
```

awswrangler.catalog.get_tables

`awswrangler.catalog.get_tables` (*catalog_id: Optional[str] = None, database: Optional[str] = None, name_contains: Optional[str] = None, name_prefix: Optional[str] = None, name_suffix: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None*) → *Iterator[Dict[str, Any]]*

Get an iterator of tables.

Note: Please, does not filter using `name_contains` and `name_prefix/name_suffix` at the same time. Only `name_prefix` and `name_suffix` can be combined together.

Parameters

- **catalog_id** (*str, optional*) – The ID of the Data Catalog from which to retrieve Databases. If none is provided, the AWS account ID is used by default.
- **database** (*str, optional*) – Database name.
- **name_contains** (*str, optional*) – Select by a specific string on table name
- **name_prefix** (*str, optional*) – Select by a specific prefix on table name
- **name_suffix** (*str, optional*) – Select by a specific suffix on table name
- **boto3_session** (*boto3.Session(), optional*) – Boto3 Session. The default boto3 session will be used if `boto3_session` receive None.

Returns Iterator of tables.

Return type `Iterator[Dict[str, Any]]`

Examples

```
>>> import awswrangler as wr
>>> tables = wr.catalog.get_tables()
```

awswrangler.catalog.overwrite_table_parameters

`awswrangler.catalog.overwrite_table_parameters` (*parameters: Dict[str, str], database: str, table: str, catalog_id: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None*) → *Dict[str, str]*

Overwrite all existing parameters.

Parameters

- **parameters** (*Dict[str, str]*) – e.g. {"source": "mysql", "destination": "data-lake"}
- **database** (*str*) – Database name.
- **table** (*str*) – Table name.
- **catalog_id** (*str, optional*) – The ID of the Data Catalog from which to retrieve Databases. If none is provided, the AWS account ID is used by default.
- **boto3_session** (*boto3.Session(), optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns All parameters after the overwrite (The same received).

Return type Dict[str, str]

Examples

```
>>> import awswrangler as wr
>>> pars = wr.catalog.overwrite_table_parameters(
...     parameters={"source": "mysql", "destination": "datalake"},
...     database="...",
...     table="...")
```

awswrangler.catalog.sanitize_column_name

awswrangler.catalog.**sanitize_column_name** (*column: str*) → str

Convert the column name to be compatible with Amazon Athena.

<https://docs.aws.amazon.com/athena/latest/ug/tables-databases-columns-names.html>

Possible transformations: - Strip accents - Remove non alphanumeric characters - Convert CamelCase to snake_case

Parameters **column** (*str*) – Column name.

Returns Normalized column name.

Return type str

Examples

```
>>> import awswrangler as wr
>>> wr.catalog.sanitize_column_name('MyNewColumn')
'my_new_column'
```

aws wrangler.catalog.sanitize_dataframe_columns_names

aws wrangler.catalog.**sanitize_dataframe_columns_names** (*df*: *pandas.core.frame.DataFrame*) → *pandas.core.frame.DataFrame*

Normalize all columns names to be compatible with Amazon Athena.

<https://docs.aws.amazon.com/athena/latest/ug/tables-databases-columns-names.html>

Possible transformations: - Strip accents - Remove non alphanumeric characters - Convert CamelCase to snake_case

Note: After transformation, some column names might not be unique anymore. Example: the columns ["A", "a"] will be sanitized to ["a", "a"]

Parameters **df** (*pandas.DataFrame*) – Original Pandas DataFrame.

Returns Original Pandas DataFrame with columns names normalized.

Return type *pandas.DataFrame*

Examples

```
>>> import aws wrangler as wr
>>> df_normalized = wr.catalog.sanitize_dataframe_columns_names(df=pd.DataFrame({
↪ 'A': [1, 2]}))
```

aws wrangler.catalog.sanitize_table_name

aws wrangler.catalog.**sanitize_table_name** (*table*: *str*) → *str*

Convert the table name to be compatible with Amazon Athena.

<https://docs.aws.amazon.com/athena/latest/ug/tables-databases-columns-names.html>

Possible transformations: - Strip accents - Remove non alphanumeric characters - Convert CamelCase to snake_case

Parameters **table** (*str*) – Table name.

Returns Normalized table name.

Return type *str*

Examples

```
>>> import aws wrangler as wr
>>> wr.catalog.sanitize_table_name('MyNewTable')
'my_new_table'
```


awswrangler.catalog.search_tables

`awswrangler.catalog.search_tables` (*text: str, catalog_id: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None*)

Get Pandas DataFrame of tables filtered by a search string.

Parameters

- **text** (*str, optional*) – Select only tables with the given string in table's properties.
- **catalog_id** (*str, optional*) – The ID of the Data Catalog from which to retrieve Databases. If none is provided, the AWS account ID is used by default.
- **boto3_session** (*boto3.Session(), optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Iterator of tables.

Return type Iterator[Dict[str, Any]]

Examples

```
>>> import awswrangler as wr
>>> df_tables = wr.catalog.search_tables(text='my_property')
```

awswrangler.catalog.table

`awswrangler.catalog.table` (*database: str, table: str, catalog_id: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None*) → `pandas.core.frame.DataFrame`

Get table details as Pandas DataFrame.

Parameters

- **database** (*str*) – Database name.
- **table** (*str*) – Table name.
- **catalog_id** (*str, optional*) – The ID of the Data Catalog from which to retrieve Databases. If none is provided, the AWS account ID is used by default.
- **boto3_session** (*boto3.Session(), optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Pandas DataFrame filled by formatted infos.

Return type `pandas.DataFrame`

Examples

```
>>> import awswrangler as wr
>>> df_table = wr.catalog.table(database='default', name='my_table')
```

aws wrangler.catalog.tables

```
aws wrangler.catalog.tables (limit: int = 100, catalog_id: Optional[str] = None, database:
                             Optional[str] = None, search_text: Optional[str] = None,
                             name_contains: Optional[str] = None, name_prefix: Op-
                             tional[str] = None, name_suffix: Optional[str] = None,
                             boto3_session: Optional[boto3.session.Session] = None) → pan-
                             das.core.frame.DataFrame
```

Get a DataFrame with tables filtered by a search term, prefix, suffix.

Parameters

- **limit** (*int*, *optional*) – Max number of tables to be returned.
- **catalog_id** (*str*, *optional*) – The ID of the Data Catalog from which to retrieve Databases. If none is provided, the AWS account ID is used by default.
- **database** (*str*, *optional*) – Database name.
- **search_text** (*str*, *optional*) – Select only tables with the given string in table's properties.
- **name_contains** (*str*, *optional*) – Select by a specific string on table name
- **name_prefix** (*str*, *optional*) – Select by a specific prefix on table name
- **name_suffix** (*str*, *optional*) – Select by a specific suffix on table name
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Pandas Dataframe filled by formatted infos.

Return type Iterator[Dict[str, Any]]

Examples

```
>>> import aws wrangler as wr
>>> df_tables = wr.catalog.tables()
```

aws wrangler.catalog.upsert_table_parameters

```
aws wrangler.catalog.upsert_table_parameters (parameters: Dict[str, str], database:
                                              str, table: str, catalog_id: Op-
                                              tional[str] = None, boto3_session: Op-
                                              tional[boto3.session.Session] = None) →
                                              Dict[str, str]
```

Insert or Update the received parameters.

Parameters

- **parameters** (*Dict[str, str]*) – e.g. {"source": "mysql", "destination": "data-lake"}
- **database** (*str*) – Database name.
- **table** (*str*) – Table name.
- **catalog_id** (*str*, *optional*) – The ID of the Data Catalog from which to retrieve Databases. If none is provided, the AWS account ID is used by default.

- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns All parameters after the upsert.

Return type Dict[str, str]

Examples

```
>>> import awswrangler as wr
>>> pars = wr.catalog.upsert_table_parameters(
...     parameters={"source": "mysql", "destination": "datalake"},
...     database="...",
...     table="...")
```

1.3.3 Amazon Athena

<code>create_athena_bucket([boto3_session])</code>	Create the default Athena bucket if it doesn't exist.
<code>get_query_columns_types(query_execution_id)</code>	Get the data type of all columns queried.
<code>get_work_group(workgroup[, boto3_session])</code>	Return information about the workgroup with the specified name.
<code>read_sql_query(sql, database[, ...])</code>	Execute any SQL query on AWS Athena and return the results as a Pandas DataFrame.
<code>read_sql_table(table, database[, ...])</code>	Extract the full table AWS Athena and return the results as a Pandas DataFrame.
<code>repair_table(table[, database, s3_output, ...])</code>	Run the Hive's metastore consistency check: 'MSCK REPAIR TABLE table;'. MSCK REPAIR TABLE table;
<code>start_query_execution(sql[, database, ...])</code>	Start a SQL Query against AWS Athena.
<code>stop_query_execution(query_execution_id[, ...])</code>	Stop a query execution.
<code>wait_query(query_execution_id[, boto3_session])</code>	Wait for the query end.

awswrangler.athena.create_athena_bucket

`awswrangler.athena.create_athena_bucket` (*boto3_session: Optional[boto3.session.Session] = None*) → str

Create the default Athena bucket if it doesn't exist.

Parameters **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Bucket s3 path (E.g. s3://aws-athena-query-results-ACCOUNT-REGION/)

Return type str

Examples

```
>>> import awswrangler as wr
>>> wr.athena.create_athena_bucket()
's3://aws-athena-query-results-ACCOUNT-REGION/'
```

awswrangler.athena.get_query_columns_types

`awswrangler.athena.get_query_columns_types(query_execution_id: str, boto3_session: Optional[boto3.session.Session] = None) → Dict[str, str]`

Get the data type of all columns queried.

<https://docs.aws.amazon.com/athena/latest/ug/data-types.html>

Parameters

- **query_execution_id** (*str*) – Athena query execution ID.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Dictionary with all data types.

Return type Dict[str, str]

Examples

```
>>> import awswrangler as wr
>>> wr.athena.get_query_columns_types('query-execution-id')
{'col0': 'int', 'col1': 'double'}
```

awswrangler.athena.get_work_group

`awswrangler.athena.get_work_group(workgroup: str, boto3_session: Optional[boto3.session.Session] = None) → Dict[str, Any]`

Return information about the workgroup with the specified name.

Parameters

- **workgroup** (*str*) – Work Group name.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns https://boto3.amazonaws.com/v1/documentation/api/latest/reference/services/athena.html#Athena.Client.get_work_group

Return type Dict[str, Any]

Examples

```
>>> import awswrangler as wr
>>> res = wr.athena.get_work_group(workgroup='workgroup_name')
```

awswrangler.athena.read_sql_query

```
awswrangler.athena.read_sql_query(sql: str, database: str, ctas_approach: bool = True,
                                  categories: List[str] = None, chunksize: Union[int,
                                  bool, None] = None, s3_output: Optional[str] =
                                  None, workgroup: Optional[str] = None, encryption:
                                  Optional[str] = None, kms_key: Optional[str] =
                                  None, keep_files: bool = True, ctas_temp_table_name:
                                  Optional[str] = None, use_threads: bool = True,
                                  boto3_session: Optional[boto3.session.Session] =
                                  None) → Union[pandas.core.frame.DataFrame, Iterator[pandas.core.frame.DataFrame]]
```

Execute any SQL query on AWS Athena and return the results as a Pandas DataFrame.

There are two approaches to be defined through `ctas_approach` parameter:

1 - `ctas_approach=True` (Default): Wrap the query with a CTAS and then reads the table data as parquet directly from s3. PROS: Faster and can handle some level of nested types. CONS: Requires create/delete table permissions on Glue and Does not support timestamp with time zone (A temporary table will be created and then deleted immediately).

2 - `ctas_approach=False`: Does a regular query on Athena and parse the regular CSV result on s3. PROS: Does not require create/delete table permissions on Glue and supports timestamp with time zone. CONS: Slower (But still faster than other libraries that uses the regular Athena API) and does not handle nested types at all.

Note: Valid encryption modes: [None, 'SSE_S3', 'SSE_KMS'].

P.S. 'CSE_KMS' is not supported.

Note: Create the default Athena bucket if it doesn't exist and `s3_output` is None.

(E.g. `s3://aws-athena-query-results-ACCOUNT-REGION/`)

Note: `Batching` (`chunksize` argument) (Memory Friendly):

Will enable the function to return a Iterable of DataFrames instead of a regular DataFrame.

There are two batching strategies on Wrangler:

- If `chunksize=True`, a new DataFrame will be returned for each file in the query result.
- If `chunked=INTEGER`, Wrangler will iterate on the data by number of rows equal the received INTEGER.

P.S. `chunksize=True` is faster and uses less memory while `chunksize=INTEGER` is more precise in number of rows for each DataFrame.

Note: In case of `use_threads=True` the number of threads that will be spawned will be get from `os.cpu_count()`.

Parameters

- **sql** (*str*) – SQL query.
- **database** (*str*) – AWS Glue/Athena database name.
- **ctas_approach** (*bool*) – Wraps the query using a CTAS, and read the resulted parquet data on S3. If false, read the regular CSV on S3.
- **categories** (*List[str], optional*) – List of columns names that should be returned as pandas.Categorical. Recommended for memory restricted environments.
- **chunksize** (*Union[int, bool], optional*) – If passed will split the data in a Iterable of DataFrames (Memory friendly). If *True* wrangler will iterate on the data by files in the most efficient way without guarantee of chunksize. If an *INTEGER* is passed Wrangler will iterate on the data by number of rows igual the received INTEGER.
- **s3_output** (*str, optional*) – AWS S3 path.
- **workgroup** (*str, optional*) – Athena workgroup.
- **encryption** (*str, optional*) – Valid values: [None, 'SSE_S3', 'SSE_KMS']. Notice: 'CSE_KMS' is not supported.
- **kms_key** (*str, optional*) – For SSE-KMS, this is the KMS key ARN or ID.
- **keep_files** (*bool*) – Should Wrangler delete or keep the staging files produced by Athena?
- **ctas_temp_table_name** (*str, optional*) – The name of the temporary table and also the directory name on S3 where the CTAS result is stored. If None, it will use the follow random pattern: *f"temp_table_{pyarrow.compat.guid()}"*. On S3 this directory will be under under the pattern: *f"{s3_output}/{ctas_temp_table_name}/"*.
- **use_threads** (*bool*) – True to enable concurrent requests, False to disable multiple threads. If enabled *os.cpu_count()* will be used as the max number of threads.
- **boto3_session** (*boto3.Session(), optional*) – Boto3 Session. The default boto3 session will be used if *boto3_session* receive None.

Returns Pandas DataFrame or Generator of Pandas DataFrames if chunksize is passed.

Return type Union[pd.DataFrame, Iterator[pd.DataFrame]]

Examples

```
>>> import awswrangler as wr
>>> df = wr.athena.read_sql_query(sql='...', database='...')
```

aws wrangler.athena.read_sql_table

```
aws wrangler.athena.read_sql_table (table: str, database: str, ctas_approach: bool = True,
                                     categories: List[str] = None, chunksize: Union[int,
                                     bool, None] = None, s3_output: Optional[str] =
                                     None, workgroup: Optional[str] = None, encryp-
                                     tion: Optional[str] = None, kms_key: Optional[str] =
                                     None, keep_files: bool = True, ctas_temp_table_name:
                                     Optional[str] = None, use_threads: bool = True,
                                     boto3_session: Optional[boto3.session.Session] =
                                     None) → Union[pandas.core.frame.DataFrame, Itera-
                                     tor[pandas.core.frame.DataFrame]]
```

Extract the full table AWS Athena and return the results as a Pandas DataFrame.

There are two approaches to be defined through `ctas_approach` parameter:

1 - `ctas_approach=True` (Default): Wrap the query with a CTAS and then reads the table data as parquet directly from s3. PROS: Faster and can handle some level of nested types CONS: Requires create/delete table permissions on Glue and Does not support timestamp with time zone (A temporary table will be created and then deleted immediately).

2 - `ctas_approach=False`: Does a regular query on Athena and parse the regular CSV result on s3. PROS: Does not require create/delete table permissions on Glue and give support timestamp with time zone. CONS: Slower (But stills faster than other libraries that uses the regular Athena API) and does not handle nested types at all

Note: Valid encryption modes: [None, 'SSE_S3', 'SSE_KMS'].

P.S. 'CSE_KMS' is not supported.

Note: Create the default Athena bucket if it doesn't exist and `s3_output` is None.

(E.g. `s3://aws-athena-query-results-ACCOUNT-REGION/`)

Note: *Batching* (`chunksize` argument) (Memory Friendly):

Will enable the function to return a Iterable of DataFrames instead of a regular DataFrame.

There are two batching strategies on Wrangler:

- If **chunksize=True**, a new DataFrame will be returned for each file in the query result.
- If **chunked=INTEGER**, Wrangler will iterate on the data by number of rows igual the received INTEGER.

P.S. chunksize=True if faster and uses less memory while *chunksize=INTEGER* is more precise in number of rows for each Dataframe.

Note: In case of `use_threads=True` the number of threads that will be spawned will be get from `os.cpu_count()`.

Parameters

- **table** (*str*) – Table name.
- **database** (*str*) – AWS Glue/Athena database name.

- **ctas_approach** (*bool*) – Wraps the query using a CTAS, and read the resulted parquet data on S3. If false, read the regular CSV on S3.
- **categories** (*List[str], optional*) – List of columns names that should be returned as pandas.Categorical. Recommended for memory restricted environments.
- **chunksize** (*Union[int, bool], optional*) – If passed will split the data in a Iterable of DataFrames (Memory friendly). If *True* wrangler will iterate on the data by files in the most efficient way without guarantee of chunksize. If an *INTEGER* is passed Wrangler will iterate on the data by number of rows igual the received INTEGER.
- **s3_output** (*str, optional*) – AWS S3 path.
- **workgroup** (*str, optional*) – Athena workgroup.
- **encryption** (*str, optional*) – None, 'SSE_S3', 'SSE_KMS', 'CSE_KMS'.
- **kms_key** (*str, optional*) – For SSE-KMS and CSE-KMS, this is the KMS key ARN or ID.
- **keep_files** (*bool*) – Should Wrangler delete or keep the staging files produced by Athena?
- **ctas_temp_table_name** (*str, optional*) – The name of the temporary table and also the directory name on S3 where the CTAS result is stored. If None, it will use the follow random pattern: *f"temp_table_{pyarrow.compat.guid()}"*. On S3 this directory will be under under the pattern: *f"{s3_output}/{ctas_temp_table_name}/"*.
- **use_threads** (*bool*) – True to enable concurrent requests, False to disable multiple threads. If enabled *os.cpu_count()* will be used as the max number of threads.
- **boto3_session** (*boto3.Session(), optional*) – Boto3 Session. The default boto3 session will be used if *boto3_session* receive None.

Returns Pandas DataFrame or Generator of Pandas DataFrames if chunksize is passed.

Return type Union[pd.DataFrame, Iterator[pd.DataFrame]]

Examples

```
>>> import awswrangler as wr
>>> df = wr.athena.read_sql_table(table='...', database='...')
```

awswrangler.athena.repair_table

```
awswrangler.athena.repair_table(table: str, database: Optional[str] = None, s3_output: Optional[str] = None, workgroup: Optional[str] = None, encryption: Optional[str] = None, kms_key: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None) → str
```

Run the Hive's metastore consistency check: 'MSCK REPAIR TABLE table;'.

Recovers partitions and data associated with partitions. Use this statement when you add partitions to the catalog. It is possible it will take some time to add all partitions. If this operation times out, it will be in an incomplete state where only a few partitions are added to the catalog.

Note: Create the default Athena bucket if it doesn't exist and `s3_output` is `None`. (E.g. `s3://aws-athena-query-results-ACCOUNT-REGION/`)

Parameters

- **table** (*str*) – Table name.
- **database** (*str*, *optional*) – AWS Glue/Athena database name.
- **s3_output** (*str*, *optional*) – AWS S3 path.
- **workgroup** (*str*, *optional*) – Athena workgroup.
- **encryption** (*str*, *optional*) – `None`, `'SSE_S3'`, `'SSE_KMS'`, `'CSE_KMS'`.
- **kms_key** (*str*, *optional*) – For SSE-KMS and CSE-KMS, this is the KMS key ARN or ID.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if `boto3_session` receive `None`.

Returns Query final state (`'SUCCEEDED'`, `'FAILED'`, `'CANCELLED'`).

Return type `str`

Examples

```
>>> import awswrangler as wr
>>> query_final_state = wr.athena.repair_table(table='...', database='...')
```

awswrangler.athena.start_query_execution

`awswrangler.athena.start_query_execution` (*sql*: *str*, *database*: *Optional[str]* = *None*, *s3_output*: *Optional[str]* = *None*, *workgroup*: *Optional[str]* = *None*, *encryption*: *Optional[str]* = *None*, *kms_key*: *Optional[str]* = *None*, *boto3_session*: *Optional[boto3.session.Session]* = *None*) → *str*

Start a SQL Query against AWS Athena.

Note: Create the default Athena bucket if it doesn't exist and `s3_output` is `None`. (E.g. `s3://aws-athena-query-results-ACCOUNT-REGION/`)

Parameters

- **sql** (*str*) – SQL query.
- **database** (*str*, *optional*) – AWS Glue/Athena database name.
- **s3_output** (*str*, *optional*) – AWS S3 path.
- **workgroup** (*str*, *optional*) – Athena workgroup.
- **encryption** (*str*, *optional*) – `None`, `'SSE_S3'`, `'SSE_KMS'`, `'CSE_KMS'`.

- **kms_key**(*str*, *optional*) – For SSE-KMS and CSE-KMS, this is the KMS key ARN or ID.
- **boto3_session**(*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Query execution ID

Return type str

Examples

```
>>> import awswrangler as wr
>>> query_exec_id = wr.athena.start_query_execution(sql='...', database='...')
```

awswrangler.athena.stop_query_execution

awswrangler.athena.stop_query_execution(*query_execution_id*: str, *boto3_session*: *Optional[boto3.session.Session]* = None) → None

Stop a query execution.

Requires you to have access to the workgroup in which the query ran.

Parameters

- **query_execution_id**(*str*) – Athena query execution ID.
- **boto3_session**(*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns None.

Return type None

Examples

```
>>> import awswrangler as wr
>>> wr.athena.stop_query_execution(query_execution_id='query-execution-id')
```

awswrangler.athena.wait_query

awswrangler.athena.wait_query(*query_execution_id*: str, *boto3_session*: *Optional[boto3.session.Session]* = None) → Dict[str, Any]

Wait for the query end.

Parameters

- **query_execution_id**(*str*) – Athena query execution ID.
- **boto3_session**(*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Dictionary with the get_query_execution response.

Return type Dict[str, Any]

Examples

```
>>> import awswrangler as wr
>>> res = wr.athena.wait_query(query_execution_id='query-execution-id')
```

1.3.4 Databases (Redshift, PostgreSQL, MySQL)

<code>copy_files_to_redshift(path, ..., mode, ...)</code>	Load Parquet files from S3 to a Table on Amazon Redshift (Through COPY command).
<code>copy_to_redshift(df, path, con, table, ...)</code>	Load Pandas DataFrame as a Table on Amazon Redshift using parquet files on S3 as stage.
<code>get_engine(db_type, host, port, database, ...)</code>	Return a SQLAlchemy Engine from the given arguments.
<code>get_redshift_temp_engine(cluster_identifier, ...)</code>	Get Glue connection details.
<code>read_sql_query(sql, con[, index_col, ...])</code>	Return a DataFrame corresponding to the result set of the query string.
<code>read_sql_table(table, con[, schema, ...])</code>	Return a DataFrame corresponding to the result set of the query string.
<code>to_sql(df, con, **pandas_kwargs)</code>	Write records stored in a DataFrame to a SQL database.
<code>unload_redshift(sql, path, con, iam_role[, ...])</code>	Load Pandas DataFrame from a Amazon Redshift query result using Parquet files on s3 as stage.
<code>unload_redshift_to_files(sql, path, con, ...)</code>	Unload Parquet files from a Amazon Redshift query result to parquet files on s3 (Through UNLOAD command).
<code>write_redshift_copy_manifest(manifest_path, ...)</code>	Write Redshift copy manifest and return its structure.

awswrangler.db.copy_files_to_redshift

`awswrangler.db.copy_files_to_redshift` (*path*: Union[str, List[str]], *manifest_directory*: str, *con*: sqlalchemy.engine.base.Engine, *table*: str, *schema*: str, *iam_role*: str, *mode*: str = 'append', *diststyle*: str = 'AUTO', *distkey*: Optional[str] = None, *sortstyle*: str = 'COMPOUND', *sortkey*: Optional[List[str]] = None, *primary_keys*: Optional[List[str]] = None, *varchar_lengths_default*: int = 256, *varchar_lengths*: Optional[Dict[str, int]] = None, *use_threads*: bool = True, *boto3_session*: Optional[boto3.session.Session] = None) → None

Load Parquet files from S3 to a Table on Amazon Redshift (Through COPY command).

https://docs.aws.amazon.com/redshift/latest/dg/r_COPY.html

Note: If the table does not exist yet, it will be automatically created for you using the Parquet metadata to infer the columns data types.

Note: In case of `use_threads=True` the number of threads that will be spawned will be get from `os.cpu_count()`.

Parameters

- **path** (*Union[str, List[str]]*) – S3 prefix (e.g. `s3://bucket/prefix`) or list of S3 objects paths (e.g. `[s3://bucket/key0, s3://bucket/key1]`).
- **manifest_directory** (*str*) – S3 prefix (e.g. `s3://bucket/prefix`)
- **con** (*sqlalchemy.engine.Engine*) – SQLAlchemy Engine. Please use, `wr.db.get_engine()`, `wr.db.get_redshift_temp_engine()` or `wr.catalog.get_engine()`
- **table** (*str*) – Table name
- **schema** (*str*) – Schema name
- **iam_role** (*str*) – AWS IAM role with the related permissions.
- **mode** (*str*) – Append, overwrite or upsert.
- **diststyle** (*str*) – Redshift distribution styles. Must be in ["AUTO", "EVEN", "ALL", "KEY"]. https://docs.aws.amazon.com/redshift/latest/dg/t_Distributing_data.html
- **distkey** (*str, optional*) – Specifies a column name or positional number for the distribution key.
- **sortstyle** (*str*) – Sorting can be "COMPOUND" or "INTERLEAVED". https://docs.aws.amazon.com/redshift/latest/dg/t_Sorting_data.html
- **sortkey** (*List[str], optional*) – List of columns to be sorted.
- **primary_keys** (*List[str], optional*) – Primary keys.
- **varchar_lengths_default** (*int*) – The size that will be set for all VARCHAR columns not specified with `varchar_lengths`.
- **varchar_lengths** (*Dict[str, int], optional*) – Dict of VARCHAR length by columns. (e.g. `{"col1": 10, "col5": 200}`).
- **use_threads** (*bool*) – True to enable concurrent requests, False to disable multiple threads. If enabled `os.cpu_count()` will be used as the max number of threads.
- **boto3_session** (*boto3.Session(), optional*) – Boto3 Session. The default boto3 session will be used if `boto3_session` receive None.

Returns None.

Return type None

Examples

```
>>> import awswrangler as wr
>>> wr.db.copy_files_to_redshift(
...     path="s3://bucket/my_parquet_files/",
...     con=wr.catalog.get_engine(connection="my_glue_conn_name"),
...     table="my_table",
...     schema="public"
...     iam_role="arn:aws:iam::XXX:role/XXX"
... )
```

awswrangler.db.copy_to_redshift

```
awswrangler.db.copy_to_redshift(df: pandas.core.frame.DataFrame, path: str, con:
                                sqlalchemy.engine.base.Engine, table: str, schema: str,
                                iam_role: str, index: bool = False, dtype: Optional[Dict[str,
                                str]] = None, mode: str = 'append', diststyle: str = 'AUTO',
                                distkey: Optional[str] = None, sortstyle: str = 'COMPOUND',
                                sortkey: Optional[List[str]] = None, primary_keys: Op-
                                tional[List[str]] = None, varchar_lengths_default: int = 256,
                                varchar_lengths: Optional[Dict[str, int]] = None, keep_files:
                                bool = False, use_threads: bool = True, boto3_session: Op-
                                tional[boto3.session.Session] = None, s3_additional_kwargs:
                                Optional[Dict[str, str]] = None) → None
```

Load Pandas DataFrame as a Table on Amazon Redshift using parquet files on S3 as stage.

This is a **HIGH** latency and **HIGH** throughput alternative to `wr.db.to_sql()` to load large DataFrames into Amazon Redshift through the **** SQL COPY command****.

This strategy has more overhead and requires more IAM privileges than the regular `wr.db.to_sql()` function, so it is only recommended to inserting +1MM rows at once.

https://docs.aws.amazon.com/redshift/latest/dg/r_COPY.html

Note: If the table does not exist yet, it will be automatically created for you using the Parquet metadata to infer the columns data types.

Note: In case of `use_threads=True` the number of threads that will be spawned will be get from `os.cpu_count()`.

Parameters

- **df** (`pandas.DataFrame`) – Pandas DataFrame.
- **path** (`Union[str, List[str]]`) – S3 path to write stage files (e.g. `s3://bucket_name/any_name/`)
- **con** (`sqlalchemy.engine.Engine`) – SQLAlchemy Engine. Please use, `wr.db.get_engine()`, `wr.db.get_redshift_temp_engine()` or `wr.catalog.get_engine()`
- **table** (`str`) – Table name
- **schema** (`str`) – Schema name
- **iam_role** (`str`) – AWS IAM role with the related permissions.
- **index** (`bool`) – True to store the DataFrame index in file, otherwise False to ignore it.
- **dtype** (`Dict[str, str], optional`) – Dictionary of columns names and Athena/Glue types to be casted. Useful when you have columns with undetermined or mixed data types. Only takes effect if `dataset=True`. (e.g. `{'col name': 'bigint', 'col2 name': 'int'}`)
- **mode** (`str`) – Append, overwrite or upsert.
- **diststyle** (`str`) – Redshift distribution styles. Must be in [“AUTO”, “EVEN”, “ALL”, “KEY”]. https://docs.aws.amazon.com/redshift/latest/dg/t_Distributing_data.html
- **distkey** (`str, optional`) – Specifies a column name or positional number for the distribution key.

- **sortstyle** (*str*) – Sorting can be “COMPOUND” or “INTERLEAVED”. https://docs.aws.amazon.com/redshift/latest/dg/t_Sorting_data.html
- **sortkey** (*List[str]*, *optional*) – List of columns to be sorted.
- **primary_keys** (*List[str]*, *optional*) – Primary keys.
- **varchar_lengths_default** (*int*) – The size that will be set for all VARCHAR columns not specified with `varchar_lengths`.
- **varchar_lengths** (*Dict[str, int]*, *optional*) – Dict of VARCHAR length by columns. (e.g. {"col1": 10, "col5": 200}).
- **keep_files** (*bool*) – Should keep the stage files?
- **use_threads** (*bool*) – True to enable concurrent requests, False to disable multiple threads. If enabled `os.cpu_count()` will be used as the max number of threads.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if `boto3_session` receive None.
- **s3_additional_kwargs** – Forward to s3fs, useful for server side encryption <https://s3fs.readthedocs.io/en/latest/#serverside-encryption>

Returns None.

Return type None

Examples

```
>>> import awswrangler as wr
>>> import pandas as pd
>>> wr.db.copy_to_redshift(
...     df=pd.DataFrame({'col': [1, 2, 3]}),
...     path="s3://bucket/my_parquet_files/",
...     con=wr.catalog.get_engine(connection="my_glue_conn_name"),
...     table="my_table",
...     schema="public"
...     iam_role="arn:aws:iam::XXX:role/XXX"
... )
```

awswrangler.db.get_engine

`awswrangler.db.get_engine` (*db_type: str, host: str, port: int, database: str, user: str, password: str*)
→ `sqlalchemy.engine.base.Engine`

Return a SQLAlchemy Engine from the given arguments.

Only Redshift, PostgreSQL and MySQL are supported.

Parameters

- **db_type** (*str*) – Database type: “redshift”, “mysql” or “postgresql”.
- **host** (*str*) – Host address.
- **port** (*str*) – Port number.
- **database** (*str*) – Database name.
- **user** (*str*) – Username.
- **password** (*str*) – Password.

Returns SQLAlchemy Engine.

Return type sqlalchemy.engine.Engine

Examples

```
>>> import awswrangler as wr
>>> engine = wr.db.get_engine(
...     db_type="postgresql",
...     host="...",
...     port=1234,
...     database="...",
...     user="...",
...     password="..."
... )
```

awswrangler.db.get_redshift_temp_engine

`awswrangler.db.get_redshift_temp_engine` (*cluster_identifier: str, user: str, database: Optional[str] = None, duration: int = 900, boto3_session: Optional[boto3.session.Session] = None*) → sqlalchemy.engine.base.Engine

Get Glue connection details.

Parameters

- **cluster_identifier** (*str*) – The unique identifier of a cluster. This parameter is case sensitive.
- **user** (*str, optional*) – The name of a database user.
- **database** (*str, optional*) – Database name. If None, the default Database is used.
- **duration** (*int, optional*) – The number of seconds until the returned temporary password expires. Constraint: minimum 900, maximum 3600. Default: 900
- **boto3_session** (*boto3.Session(), optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns SQLAlchemy Engine.

Return type sqlalchemy.engine.Engine

Examples

```
>>> import awswrangler as wr
>>> engine = wr.db.get_redshift_temp_engine('my_cluster', 'my_user')
```

aws wrangler.db.read_sql_query

```
aws wrangler.db.read_sql_query (sql: str, con: sqlalchemy.engine.base.Engine, index_col:
                                Union[str, List[str], None] = None, params: Union[List,
                                Tuple, Dict, None] = None, chunksize: Optional[int] =
                                None, dtype: Optional[Dict[str, pyarrow.lib.DataType]]
                                = None) → Union[pandas.core.frame.DataFrame, Itera-
                                tor[pandas.core.frame.DataFrame]]
```

Return a DataFrame corresponding to the result set of the query string.

Support for **Redshift**, **PostgreSQL** and **MySQL**.

Note: Redshift: For large extractions (1MM+ rows) consider the function **wr.db.unload_redshift()**.

Parameters

- **sql** (*str*) – Pandas DataFrame <https://pandas.pydata.org/pandas-docs/stable/reference/api/pandas.DataFrame.html>
- **con** (*sqlalchemy.engine.Engine*) – SQLAlchemy Engine. Please use, `wr.db.get_engine()`, `wr.db.get_redshift_temp_engine()` or `wr.catalog.get_engine()`
- **index_col** (*Union[str, List[str]]*, *optional*) – Column(s) to set as index(MultiIndex).
- **params** (*Union[List, Tuple, Dict]*, *optional*) – List of parameters to pass to execute method. The syntax used to pass parameters is database driver dependent. Check your database driver documentation for which of the five syntax styles, described in PEP 249's paramstyle, is supported. Eg. for psycopg2, uses %(name)s so use `params={'name': 'value'}`.
- **chunksize** (*int*, *optional*) – If specified, return an iterator where chunksize is the number of rows to include in each chunk.
- **dtype** (*Dict[str, pyarrow.DataType]*, *optional*) – Specifying the datatype for columns. The keys should be the column names and the values should be the PyArrow types.

Returns Result as Pandas DataFrame(s).

Return type Union[pandas.DataFrame, Iterator[pandas.DataFrame]]

Examples

Reading from Redshift with temporary credentials

```
>>> import aws wrangler as wr
>>> df = wr.db.read_sql_query(
...     sql="SELECT * FROM public.my_table",
...     con=wr.db.get_redshift_temp_engine(cluster_identifier="...", user="...")
... )
```

Reading from Redshift from Glue Catalog Connections

```
>>> import aws wrangler as wr
>>> df = wr.db.read_sql_query(
...     sql="SELECT * FROM public.my_table",
```

(continues on next page)

(continued from previous page)

```
... con=wr.catalog.get_engine(connection="...")
... )
```

awswrangler.db.read_sql_table

```
awswrangler.db.read_sql_table(table: str, con: sqlalchemy.engine.base.Engine, schema:
Optional[str] = None, index_col: Union[str, List[str],
None] = None, params: Union[List, Tuple, Dict,
None] = None, chunksize: Optional[int] = None,
dtype: Optional[Dict[str, pyarrow.lib.DataType]] =
None) → Union[pandas.core.frame.DataFrame,
Iterator[pandas.core.frame.DataFrame]]
```

Return a DataFrame corresponding to the result set of the query string.

Support for **Redshift**, **PostgreSQL** and **MySQL**.

Note: Redshift: For large extractions (1MM+ rows) consider the function `wr.db.unload_redshift()`.

Parameters

- **table** (*str*) – Nable name.
- **con** (*sqlalchemy.engine.Engine*) – SQLAlchemy Engine. Please use, `wr.db.get_engine()`, `wr.db.get_redshift_temp_engine()` or `wr.catalog.get_engine()`
- **schema** (*str, optional*) – Name of SQL schema in database to query (if database flavor supports this). Uses default schema if None (default).
- **index_col** (*Union[str, List[str]], optional*) – Column(s) to set as index(MultiIndex).
- **params** (*Union[List, Tuple, Dict], optional*) – List of parameters to pass to execute method. The syntax used to pass parameters is database driver dependent. Check your database driver documentation for which of the five syntax styles, described in PEP 249's paramstyle, is supported. Eg. for psycopg2, uses `%(name)s` so use `params={'name': 'value'}`.
- **chunksize** (*int, optional*) – If specified, return an iterator where chunksize is the number of rows to include in each chunk.
- **dtype** (*Dict[str, pyarrow.DataType], optional*) – Specifying the datatype for columns. The keys should be the column names and the values should be the PyArrow types.

Returns Result as Pandas DataFrame(s).

Return type Union[pandas.DataFrame, Iterator[pandas.DataFrame]]

Examples

Reading from Redshift with temporary credentials

```
>>> import awswrangler as wr
>>> df = wr.db.read_sql_table(
...     table="my_table",
...     schema="public",
...     con=wr.db.get_redshift_temp_engine(cluster_identifier="...", user="...")
... )
```

Reading from Redshift from Glue Catalog Connections

```
>>> import awswrangler as wr
>>> df = wr.db.read_sql_table(
...     table="my_table",
...     schema="public",
...     con=wr.catalog.get_engine(connection="...")
... )
```

awswrangler.db.to_sql

`awswrangler.db.to_sql(df: pandas.core.frame.DataFrame, con: sqlalchemy.engine.base.Engine, **pandas_kwargs) → None`

Write records stored in a DataFrame to a SQL database.

Support for **Redshift**, **PostgreSQL** and **MySQL**.

Support for all pandas `to_sql()` arguments: https://pandas.pydata.org/pandas-docs/stable/reference/api/pandas.DataFrame.to_sql.html

Note: Redshift: For large DataFrames (1MM+ rows) consider the function `wr.db.copy_to_redshift()`.

Note: Redshift: `index=False` will be forced.

Parameters

- **df** (`pandas.DataFrame`) – Pandas DataFrame <https://pandas.pydata.org/pandas-docs/stable/reference/api/pandas.DataFrame.html>
- **con** (`sqlalchemy.engine.Engine`) – SQLAlchemy Engine. Please use, `wr.db.get_engine()`, `wr.db.get_redshift_temp_engine()` or `wr.catalog.get_engine()`
- **pandas_kwargs** – keyword arguments forwarded to `pandas.DataFrame.to_csv()` https://pandas.pydata.org/pandas-docs/stable/reference/api/pandas.DataFrame.to_sql.html

Returns None.

Return type None

Examples

Writing to Redshift with temporary credentials

```
>>> import awswrangler as wr
>>> import pandas as pd
>>> wr.db.to_sql(
...     df=pd.DataFrame({'col': [1, 2, 3]}),
...     con=wr.db.get_redshift_temp_engine(cluster_identifier="...", user="..."),
...     name="table_name",
...     schema="schema_name"
... )
```

Writing to Redshift from Glue Catalog Connections

```
>>> import awswrangler as wr
>>> import pandas as pd
>>> wr.db.to_sql(
...     df=pd.DataFrame({'col': [1, 2, 3]}),
...     con=wr.catalog.get_engine(connection="..."),
...     name="table_name",
...     schema="schema_name"
... )
```

awswrangler.db.unload_redshift

`awswrangler.db.unload_redshift` (*sql*: str, *path*: str, *con*: sqlalchemy.engine.base.Engine, *iam_role*: str, *region*: Optional[str] = None, *max_file_size*: Optional[float] = None, *kms_key_id*: Optional[str] = None, *categories*: List[str] = None, *chunked*: Union[bool, int] = False, *keep_files*: bool = False, *use_threads*: bool = True, *boto3_session*: Optional[boto3.session.Session] = None, *s3_additional_kwargs*: Optional[Dict[str, str]] = None) → Union[pandas.core.frame.DataFrame, Iterator[pandas.core.frame.DataFrame]]

Load Pandas DataFrame from a Amazon Redshift query result using Parquet files on s3 as stage.

This is a **HIGH** latency and **HIGH** throughput alternative to `wr.db.read_sql_query()/wr.db.read_sql_table()` to extract large Amazon Redshift data into a Pandas DataFrames through the **UNLOAD command**.

This strategy has more overhead and requires more IAM privileges than the regular `wr.db.read_sql_query()/wr.db.read_sql_table()` function, so it is only recommended to fetch +1MM rows at once.

https://docs.aws.amazon.com/redshift/latest/dg/r_UNLOAD.html

Note: Batching (*chunked* argument) (Memory Friendly):

Will enable the function to return a Iterable of DataFrames instead of a regular DataFrame.

There are two batching strategies on Wrangler:

- If **chunked=True**, a new DataFrame will be returned for each file in your path/dataset.
- If **chunked=INTEGER**, Wrangler will iterate on the data by number of rows igual the received INTEGER.

P.S. `chunked=True` if faster and uses less memory while `chunked=INTEGER` is more precise in number of rows for each Dataframe.

Note: In case of `use_threads=True` the number of threads that will be spawned will be get from `os.cpu_count()`.

Parameters

- **sql** (*str*) – SQL query.
- **path** (*Union[str, List[str]]*) – S3 path to write stage files (e.g. `s3://bucket_name/any_name/`)
- **con** (*sqlalchemy.engine.Engine*) – SQLAlchemy Engine. Please use, `wr.db.get_engine()`, `wr.db.get_redshift_temp_engine()` or `wr.catalog.get_engine()`
- **iam_role** (*str*) – AWS IAM role with the related permissions.
- **region** (*str, optional*) – Specifies the AWS Region where the target Amazon S3 bucket is located. REGION is required for UNLOAD to an Amazon S3 bucket that isn't in the same AWS Region as the Amazon Redshift cluster. By default, UNLOAD assumes that the target Amazon S3 bucket is located in the same AWS Region as the Amazon Redshift cluster.
- **max_file_size** (*float, optional*) – Specifies the maximum size (MB) of files that UNLOAD creates in Amazon S3. Specify a decimal value between 5.0 MB and 6200.0 MB. If None, the default maximum file size is 6200.0 MB.
- **kms_key_id** (*str, optional*) – Specifies the key ID for an AWS Key Management Service (AWS KMS) key to be used to encrypt data files on Amazon S3.
- **categories** (*List[str], optional*) – List of columns names that should be returned as `pandas.Categorical`. Recommended for memory restricted environments.
- **keep_files** (*bool*) – Should keep the stage files?
- **chunked** (*Union[int, bool]*) – If passed will split the data in a Iterable of DataFrames (Memory friendly). If `True` wrangler will iterate on the data by files in the most efficient way without guarantee of chunksize. If an `INTEGER` is passed Wrangler will iterate on the data by number of rows igual the received `INTEGER`.
- **use_threads** (*bool*) – True to enable concurrent requests, False to disable multiple threads. If enabled `os.cpu_count()` will be used as the max number of threads.
- **boto3_session** (*boto3.Session(), optional*) – Boto3 Session. The default boto3 session will be used if `boto3_session` receive None.
- **s3_additional_kwargs** – Forward to s3fs, useful for server side encryption <https://s3fs.readthedocs.io/en/latest/#serverside-encryption>

Returns Pandas DataFrame

Return type `pandas.DataFrame`

Examples

```
>>> import awswrangler as wr
>>> import pandas as pd
>>> df = wr.db.unload_redshift(
...     sql="SELECT * FROM public.mytable",
...     path="s3://bucket/extracted_parquet_files/",
...     con=wr.catalog.get_engine(connection="my_glue_connection"),
...     iam_role="arn:aws:iam::XXX:role/XXX"
... )
```

awswrangler.db.unload_redshift_to_files

```
awswrangler.db.unload_redshift_to_files (sql: str, path: str, con:
                                         sqlalchemy.engine.base.Engine, iam_role: str,
                                         region: Optional[str] = None, max_file_size:
                                         Optional[float] = None, kms_key_id: Optional[str]
                                         = None, use_threads: bool = True, manifest: bool
                                         = False, partition_cols: Optional[List] = None,
                                         boto3_session: Optional[boto3.session.Session] =
                                         None) → List[str]
```

Unload Parquet files from a Amazon Redshift query result to parquet files on s3 (Through UNLOAD command).

https://docs.aws.amazon.com/redshift/latest/dg/r_UNLOAD.html

Note: In case of `use_threads=True` the number of threads that will be spawned will be get from `os.cpu_count()`.

Parameters

- **sql** (*str*) – SQL query.
- **path** (*Union[str, List[str]]*) – S3 path to write stage files (e.g. `s3://bucket_name/any_name/`)
- **con** (*sqlalchemy.engine.Engine*) – SQLAlchemy Engine. Please use, `wr.db.get_engine()`, `wr.db.get_redshift_temp_engine()` or `wr.catalog.get_engine()`
- **iam_role** (*str*) – AWS IAM role with the related permissions.
- **region** (*str, optional*) – Specifies the AWS Region where the target Amazon S3 bucket is located. REGION is required for UNLOAD to an Amazon S3 bucket that isn't in the same AWS Region as the Amazon Redshift cluster. By default, UNLOAD assumes that the target Amazon S3 bucket is located in the same AWS Region as the Amazon Redshift cluster.
- **max_file_size** (*float, optional*) – Specifies the maximum size (MB) of files that UNLOAD creates in Amazon S3. Specify a decimal value between 5.0 MB and 6200.0 MB. If None, the default maximum file size is 6200.0 MB.
- **kms_key_id** (*str, optional*) – Specifies the key ID for an AWS Key Management Service (AWS KMS) key to be used to encrypt data files on Amazon S3.
- **use_threads** (*bool*) – True to enable concurrent requests, False to disable multiple threads. If enabled `os.cpu_count()` will be used as the max number of threads.
- **manifest** (*bool*) – Unload a manifest file on S3.

- **partition_cols** (*List[str], optional*) – Specifies the partition keys for the unload operation.
- **boto3_session** (*boto3.Session(), optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Paths list with all unloaded files.

Return type List[str]

Examples

```
>>> import awswrangler as wr
>>> paths = wr.db.unload_redshift_to_files(
...     sql="SELECT * FROM public.mytable",
...     path="s3://bucket/extracted_parquet_files/",
...     con=wr.catalog.get_engine(connection="my_glue_connection"),
...     iam_role="arn:aws:iam::XXX:role/XXX"
... )
```

awswrangler.db.write_redshift_copy_manifest

`awswrangler.db.write_redshift_copy_manifest` (*manifest_path: str, paths: List[str], use_threads: bool = True, boto3_session: Optional[boto3.session.Session] = None*)
→ Dict[str, List[Dict[str, Union[str, bool, Dict[str, int]]]]]

Write Redshift copy manifest and return its structure.

Only Parquet files are supported.

Note: In case of *use_threads=True* the number of threads that will be spawned will be get from `os.cpu_count()`.

Parameters

- **manifest_path** (*str*) – Amazon S3 manifest path (e.g. `s3://...`)
- **paths** (*List[str]*) – List of S3 paths (Parquet Files) to be copied.
- **use_threads** (*bool*) – True to enable concurrent requests, False to disable multiple threads. If enabled `os.cpu_count()` will be used as the max number of threads.
- **boto3_session** (*boto3.Session(), optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Manifest content.

Return type Dict[str, List[Dict[str, Union[str, bool, Dict[str, int]]]]]

Examples

Copying two files to Redshift cluster.

```
>>> import awswrangler as wr
>>> wr.db.write_redshift_copy_manifest(
...     path="s3://bucket/my.manifest",
...     paths=["s3://...parquet", "s3://...parquet"]
... )
```

1.3.5 EMR

<code>build_spark_step(path[, deploy_mode, ...])</code>	Build the Step structure (dictionary).
<code>build_step(command[, name, ...])</code>	Build the Step structure (dictionary).
<code>create_cluster(subnet_id[, cluster_name, ...])</code>	Create a EMR cluster with instance fleets configuration.
<code>get_cluster_state(cluster_id[, boto3_session])</code>	Get the EMR cluster state.
<code>get_step_state(cluster_id, step_id[, ...])</code>	Get EMR step state.
<code>submit_ecr_credentials_refresh(cluster_id, path)</code>	Update internal ECR credentials.
<code>submit_spark_step(cluster_id, path[, ...])</code>	Submit Spark Step.
<code>submit_step(cluster_id, command[, name, ...])</code>	Submit new job in the EMR Cluster.
<code>submit_steps(cluster_id, steps[, boto3_session])</code>	Submit a list of steps.
<code>terminate_cluster(cluster_id[, boto3_session])</code>	Terminate EMR cluster.

awswrangler.emr.build_spark_step

`awswrangler.emr.build_spark_step` (*path*: *str*, *deploy_mode*: *str* = 'cluster', *docker_image*: *Optional[str]* = None, *name*: *str* = 'my-step', *action_on_failure*: *str* = 'CONTINUE', *region*: *Optional[str]* = None, *boto3_session*: *Optional[boto3.session.Session]* = None) → Dict[str, Any]

Build the Step structure (dictionary).

Parameters

- **path** (*str*) – Script path. (e.g. s3://bucket/app.py)
- **deploy_mode** (*str*) – “cluster” | “client”
- **docker_image** (*str*, *optional*) – e.g. “{ACCOUNT_ID}.dkr.ecr.{REGION}.amazonaws.com/{IMAGE_NAME}:{TAG}”
- **name** (*str*, *optional*) – Step name.
- **action_on_failure** (*str*) – ‘TERMINATE_JOB_FLOW’, ‘TERMINATE_CLUSTER’, ‘CANCEL_AND_WAIT’, ‘CONTINUE’
- **region** (*str*, *optional*) – Region name to not get it from boto3.Session. (e.g. *us-east-1*)
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Step structure.

Return type Dict[str, Any]

Examples

```
>>> import awswrangler as wr
>>> step_id = wr.emr.submit_steps(
>>>     cluster_id="cluster-id",
>>>     steps=[
>>>         wr.emr.build_spark_step(path="s3://bucket/app.py")
>>>     ]
>>> )
```

awswrangler.emr.build_step

`awswrangler.emr.build_step`(*command*: str, *name*: str = 'my-step', *action_on_failure*: str = 'CONTINUE', *script*: bool = False, *region*: Optional[str] = None, *boto3_session*: Optional[boto3.session.Session] = None) → Dict[str, Any]

Build the Step structure (dictionary).

Parameters

- **command** (str) – e.g. 'echo "Hello!"' e.g. for script 's3://.../script.sh arg1 arg2'
- **name** (str, optional) – Step name.
- **action_on_failure** (str) – 'TERMINATE_JOB_FLOW', 'TERMINATE_CLUSTER', 'CANCEL_AND_WAIT', 'CONTINUE'
- **script** (bool) – False for raw command or True for script runner. <https://docs.aws.amazon.com/emr/latest/ReleaseGuide/emr-commandrunner.html>
- **region** (str, optional) – Region name to not get it from boto3.Session. (e.g. *us-east-1*)
- **boto3_session** (boto3.Session(), optional) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Step structure.

Return type Dict[str, Any]

Examples

```
>>> import awswrangler as wr
>>> for cmd in ['echo "Hello"', 'ls -la']:
...     steps.append(wr.emr.build_step(name=cmd, command=cmd))
>>> wr.emr.submit_steps(cluster_id="cluster-id", steps=steps)
```


aws wrangler.emr.create_cluster

```
aws wrangler.emr.create_cluster(subnet_id: str, cluster_name: str = 'my-emr-
cluster', logging_s3_path: Optional[str] = None,
emr_release: str = 'emr-6.0.0', emr_ec2_role:
str = 'EMR_EC2_DefaultRole', emr_role: str =
'EMR_DefaultRole', instance_type_master: str = 'r5.xlarge',
instance_type_core: str = 'r5.xlarge', instance_type_task:
str = 'r5.xlarge', instance_ebs_size_master: int = 64, in-
stance_ebs_size_core: int = 64, instance_ebs_size_task:
int = 64, instance_num_on_demand_master: int
= 1, instance_num_on_demand_core: int = 0,
instance_num_on_demand_task: int = 0, in-
stance_num_spot_master: int = 0, instance_num_spot_core:
int = 0, instance_num_spot_task: int = 0,
spot_bid_percentage_of_on_demand_master: int =
100, spot_bid_percentage_of_on_demand_core: int
= 100, spot_bid_percentage_of_on_demand_task:
int = 100, spot_provisioning_timeout_master:
int = 5, spot_provisioning_timeout_core: int
= 5, spot_provisioning_timeout_task: int = 5,
spot_timeout_to_on_demand_master: bool = True,
spot_timeout_to_on_demand_core: bool = True,
spot_timeout_to_on_demand_task: bool = True, python3: bool
= True, spark_glue_catalog: bool = True, hive_glue_catalog:
bool = True, presto_glue_catalog: bool = True, consistent_view:
bool = False, consistent_view_retry_seconds: int = 10, consis-
tent_view_retry_count: int = 5, consistent_view_table_name:
str = 'EmrFSMetadata', bootstraps_paths: Optional[List[str]] =
None, debugging: bool = True, applications: Optional[List[str]]
= None, visible_to_all_users: bool = True, key_pair_name:
Optional[str] = None, security_group_master: Optional[str] =
None, security_groups_master_additional: Optional[List[str]]
= None, security_group_slave: Optional[str] = None, se-
curity_groups_slave_additional: Optional[List[str]] =
None, security_group_service_access: Optional[str] =
None, docker: bool = False, extra_public_registries: Op-
tional[List[str]] = None, spark_log_level: str = 'WARN',
spark_jars_path: Optional[List[str]] = None, spark_defaults:
Optional[Dict[str, str]] = None, spark_pyarrow: bool
= False, custom_classifications: Optional[List[Dict[str,
Any]]] = None, maximize_resource_allocation: bool =
False, steps: Optional[List[Dict[str, Any]]] = None,
keep_cluster_alive_when_no_steps: bool = True, termina-
tion_protected: bool = False, tags: Optional[Dict[str, str]] =
None, boto3_session: Optional[boto3.session.Session] = None)
→ str
```

Create a EMR cluster with instance fleets configuration.

<https://docs.aws.amazon.com/emr/latest/ManagementGuide/emr-instance-fleet.html>

Parameters

- **subnet_id** (*str*) – VPC subnet ID.
- **cluster_name** (*str*) – Cluster name.

- **logging_s3_path** (*str*, *optional*) – Logging s3 path (e.g. `s3://BUCKET_NAME/DIRECTORY_NAME/`). If None, the default is `s3://aws-logs-{AccountId}-{RegionId}/elasticmapreduce/`
- **emr_release** (*str*) – EMR release (e.g. `emr-5.28.0`).
- **emr_ec2_role** (*str*) – IAM role name.
- **emr_role** (*str*) – IAM role name.
- **instance_type_master** (*str*) – EC2 instance type.
- **instance_type_core** (*str*) – EC2 instance type.
- **instance_type_task** (*str*) – EC2 instance type.
- **instance_ebs_size_master** (*int*) – Size of EBS in GB.
- **instance_ebs_size_core** (*int*) – Size of EBS in GB.
- **instance_ebs_size_task** (*int*) – Size of EBS in GB.
- **instance_num_on_demand_master** (*int*) – Number of on demand instances.
- **instance_num_on_demand_core** (*int*) – Number of on demand instances.
- **instance_num_on_demand_task** (*int*) – Number of on demand instances.
- **instance_num_spot_master** (*int*) – Number of spot instances.
- **instance_num_spot_core** (*int*) – Number of spot instances.
- **instance_num_spot_task** (*int*) – Number of spot instances.
- **spot_bid_percentage_of_on_demand_master** (*int*) – The bid price, as a percentage of On-Demand price.
- **spot_bid_percentage_of_on_demand_core** (*int*) – The bid price, as a percentage of On-Demand price.
- **spot_bid_percentage_of_on_demand_task** (*int*) – The bid price, as a percentage of On-Demand price.
- **spot_provisioning_timeout_master** (*int*) – The spot provisioning timeout period in minutes. If Spot instances are not provisioned within this time period, the `TimeOutAction` is taken. Minimum value is 5 and maximum value is 1440. The timeout applies only during initial provisioning, when the cluster is first created.
- **spot_provisioning_timeout_core** (*int*) – The spot provisioning timeout period in minutes. If Spot instances are not provisioned within this time period, the `TimeOutAction` is taken. Minimum value is 5 and maximum value is 1440. The timeout applies only during initial provisioning, when the cluster is first created.
- **spot_provisioning_timeout_task** (*int*) – The spot provisioning timeout period in minutes. If Spot instances are not provisioned within this time period, the `TimeOutAction` is taken. Minimum value is 5 and maximum value is 1440. The timeout applies only during initial provisioning, when the cluster is first created.
- **spot_timeout_to_on_demand_master** (*bool*) – After a provisioning timeout should the cluster switch to on demand or shutdown?
- **spot_timeout_to_on_demand_core** (*bool*) – After a provisioning timeout should the cluster switch to on demand or shutdown?
- **spot_timeout_to_on_demand_task** (*bool*) – After a provisioning timeout should the cluster switch to on demand or shutdown?

- **python3** (*bool*) – Python 3 Enabled?
- **spark_glue_catalog** (*bool*) – Spark integration with Glue Catalog?
- **hive_glue_catalog** (*bool*) – Hive integration with Glue Catalog?
- **presto_glue_catalog** (*bool*) – Presto integration with Glue Catalog?
- **consistent_view** (*bool*) – Consistent view allows EMR clusters to check for list and read-after-write consistency for Amazon S3 objects written by or synced with EMRFS. <https://docs.aws.amazon.com/emr/latest/ManagementGuide/emr-plan-consistent-view.html>
- **consistent_view_retry_seconds** (*int*) – Delay between the tries (seconds).
- **consistent_view_retry_count** (*int*) – Number of tries.
- **consistent_view_table_name** (*str*) – Name of the DynamoDB table to store the consistent view data.
- **bootstraps_paths** (*List[str], optional*) – Bootstraps paths (e.g. ["s3://BUCKET_NAME/script.sh"]).
- **debugging** (*bool*) – Debugging enabled?
- **applications** (*List[str], optional*) – List of applications (e.g. ["Hadoop", "Spark", "Ganglia", "Hive"]). If None, ["Spark"] will be considered.
- **visible_to_all_users** (*bool*) – True or False.
- **key_pair_name** (*str, optional*) – Key pair name.
- **security_group_master** (*str, optional*) – The identifier of the Amazon EC2 security group for the master node.
- **security_groups_master_additional** (*str, optional*) – A list of additional Amazon EC2 security group IDs for the master node.
- **security_group_slave** (*str, optional*) – The identifier of the Amazon EC2 security group for the core and task nodes.
- **security_groups_slave_additional** (*str, optional*) – A list of additional Amazon EC2 security group IDs for the core and task nodes.
- **security_group_service_access** (*str, optional*) – The identifier of the Amazon EC2 security group for the Amazon EMR service to access clusters in VPC private subnets.
- **docker** (*bool*) – Enable Docker Hub and ECR registries access.
- **extra_public_registries** (*List[str], optional*) – Additional docker registries.
- **spark_log_level** (*str*) – log4j.rootCategory log level (ALL, DEBUG, INFO, WARN, ERROR, FATAL, OFF, TRACE).
- **spark_jars_path** (*List[str], optional*) – spark.jars e.g. [s3://.../foo.jar, s3://.../boo.jar] <https://spark.apache.org/docs/latest/configuration.html>
- **spark_defaults** (*Dict[str, str], optional*) – <https://docs.aws.amazon.com/emr/latest/ReleaseGuide/emr-spark-configure.html#spark-defaults>
- **spark_pyarrow** (*bool*) – Enable PySpark to use PyArrow behind the scenes. P.S. You must install pyarrow by your self via bootstrap

- **custom_classifications** (*List[Dict[str, Any]]*, *optional*) – Extra classifications.
- **maximize_resource_allocation** (*bool*) – Configure your executors to utilize the maximum resources possible <https://docs.aws.amazon.com/emr/latest/ReleaseGuide/emr-spark-configure.html#emr-spark-maximizeresourceallocation>
- **steps** (*List[Dict[str, Any]]*, *optional*) – Steps definitions (Obs : str Use `EMR.build_step()` to build it)
- **keep_cluster_alive_when_no_steps** (*bool*) – Specifies whether the cluster should remain available after completing all steps
- **termination_protected** (*bool*) – Specifies whether the Amazon EC2 instances in the cluster are protected from termination by API calls, user intervention, or in the event of a job-flow error.
- **tags** (*Dict[str, str]*, *optional*) – Key/Value collection to put on the Cluster. e.g. {"foo": "boo", "bar": "xoo"}
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Cluster ID.

Return type str

Examples

Minimal Example

```
>>> import awswrangler as wr
>>> cluster_id = wr.emr.create_cluster("SUBNET_ID")
```

Minimal Example With Custom Classification

```
>>> import awswrangler as wr
>>> cluster_id = wr.emr.create_cluster(
>>>     subnet_id="SUBNET_ID",
>>>     custom_classifications=[
>>>         {
>>>             "Classification": "livy-conf",
>>>             "Properties": {
>>>                 "livy.spark.master": "yarn",
>>>                 "livy.spark.deploy-mode": "cluster",
>>>                 "livy.server.session.timeout": "16h",
>>>             },
>>>         }
>>>     ],
>>> )
```

Full Example

```
>>> import awswrangler as wr
>>> cluster_id = wr.emr.create_cluster(
...     cluster_name="wrangler_cluster",
...     logging_s3_path=f"s3://BUCKET_NAME/emr-logs/",
...     emr_release="emr-5.28.0",
...     subnet_id="SUBNET_ID",
```

(continues on next page)

(continued from previous page)

```

...     emr_ec2_role="EMR_EC2_DefaultRole",
...     emr_role="EMR_DefaultRole",
...     instance_type_master="m5.xlarge",
...     instance_type_core="m5.xlarge",
...     instance_type_task="m5.xlarge",
...     instance_ebs_size_master=50,
...     instance_ebs_size_core=50,
...     instance_ebs_size_task=50,
...     instance_num_on_demand_master=1,
...     instance_num_on_demand_core=1,
...     instance_num_on_demand_task=1,
...     instance_num_spot_master=0,
...     instance_num_spot_core=1,
...     instance_num_spot_task=1,
...     spot_bid_percentage_of_on_demand_master=100,
...     spot_bid_percentage_of_on_demand_core=100,
...     spot_bid_percentage_of_on_demand_task=100,
...     spot_provisioning_timeout_master=5,
...     spot_provisioning_timeout_core=5,
...     spot_provisioning_timeout_task=5,
...     spot_timeout_to_on_demand_master=True,
...     spot_timeout_to_on_demand_core=True,
...     spot_timeout_to_on_demand_task=True,
...     python3=True,
...     spark_glue_catalog=True,
...     hive_glue_catalog=True,
...     presto_glue_catalog=True,
...     bootstraps_paths=None,
...     debugging=True,
...     applications=["Hadoop", "Spark", "Ganglia", "Hive"],
...     visible_to_all_users=True,
...     key_pair_name=None,
...     spark_jars_path=[f"s3://...jar"],
...     maximize_resource_allocation=True,
...     keep_cluster_alive_when_no_steps=True,
...     termination_protected=False,
...     spark_pyarrow=True,
...     tags={
...         "foo": "boo"
...     })

```

aws wrangler.emr.get_cluster_state

`aws wrangler.emr.get_cluster_state` (*cluster_id*: *str*, *boto3_session*: *Optional[boto3.session.Session]* = *None*) → *str*

Get the EMR cluster state.

Possible states: 'STARTING', 'BOOTSTRAPPING', 'RUNNING', 'WAITING', 'TERMINATING', 'TERMINATED', 'TERMINATED_WITH_ERRORS'

Parameters

- **cluster_id** (*str*) – Cluster ID.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns State.

Return type str

Examples

```
>>> import awswrangler as wr
>>> state = wr.emr.get_cluster_state("cluster-id")
```

awswrangler.emr.get_step_state

`awswrangler.emr.get_step_state(cluster_id: str, step_id: str, boto3_session: Optional[boto3.session.Session] = None) → str`

Get EMR step state.

Possible states: 'PENDING', 'CANCEL_PENDING', 'RUNNING', 'COMPLETED', 'CANCELLED', 'FAILED', 'INTERRUPTED'

Parameters

- **cluster_id** (*str*) – Cluster ID.
- **step_id** (*str*) – Step ID.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns State.

Return type str

Examples

```
>>> import awswrangler as wr
>>> state = wr.emr.get_step_state("cluster-id", "step-id")
```

awswrangler.emr.submit_ecr_credentials_refresh

`awswrangler.emr.submit_ecr_credentials_refresh(cluster_id: str, path: str, action_on_failure: str = 'CONTINUE', boto3_session: Optional[boto3.session.Session] = None) → str`

Update internal ECR credentials.

Parameters

- **cluster_id** (*str*) – Cluster ID.
- **path** (*str*) – Amazon S3 path where Wrangler will stage the script `ecr_credentials_refresh.py` (e.g. `s3://bucket/emr/`)
- **action_on_failure** (*str*) – 'TERMINATE_JOB_FLOW', 'TERMINATE_CLUSTER', 'CANCEL_AND_WAIT', 'CONTINUE'
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Step ID.

Return type str

Examples

```
>>> import awswrangler as wr
>>> step_id = wr.emr.submit_ecr_credentials_refresh("cluster_id", "s3://bucket/
↪emr/")
```

awswrangler.emr.submit_spark_step

`awswrangler.emr.submit_spark_step`(*cluster_id*: str, *path*: str, *deploy_mode*: str = 'cluster', *docker_image*: Optional[str] = None, *name*: str = 'my-step', *action_on_failure*: str = 'CONTINUE', *region*: Optional[str] = None, *boto3_session*: Optional[boto3.session.Session] = None) → str

Submit Spark Step.

Parameters

- **cluster_id** (str) – Cluster ID.
- **path** (str) – Script path. (e.g. s3://bucket/app.py)
- **deploy_mode** (str) – “cluster” | “client”
- **docker_image** (str, optional) – e.g. “{ACCOUNT_ID}.dkr.ecr.{REGION}.amazonaws.com/{IMAGE_NAME}:{TAG}”
- **name** (str, optional) – Step name.
- **action_on_failure** (str) – ‘TERMINATE_JOB_FLOW’, ‘TERMINATE_CLUSTER’, ‘CANCEL_AND_WAIT’, ‘CONTINUE’
- **region** (str, optional) – Region name to not get it from boto3.Session. (e.g. *us-east-1*)
- **boto3_session** (boto3.Session(), optional) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Step ID.

Return type str

Examples

```
>>> import awswrangler as wr
>>> step_id = wr.emr.submit_spark_step(
>>>     cluster_id="cluster-id",
>>>     path="s3://bucket/emr/app.py"
>>> )
```

aws wrangler.emr.submit_step

`aws wrangler.emr.submit_step` (*cluster_id*: str, *command*: str, *name*: str = 'my-step', *action_on_failure*: str = 'CONTINUE', *script*: bool = False, *boto3_session*: Optional[boto3.session.Session] = None) → str

Submit new job in the EMR Cluster.

Parameters

- **cluster_id** (str) – Cluster ID.
- **command** (str) – e.g. 'echo "Hello!"' e.g. for script 's3://.../script.sh arg1 arg2'
- **name** (str, optional) – Step name.
- **action_on_failure** (str) – 'TERMINATE_JOB_FLOW', 'TERMINATE_CLUSTER', 'CANCEL_AND_WAIT', 'CONTINUE'
- **script** (bool) – True for raw command or False for script runner. <https://docs.aws.amazon.com/emr/latest/ReleaseGuide/emr-commandrunner.html>
- **boto3_session** (boto3.Session(), optional) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Step ID.

Return type str

Examples

```
>>> import aws wrangler as wr
>>> step_id = wr.emr.submit_step(
...     cluster_id=cluster_id,
...     name="step_test",
...     command="s3://...script.sh arg1 arg2",
...     script=True)
```

aws wrangler.emr.submit_steps

`aws wrangler.emr.submit_steps` (*cluster_id*: str, *steps*: List[Dict[str, Any]], *boto3_session*: Optional[boto3.session.Session] = None) → List[str]

Submit a list of steps.

Parameters

- **cluster_id** (str) – Cluster ID.
- **steps** (List[Dict[str, Any]]) – Steps definitions (Obs: Use EMR.build_step() to build it).
- **boto3_session** (boto3.Session(), optional) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns List of step IDs.

Return type List[str]

Examples

```
>>> import awswrangler as wr
>>> for cmd in ['echo "Hello"', 'ls -la']:
...     steps.append(wr.emr.build_step(name=cmd, command=cmd))
>>> wr.emr.submit_steps(cluster_id="cluster-id", steps=steps)
```

awswrangler.emr.terminate_cluster

`awswrangler.emr.terminate_cluster` (*cluster_id*: *str*, *boto3_session*: *Optional[boto3.session.Session]* = *None*) → *None*

Terminate EMR cluster.

Parameters

- **cluster_id** (*str*) – Cluster ID.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if *boto3_session* receive *None*.

Returns *None*.

Return type *None*

Examples

```
>>> import awswrangler as wr
>>> wr.emr.terminate_cluster("cluster-id")
```

1.3.6 CloudWatch Logs

<code>read_logs</code> (<i>query</i> , <i>log_group_names</i> [, ...])	Run a query against AWS CloudWatchLogs Insights and convert the results to Pandas DataFrame.
<code>run_query</code> (<i>query</i> , <i>log_group_names</i> [, ...])	Run a query against AWS CloudWatchLogs Insights and wait the results.
<code>start_query</code> (<i>query</i> , <i>log_group_names</i> [, ...])	Run a query against AWS CloudWatchLogs Insights.
<code>wait_query</code> (<i>query_id</i> [, <i>boto3_session</i>])	Wait query ends.

awswrangler.cloudwatch.read_logs

`awswrangler.cloudwatch.read_logs` (*query*: *str*, *log_group_names*: *List[str]*, *start_time*: *datetime.datetime* = *datetime.datetime(1970, 1, 1, 0, 0)*, *end_time*: *datetime.datetime* = *datetime.datetime(2020, 6, 14, 1, 49, 4, 640386)*, *limit*: *Optional[int]* = *None*, *boto3_session*: *Optional[boto3.session.Session]* = *None*) → *pandas.core.frame.DataFrame*

Run a query against AWS CloudWatchLogs Insights and convert the results to Pandas DataFrame.

https://docs.aws.amazon.com/AmazonCloudWatch/latest/logs/CWL_QuerySyntax.html

Parameters

- **query** (*str*) – The query string.

- **log_group_names** (*str*) – The list of log groups to be queried. You can include up to 20 log groups.
- **start_time** (*datetime.datetime*) – The beginning of the time range to query.
- **end_time** (*datetime.datetime*) – The end of the time range to query.
- **limit** (*Optional[int]*) – The maximum number of log events to return in the query.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Result as a Pandas DataFrame.

Return type pandas.DataFrame

Examples

```
>>> import awswrangler as wr
>>> df = wr.cloudwatch.read_logs(
...     log_group_names=["loggroup"],
...     query="fields @timestamp, @message | sort @timestamp desc | limit 5",
... )
```

awswrangler.cloudwatch.run_query

`awswrangler.cloudwatch.run_query` (*query: str, log_group_names: List[str], start_time: datetime.datetime = datetime.datetime(1970, 1, 1, 0, 0), end_time: datetime.datetime = datetime.datetime(2020, 6, 14, 1, 49, 4, 640342), limit: Optional[int] = None, boto3_session: Optional[boto3.session.Session] = None*) → List[List[Dict[str, str]]]

Run a query against AWS CloudWatchLogs Insights and wait the results.

https://docs.aws.amazon.com/AmazonCloudWatch/latest/logs/CWL_QuerySyntax.html

Parameters

- **query** (*str*) – The query string.
- **log_group_names** (*str*) – The list of log groups to be queried. You can include up to 20 log groups.
- **start_time** (*datetime.datetime*) – The beginning of the time range to query.
- **end_time** (*datetime.datetime*) – The end of the time range to query.
- **limit** (*Optional[int]*) – The maximum number of log events to return in the query.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Result.

Return type List[List[Dict[str, str]]]

Examples

```
>>> import awswrangler as wr
>>> result = wr.cloudwatch.run_query(
...     log_group_names=["loggroup"],
...     query="fields @timestamp, @message | sort @timestamp desc | limit 5",
... )
```

awswrangler.cloudwatch.start_query

`awswrangler.cloudwatch.start_query` (*query: str, log_group_names: List[str], start_time: datetime.datetime = datetime.datetime(1970, 1, 1, 0, 0), end_time: datetime.datetime = datetime.datetime(2020, 6, 14, 1, 49, 4, 640293), limit: Optional[int] = None, boto3_session: Optional[boto3.session.Session] = None*)
→ str

Run a query against AWS CloudWatchLogs Insights.

https://docs.aws.amazon.com/AmazonCloudWatch/latest/logs/CWL_QuerySyntax.html

Parameters

- **query** (*str*) – The query string.
- **log_group_names** (*str*) – The list of log groups to be queried. You can include up to 20 log groups.
- **start_time** (*datetime.datetime*) – The beginning of the time range to query.
- **end_time** (*datetime.datetime*) – The end of the time range to query.
- **limit** (*Optional[int]*) – The maximum number of log events to return in the query.
- **boto3_session** (*boto3.Session(), optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Query ID.

Return type str

Examples

```
>>> import awswrangler as wr
>>> query_id = wr.cloudwatch.start_query(
...     log_group_names=["loggroup"],
...     query="fields @timestamp, @message | sort @timestamp desc | limit 5",
... )
```

aws wrangler.cloudwatch.wait_query

`aws wrangler.cloudwatch.wait_query` (*query_id*: *str*, *boto3_session*: *Optional[boto3.session.Session] = None*) → Dict[str, Any]

Wait query ends.

https://docs.aws.amazon.com/AmazonCloudWatch/latest/logs/CWL_QuerySyntax.html

Parameters

- **query_id** (*str*) – Query ID.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if `boto3_session` receive None.

Returns Query result payload.

Return type Dict[str, Any]

Examples

```
>>> import aws wrangler as wr
>>> query_id = wr.cloudwatch.start_query(
...     log_group_names=["loggroup"],
...     query="fields @timestamp, @message | sort @timestamp desc | limit 5",
... )
... response = wr.cloudwatch.wait_query(query_id=query_id)
```

1.3.7 Amazon QuickSight

<code>cancel_ingestion([ingestion_id, ...])</code>	Cancel an ongoing ingestion of data into SPICE.
<code>create_athena_data_source(name[, work-group, ...])</code>	Create a QuickSight data source pointing to an Athena/Workgroup.
<code>create_athena_dataset(name[, database, ...])</code>	Create a QuickSight dataset.
<code>create_ingestion([dataset_name, dataset_id, ...])</code>	Create and starts a new SPICE ingestion on a dataset.
<code>delete_all_dashboards([account_id, ...])</code>	Delete all dashboards.
<code>delete_all_data_sources([account_id, ...])</code>	Delete all data sources.
<code>delete_all_datasets([account_id, boto3_session])</code>	Delete all datasets.
<code>delete_all_templates([account_id, boto3_session])</code>	Delete all templates.
<code>delete_dashboard([name, dashboard_id, ...])</code>	Delete a dashboard.
<code>delete_data_source([name, data_source_id, ...])</code>	Delete a data source.
<code>delete_dataset([name, dataset_id, ...])</code>	Delete a dataset.
<code>delete_template([name, template_id, ...])</code>	Delete a tamplate.
<code>describe_dashboard([name, dashboard_id, ...])</code>	Describe a QuickSight dashboard by name or ID.
<code>describe_data_source([name, data_source_id, ...])</code>	Describe a QuickSight data source by name or ID.
<code>describe_data_source_permissions([name, ...])</code>	Describe a QuickSight data source permissions by name or ID.
<code>describe_dataset([name, dataset_id, ...])</code>	Describe a QuickSight dataset by name or ID.

continues on next page

Table 7 – continued from previous page

<code>describe_ingestion([ingestion_id, ...])</code>	Describe a QuickSight ingestion by ID.
<code>get_dashboard_id(name[, account_id, ...])</code>	Get QuickSight dashboard ID given a name and fails if there is more than 1 ID associated with this name.
<code>get_dashboard_ids(name[, account_id, ...])</code>	Get QuickSight dashboard IDs given a name.
<code>get_data_source_arn(name[, account_id, ...])</code>	Get QuickSight data source ARN given a name and fails if there is more than 1 ARN associated with this name.
<code>get_data_source_arns(name[, account_id, ...])</code>	Get QuickSight Data source ARNs given a name.
<code>get_data_source_id(name[, account_id, ...])</code>	Get QuickSight data source ID given a name and fails if there is more than 1 ID associated with this name.
<code>get_data_source_ids(name[, account_id, ...])</code>	Get QuickSight data source IDs given a name.
<code>get_dataset_id(name[, account_id, boto3_session])</code>	Get QuickSight Dataset ID given a name and fails if there is more than 1 ID associated with this name.
<code>get_dataset_ids(name[, account_id, ...])</code>	Get QuickSight dataset IDs given a name.
<code>get_template_id(name[, account_id, ...])</code>	Get QuickSight template ID given a name and fails if there is more than 1 ID associated with this name.
<code>get_template_ids(name[, account_id, ...])</code>	Get QuickSight template IDs given a name.
<code>list_dashboards([account_id, boto3_session])</code>	List dashboards in an AWS account.
<code>list_data_sources([account_id, boto3_session])</code>	List all QuickSight Data sources summaries.
<code>list_datasets([account_id, boto3_session])</code>	List all QuickSight datasets summaries.
<code>list_groups([namespace, account_id, ...])</code>	List all QuickSight Groups.
<code>list_group_memberships(group_name[, ...])</code>	List all QuickSight Group memberships.
<code>list_iam_policy_assignments([status, ...])</code>	List IAM policy assignments in the current Amazon QuickSight account.
<code>list_iam_policy_assignments_for_user(user[, ...])</code>	List the IAM policy assignments.
<code>list_ingestions([dataset_name, dataset_id, ...])</code>	List the history of SPICE ingestions for a dataset.
<code>list_templates([account_id, boto3_session])</code>	List all QuickSight templates.
<code>list_users([namespace, account_id, ...])</code>	Return a list of all of the Amazon QuickSight users belonging to this account.
<code>list_user_groups(user_name[, namespace, ...])</code>	List the Amazon QuickSight groups that an Amazon QuickSight user is a member of.

aws wrangler quicksight.cancel_ingestion

`aws wrangler quicksight.cancel_ingestion` (*ingestion_id*: *str* = *None*, *dataset_name*: *Optional*[*str*] = *None*, *dataset_id*: *Optional*[*str*] = *None*, *account_id*: *Optional*[*str*] = *None*, *boto3_session*: *Optional*[*boto3.session.Session*] = *None*) → *None*

Cancel an ongoing ingestion of data into SPICE.

Note: You must pass a not *None* value for *dataset_name* or *dataset_id* argument.

Parameters

- **ingestion_id** (*str*) – Ingestion ID.
- **dataset_name** (*str*, *optional*) – Dataset name.
- **dataset_id** (*str*, *optional*) – Dataset ID.
- **account_id** (*str*, *optional*) – If *None*, the account ID will be inferred from your *boto3* session.

- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns None.

Return type None

Examples

```
>>> import awswrangler as wr
>>> wr.quicksight.cancel_ingestion(ingestion_id="...", dataset_name="...")
```

awswrangler.quicksight.create_athena_data_source

```
awswrangler.quicksight.create_athena_data_source(name: str, workgroup: str
                                                  = 'primary', allowed_to_use:
                                                  Optional[List[str]] = None,
                                                  allowed_to_manage: Op-
                                                  tional[List[str]] = None, tags:
                                                  Optional[Dict[str, str]] = None,
                                                  account_id: Optional[str] =
                                                  None, boto3_session: Op-
                                                  tional[boto3.session.Session] =
                                                  None) → None
```

Create a QuickSight data source pointing to an Athena/Workgroup.

Note: You will not be able to see the the data source in the console if you not pass your user to one of the `allowed_*` arguments.

Parameters

- **name** (*str*) – Data source name.
- **workgroup** (*str*) – Athena workgroup.
- **tags** (*Dict[str, str]*, *optional*) – Key/Value collection to put on the Cluster. e.g. {"foo": "boo", "bar": "xoo"}
- **allowed_to_use** (*optional*) – List of principals that will be allowed to see and use the data source. e.g. ["John"]
- **allowed_to_manage** (*optional*) – List of principals that will be allowed to see, use, update and delete the data source. e.g. ["Mary"]
- **account_id** (*str*, *optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns None.

Return type None

Examples

```
>>> import awswrangler as wr
>>> wr.quicksight.create_athena_data_source(
...     name="...",
...     allowed_to_manage=["john"]
... )
```

awswrangler.quicksight.create_athena_dataset

```
awswrangler.quicksight.create_athena_dataset(name: str, database: Optional[str] =
None, table: Optional[str] = None, sql:
Optional[str] = None, sql_name: str =
'CustomSQL', data_source_name: Op-
tional[str] = None, data_source_arn:
Optional[str] = None, import_mode: str
= 'DIRECT_QUERY', allowed_to_use:
Optional[List[str]] = None, al-
lowed_to_manage: Optional[List[str]]
= None, logical_table_alias: str
= 'LogicalTable', rename_columns:
Optional[Dict[str, str]] = None,
cast_columns_types: Optional[Dict[str,
str]] = None, tags: Optional[Dict[str,
str]] = None, account_id: Op-
tional[str] = None, boto3_session:
Optional[boto3.session.Session] = None)
→ None
```

Create a QuickSight dataset.

Note: You will not be able to see the the dataset in the console if you not pass your user to one of the `allowed_*` arguments.

Note: You must pass `database/table` OR `sql` argument.

Note: You must pass `data_source_name` OR `data_source_arn` argument.

Parameters

- **name** (*str*) – Dataset name.
- **database** (*str*) – Athena's database name.
- **table** (*str*) – Athena's table name.
- **sql** (*str*) – Use a SQL query to define your table.
- **sql_name** (*str*) – Query name.
- **data_source_name** (*str*, *optional*) – QuickSight data source name.
- **data_source_arn** (*str*, *optional*) – QuickSight data source ARN.

- **import_mode** (*str*) – Indicates whether you want to import the data into SPICE. ‘SPICE’|‘DIRECT_QUERY’
- **tags** (*Dict[str, str]*, *optional*) – Key/Value collection to put on the Cluster. e.g. {“foo”: “boo”, “bar”: “xoo”}
- **allowed_to_use** (*optional*) – List of principals that will be allowed to see and use the data source. e.g. [“john”, “Mary”]
- **allowed_to_manage** (*optional*) – List of principals that will be allowed to see, use, update and delete the data source. e.g. [“Mary”]
- **logical_table_alias** (*str*) – A display name for the logical table.
- **rename_columns** (*Dict[str, str]*, *optional*) – Dictionary to map column re-names. e.g. {“old_name”: “new_name”, “old_name2”: “new_name2”}
- **cast_columns_types** (*Dict[str, str]*, *optional*) – Dictionary to map column casts. e.g. {“col_name”: “STRING”, “col_name2”: “DECIMAL”} Valid types: ‘STRING’|‘INTEGER’|‘DECIMAL’|‘DATETIME’
- **account_id** (*str*, *optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns None.

Return type None

Examples

```
>>> import awswrangler as wr
>>> wr.quicksight.create_athena_dataset(
...     name="...",
...     database="..."
...     table="..."
...     data_source_name="..."
...     allowed_to_manage=["Mary"]
... )
```

awswrangler.quicksight.create_ingestion

`awswrangler.quicksight.create_ingestion` (*dataset_name: Optional[str] = None, dataset_id: Optional[str] = None, ingestion_id: Optional[str] = None, account_id: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None*) → *str*

Create and starts a new SPICE ingestion on a dataset.

Note: You must pass `dataset_name` OR `dataset_id` argument.

Parameters

- **dataset_name** (*str*, *optional*) – Dataset name.

- **dataset_id**(*str*, *optional*) – Dataset ID.
- **ingestion_id**(*str*, *optional*) – Ingestion ID.
- **account_id**(*str*, *optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session**(*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Ingestion ID

Return type str

Examples

```
>>> import awswrangler as wr
>>> status = wr.quicksight.create_ingestion("my_dataset")
```

awswrangler.quicksight.delete_all_dashboards

```
awswrangler.quicksight.delete_all_dashboards(account_id: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None)
→ None
```

Delete all dashboards.

Parameters

- **account_id**(*str*, *optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session**(*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns None.

Return type None

Examples

```
>>> import awswrangler as wr
>>> wr.quicksight.delete_all_dashboards()
```

awswrangler.quicksight.delete_all_data_sources

```
awswrangler.quicksight.delete_all_data_sources(account_id: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None)
→ None
```

Delete all data sources.

Parameters

- **account_id**(*str*, *optional*) – If None, the account ID will be inferred from your boto3 session.

- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns None.

Return type None

Examples

```
>>> import awswrangler as wr
>>> wr.quicksight.delete_all_data_sources()
```

awswrangler.quicksight.delete_all_datasets

```
awswrangler.quicksight.delete_all_datasets(account_id: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None) → None
```

Delete all datasets.

Parameters

- **account_id** (*str*, *optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns None.

Return type None

Examples

```
>>> import awswrangler as wr
>>> wr.quicksight.delete_all_datasets()
```

awswrangler.quicksight.delete_all_templates

```
awswrangler.quicksight.delete_all_templates(account_id: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None) → None
```

Delete all templates.

Parameters

- **account_id** (*str*, *optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns None.

Return type None

Examples

```
>>> import awswrangler as wr
>>> wr.quicksight.delete_all_templates()
```

awswrangler.quicksight.delete_dashboard

`awswrangler.quicksight.delete_dashboard` (*name: Optional[str] = None, dashboard_id: Optional[str] = None, version_number: Optional[int] = None, account_id: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None*) → None

Delete a dashboard.

Note: You must pass a not None name or dashboard_id argument.

Parameters

- **name** (*str, optional*) – Dashboard name.
- **dashboard_id** (*str, optional*) – The ID for the dashboard.
- **version_number** (*int, optional*) – The version number of the dashboard. If the version number property is provided, only the specified version of the dashboard is deleted.
- **account_id** (*str, optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session** (*boto3.Session(), optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns None.

Return type None

Examples

```
>>> import awswrangler as wr
>>> wr.quicksight.delete_dashboard(name="...")
```

awswrangler.quicksight.delete_data_source

`awswrangler.quicksight.delete_data_source` (*name: Optional[str] = None, data_source_id: Optional[str] = None, account_id: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None*) → None

Delete a data source.

Note: You must pass a not None name or data_source_id argument.

Parameters

- **name** (*str*, *optional*) – Dashboard name.
- **data_source_id** (*str*, *optional*) – The ID for the data source.
- **account_id** (*str*, *optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns None.

Return type None

Examples

```
>>> import awswrangler as wr
>>> wr.quicksight.delete_data_source(name="...")
```

awswrangler.quicksight.delete_dataset

`awswrangler.quicksight.delete_dataset` (*name: Optional[str] = None, dataset_id: Optional[str] = None, account_id: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None*) → None

Delete a dataset.

Note: You must pass a not None name or dataset_id argument.

Parameters

- **name** (*str*, *optional*) – Dashboard name.
- **dataset_id** (*str*, *optional*) – The ID for the dataset.
- **account_id** (*str*, *optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns None.

Return type None

Examples

```
>>> import awswrangler as wr
>>> wr.quicksight.delete_dataset(name="...")
```

aws wrangler quicksight.delete_template

```
aws wrangler quicksight.delete_template (name: Optional[str] = None, template_id: Optional[str] = None, version_number: Optional[int] = None, account_id: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None) → None
```

Delete a template.

Note: You must pass a not None name or template_id argument.

Parameters

- **name** (*str, optional*) – Dashboard name.
- **template_id** (*str, optional*) – The ID for the dashboard.
- **version_number** (*int, optional*) – Specifies the version of the template that you want to delete. If you don't provide a version number, it deletes all versions of the template.
- **account_id** (*str, optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session** (*boto3.Session(), optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns None.

Return type None

Examples

```
>>> import aws wrangler as wr
>>> wr.quick sight.delete_template(name="...")
```

aws wrangler quicksight.describe_dashboard

```
aws wrangler quicksight.describe_dashboard (name: Optional[str] = None, dashboard_id: Optional[str] = None, account_id: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None) → Dict[str, Any]
```

Describe a QuickSight dashboard by name or ID.

Note: You must pass a not None name or dashboard_id argument.

Parameters

- **name** (*str, optional*) – Dashboard name.
- **dashboard_id** (*str, optional*) – Dashboard ID.
- **account_id** (*str, optional*) – If None, the account ID will be inferred from your boto3 session.

- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Dashboad Description.

Return type Dict[str, Any]

Examples

```
>>> import awswrangler as wr
>>> description = wr.quicksight.describe_dashboard(name="my-dashboard")
```

awswrangler.quicksight.describe_data_source

`awswrangler.quicksight.describe_data_source` (*name: Optional[str] = None*,
data_source_id: Optional[str] = None, *account_id: Optional[str] = None*, *boto3_session: Optional[boto3.session.Session] = None*)
→ Dict[str, Any]

Describe a QuickSight data source by name or ID.

Note: You must pass a not None name or data_source_id argument.

Parameters

- **name** (*str*, *optional*) – Data source name.
- **data_source_id** (*str*, *optional*) – Data source ID.
- **account_id** (*str*, *optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Data source Description.

Return type Dict[str, Any]

Examples

```
>>> import awswrangler as wr
>>> description = wr.quicksight.describe_data_source("...")
```

awswrangler.quicksight.describe_data_source_permissions

```
awswrangler.quicksight.describe_data_source_permissions (name: Optional[str] =
                                                         None, data_source_id:
                                                         Optional[str] = None, ac-
                                                         count_id: Optional[str] =
                                                         None, boto3_session: Op-
                                                         tional[boto3.session.Session]
                                                         = None) → Dict[str, Any]
```

Describe a QuickSight data source permissions by name or ID.

Note: You must pass a not None name or data_source_id argument.

Parameters

- **name** (*str, optional*) – Data source name.
- **data_source_id** (*str, optional*) – Data source ID.
- **account_id** (*str, optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session** (*boto3.Session(), optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Data source Permissions Description.

Return type Dict[str, Any]

Examples

```
>>> import awswrangler as wr
>>> description = wr.quicksight.describe_data_source_permissions("my-data-source")
```

awswrangler.quicksight.describe_dataset

```
awswrangler.quicksight.describe_dataset (name: Optional[str] = None, dataset_id:
                                          Optional[str] = None, account_id: Op-
                                          tional[str] = None, boto3_session: Op-
                                          tional[boto3.session.Session] = None) → Dict[str,
                                          Any]
```

Describe a QuickSight dataset by name or ID.

Note: You must pass a not None name or dataset_id argument.

Parameters

- **name** (*str, optional*) – Dataset name.
- **dataset_id** (*str, optional*) – Dataset ID.
- **account_id** (*str, optional*) – If None, the account ID will be inferred from your boto3 session.

- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Dataset Description.

Return type Dict[str, Any]

Examples

```
>>> import awswrangler as wr
>>> description = wr.quicksight.describe_dataset("my-dataset")
```

awswrangler.quicksight.describe_ingestion

```
awswrangler.quicksight.describe_ingestion(ingestion_id: str = None, dataset_name:
Optional[str] = None, dataset_id: Optional[str] = None, account_id: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None) →
Dict[str, Any]
```

Describe a QuickSight ingestion by ID.

Note: You must pass a not None value for dataset_name or dataset_id argument.

Parameters

- **ingestion_id** (*str*) – Ingestion ID.
- **dataset_name** (*str*, *optional*) – Dataset name.
- **dataset_id** (*str*, *optional*) – Dataset ID.
- **account_id** (*str*, *optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Ingestion Description.

Return type Dict[str, Any]

Examples

```
>>> import awswrangler as wr
>>> description = wr.quicksight.describe_dataset(ingestion_id="...", dataset_name=
↳ "...")
```


aws wrangler quicksight.get_dashboard_id

`aws wrangler quicksight.get_dashboard_id` (*name: str, account_id: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None*) → str

Get QuickSight dashboard ID given a name and fails if there is more than 1 ID associated with this name.

Parameters

- **name** (*str*) – Dashboard name.
- **account_id** (*str, optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session** (*boto3.Session(), optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Dashboard ID.

Return type str

Examples

```
>>> import aws wrangler as wr
>>> my_id = wr.quicksight.get_dashboard_id(name="...")
```

aws wrangler quicksight.get_dashboard_ids

`aws wrangler quicksight.get_dashboard_ids` (*name: str, account_id: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None*) → List[str]

Get QuickSight dashboard IDs given a name.

Note: This function returns a list of ID because Quicksight accepts duplicated dashboard names, so you may have more than 1 ID for a given name.

Parameters

- **name** (*str*) – Dashboard name.
- **account_id** (*str, optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session** (*boto3.Session(), optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Dashboard IDs.

Return type List[str]

Examples

```
>>> import awswrangler as wr
>>> ids = wr.quicksight.get_dashboard_ids(name="...")
```

awswrangler.quicksight.get_data_source_arn

```
awswrangler.quicksight.get_data_source_arn(name: str, account_id: Optional[str]
                                           = None, boto3_session: Optional[boto3.session.Session] = None) →
                                           str
```

Get QuickSight data source ARN given a name and fails if there is more than 1 ARN associated with this name.

Note: This function returns a list of ARNs because QuickSight accepts duplicated data source names, so you may have more than 1 ARN for a given name.

Parameters

- **name** (*str*) – Data source name.
- **account_id** (*str*, *optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Data source ARN.

Return type str

Examples

```
>>> import awswrangler as wr
>>> arn = wr.quicksight.get_data_source_arn("...")
```

awswrangler.quicksight.get_data_source_arns

```
awswrangler.quicksight.get_data_source_arns(name: str, account_id: Optional[str]
                                              = None, boto3_session: Optional[boto3.session.Session] = None)
                                              → List[str]
```

Get QuickSight Data source ARNs given a name.

Note: This function returns a list of ARNs because QuickSight accepts duplicated data source names, so you may have more than 1 ARN for a given name.

Parameters

- **name** (*str*) – Data source name.
- **account_id** (*str*, *optional*) – If None, the account ID will be inferred from your boto3 session.

- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Data source ARNs.

Return type List[str]

Examples

```
>>> import awswrangler as wr
>>> arns = wr.quicksight.get_data_source_arns(name="...")
```

awswrangler.quicksight.get_data_source_id

```
awswrangler.quicksight.get_data_source_id(name: str, account_id: Optional[str]
                                           = None, boto3_session: Optional[boto3.session.Session] = None) →
                                           str
```

Get QuickSight data source ID given a name and fails if there is more than 1 ID associated with this name.

Parameters

- **name** (*str*) – Data source name.
- **account_id** (*str*, *optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Dataset ID.

Return type str

Examples

```
>>> import awswrangler as wr
>>> my_id = wr.quicksight.get_data_source_id(name="...")
```

awswrangler.quicksight.get_data_source_ids

```
awswrangler.quicksight.get_data_source_ids(name: str, account_id: Optional[str]
                                           = None, boto3_session: Optional[boto3.session.Session] = None) →
                                           List[str]
```

Get QuickSight data source IDs given a name.

Note: This function returns a list of ID because Quicksight accepts duplicated data source names, so you may have more than 1 ID for a given name.

Parameters

- **name** (*str*) – Data source name.

- **account_id** (*str*, *optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Data source IDs.

Return type List[str]

Examples

```
>>> import awswrangler as wr
>>> ids = wr.quicksight.get_data_source_ids(name="...")
```

awswrangler.quicksight.get_dataset_id

`awswrangler.quicksight.get_dataset_id(name: str, account_id: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None) → str`

Get QuickSight Dataset ID given a name and fails if there is more than 1 ID associated with this name.

Parameters

- **name** (*str*) – Dataset name.
- **account_id** (*str*, *optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Dataset ID.

Return type str

Examples

```
>>> import awswrangler as wr
>>> my_id = wr.quicksight.get_dataset_id(name="...")
```

awswrangler.quicksight.get_dataset_ids

`awswrangler.quicksight.get_dataset_ids(name: str, account_id: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None) → List[str]`

Get QuickSight dataset IDs given a name.

Note: This function returns a list of ID because QuickSight accepts duplicated datasets names, so you may have more than 1 ID for a given name.

Parameters

- **name** (*str*) – Dataset name.

- **account_id** (*str*, *optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Datasets IDs.

Return type List[str]

Examples

```
>>> import awswrangler as wr
>>> ids = wr.quicksight.get_dataset_ids(name="...")
```

awswrangler.quicksight.get_template_id

`awswrangler.quicksight.get_template_id(name: str, account_id: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None) → str`

Get QuickSight template ID given a name and fails if there is more than 1 ID associated with this name.

Parameters

- **name** (*str*) – Template name.
- **account_id** (*str*, *optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Template ID.

Return type str

Examples

```
>>> import awswrangler as wr
>>> my_id = wr.quicksight.get_template_id(name="...")
```

awswrangler.quicksight.get_template_ids

`awswrangler.quicksight.get_template_ids(name: str, account_id: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None) → List[str]`

Get QuickSight template IDs given a name.

Note: This function returns a list of ID because QuickSight accepts duplicated templates names, so you may have more than 1 ID for a given name.

Parameters

- **name** (*str*) – Template name.

- **account_id** (*str*, *optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Template IDs.

Return type List[str]

Examples

```
>>> import awswrangler as wr
>>> ids = wr.quicksight.get_template_ids(name="...")
```

awswrangler.quicksight.list_dashboards

awswrangler.quicksight.list_dashboards (*account_id: Optional[str] = None*, *boto3_session: Optional[boto3.session.Session] = None*) → List[Dict[str, Any]]

List dashboards in an AWS account.

Parameters

- **account_id** (*str*, *optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Dashboards.

Return type List[Dict[str, Any]]

Examples

```
>>> import awswrangler as wr
>>> dashboards = wr.quicksight.list_dashboards()
```

awswrangler.quicksight.list_data_sources

awswrangler.quicksight.list_data_sources (*account_id: Optional[str] = None*, *boto3_session: Optional[boto3.session.Session] = None*) → List[Dict[str, Any]]

List all QuickSight Data sources summaries.

Parameters

- **account_id** (*str*, *optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Data sources summaries.

Return type List[Dict[str, Any]]

Examples

```
>>> import awswrangler as wr
>>> sources = wr.quicksight.list_data_sources()
```

awswrangler.quicksight.list_datasets

`awswrangler.quicksight.list_datasets` (*account_id: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None*) → List[Dict[str, Any]]

List all QuickSight datasets summaries.

Parameters

- **account_id** (*str, optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session** (*boto3.Session(), optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Datasets summaries.

Return type List[Dict[str, Any]]

Examples

```
>>> import awswrangler as wr
>>> datasets = wr.quicksight.list_datasets()
```

awswrangler.quicksight.list_groups

`awswrangler.quicksight.list_groups` (*namespace: str = 'default', account_id: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None*) → List[Dict[str, Any]]

List all QuickSight Groups.

Parameters

- **namespace** (*str*) – The namespace. Currently, you should set this to default .
- **account_id** (*str, optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session** (*boto3.Session(), optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Groups.

Return type List[Dict[str, Any]]

Examples

```
>>> import awswrangler as wr
>>> groups = wr.quicksight.list_groups()
```

awswrangler.quicksight.list_group_memberships

```
awswrangler.quicksight.list_group_memberships(group_name: str, namespace: str = 'default', account_id: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None)
→ List[Dict[str, Any]]
```

List all QuickSight Group memberships.

Parameters

- **group_name** (*str*) – The name of the group that you want to see a membership list of.
- **namespace** (*str*) – The namespace. Currently, you should set this to default .
- **account_id** (*str*, *optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Group memberships.

Return type List[Dict[str, Any]]

Examples

```
>>> import awswrangler as wr
>>> memberships = wr.quicksight.list_group_memberships()
```

awswrangler.quicksight.list_iam_policy_assignments

```
awswrangler.quicksight.list_iam_policy_assignments(status: Optional[str] = None, namespace: str = 'default', account_id: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None)
→ List[Dict[str, Any]]
```

List IAM policy assignments in the current Amazon QuickSight account.

Parameters

- **status** (*str*, *optional*) – The status of the assignments. 'ENABLED'!'DRAFT'!'DISABLED'
- **namespace** (*str*) – The namespace. Currently, you should set this to default .
- **account_id** (*str*, *optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns IAM policy assignments.

Return type List[Dict[str, Any]]

Examples

```
>>> import awswrangler as wr
>>> assigns = wr.quicksight.list_iam_policy_assignments()
```

awswrangler.quicksight.list_iam_policy_assignments_for_user

```
awswrangler.quicksight.list_iam_policy_assignments_for_user(
    user_name: str,
    namespace: str
    = 'default',
    account_id: Optional[str] = None,
    boto3_session: Optional[boto3.session.Session]
    = None) →
    List[Dict[str, Any]]
```

List all the IAM policy assignments.

Including the Amazon Resource Names (ARNs) for the IAM policies assigned to the specified user and group or groups that the user belongs to.

Parameters

- **user_name** (*str*) – The name of the user.
- **namespace** (*str*) – The namespace. Currently, you should set this to default .
- **account_id** (*str, optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session** (*boto3.Session(), optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns IAM policy assignments.

Return type List[Dict[str, Any]]

Examples

```
>>> import awswrangler as wr
>>> assigns = wr.quicksight.list_iam_policy_assignments_for_user()
```

awswrangler.quicksight.list_ingestions

```
awswrangler.quicksight.list_ingestions(dataset_name: Optional[str] = None, dataset_id:
                                         Optional[str] = None, account_id: Op-
                                         tional[str] = None, boto3_session: Op-
                                         tional[boto3.session.Session] = None) →
                                         List[Dict[str, Any]]
```

List the history of SPICE ingestions for a dataset.

Parameters

- **dataset_name** (*str, optional*) – Dataset name.
- **dataset_id** (*str, optional*) – The ID of the dataset used in the ingestion.
- **account_id** (*str, optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session** (*boto3.Session(), optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns IAM policy assignments.

Return type List[Dict[str, Any]]

Examples

```
>>> import awswrangler as wr
>>> ingestions = wr.quicksight.list_ingestions()
```

awswrangler.quicksight.list_templates

```
awswrangler.quicksight.list_templates(account_id: Optional[str] = None, boto3_session:
                                         Optional[boto3.session.Session] = None) →
                                         List[Dict[str, Any]]
```

List all QuickSight templates.

Parameters

- **account_id** (*str, optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session** (*boto3.Session(), optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Templates summaries.

Return type List[Dict[str, Any]]

Examples

```
>>> import awswrangler as wr
>>> templates = wr.quicksight.list_templates()
```

awswrangler.quicksight.list_users

`awswrangler.quicksight.list_users(namespace: str = 'default', account_id: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None) → List[Dict[str, Any]]`

Return a list of all of the Amazon QuickSight users belonging to this account.

Parameters

- **namespace** (*str*) – The namespace. Currently, you should set this to default .
- **account_id** (*str*, *optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Groups.

Return type List[Dict[str, Any]]

Examples

```
>>> import awswrangler as wr
>>> users = wr.quicksight.list_users()
```

awswrangler.quicksight.list_user_groups

`awswrangler.quicksight.list_user_groups(user_name: str, namespace: str = 'default', account_id: Optional[str] = None, boto3_session: Optional[boto3.session.Session] = None) → List[Dict[str, Any]]`

List the Amazon QuickSight groups that an Amazon QuickSight user is a member of.

Parameters

- **user_name** (*str:*) – The Amazon QuickSight user name that you want to list group memberships for.
- **namespace** (*str*) – The namespace. Currently, you should set this to default .
- **account_id** (*str*, *optional*) – If None, the account ID will be inferred from your boto3 session.
- **boto3_session** (*boto3.Session()*, *optional*) – Boto3 Session. The default boto3 session will be used if boto3_session receive None.

Returns Groups.

Return type List[Dict[str, Any]]

Examples

```
>>> import awswrangler as wr
>>> groups = wr.quicksight.list_user_groups()
```

A

`add_csv_partitions()` (in module `aws wrangler.catalog`), 35
`add_parquet_partitions()` (in module `aws wrangler.catalog`), 36

B

`build_spark_step()` (in module `aws wrangler.emr`), 75
`build_step()` (in module `aws wrangler.emr`), 76

C

`cancel_ingestion()` (in module `aws wrangler.quicksight`), 89
`copy_files_to_redshift()` (in module `aws wrangler.db`), 63
`copy_objects()` (in module `aws wrangler.s3`), 6
`copy_to_redshift()` (in module `aws wrangler.db`), 65
`create_athena_bucket()` (in module `aws wrangler.athena`), 55
`create_athena_data_source()` (in module `aws wrangler.quicksight`), 90
`create_athena_dataset()` (in module `aws wrangler.quicksight`), 91
`create_cluster()` (in module `aws wrangler.emr`), 77
`create_csv_table()` (in module `aws wrangler.catalog`), 37
`create_database()` (in module `aws wrangler.catalog`), 38
`create_ingestion()` (in module `aws wrangler.quicksight`), 92
`create_parquet_table()` (in module `aws wrangler.catalog`), 39

D

`databases()` (in module `aws wrangler.catalog`), 41
`delete_all_dashboards()` (in module `aws wrangler.quicksight`), 93
`delete_all_data_sources()` (in module `aws wrangler.quicksight`), 93

`delete_all_datasets()` (in module `aws wrangler.quicksight`), 94
`delete_all_templates()` (in module `aws wrangler.quicksight`), 94
`delete_dashboard()` (in module `aws wrangler.quicksight`), 95
`delete_data_source()` (in module `aws wrangler.quicksight`), 95
`delete_database()` (in module `aws wrangler.catalog`), 41
`delete_dataset()` (in module `aws wrangler.quicksight`), 96
`delete_objects()` (in module `aws wrangler.s3`), 7
`delete_table_if_exists()` (in module `aws wrangler.catalog`), 42
`delete_template()` (in module `aws wrangler.quicksight`), 97
`describe_dashboard()` (in module `aws wrangler.quicksight`), 97
`describe_data_source()` (in module `aws wrangler.quicksight`), 98
`describe_data_source_permissions()` (in module `aws wrangler.quicksight`), 99
`describe_dataset()` (in module `aws wrangler.quicksight`), 99
`describe_ingestion()` (in module `aws wrangler.quicksight`), 100
`describe_objects()` (in module `aws wrangler.s3`), 8
`does_object_exist()` (in module `aws wrangler.s3`), 9
`does_table_exist()` (in module `aws wrangler.catalog`), 42
`drop_duplicated_columns()` (in module `aws wrangler.catalog`), 43

E

`extract_athena_types()` (in module `aws wrangler.catalog`), 43

G

`get_bucket_region()` (in module `aws wrangler.s3`), 9

- [get_cluster_state\(\)](#) (in module `awswrangler.emr`), 81
[get_columns_comments\(\)](#) (in module `awswrangler.catalog`), 44
[get_csv_partitions\(\)](#) (in module `awswrangler.catalog`), 45
[get_dashboard_id\(\)](#) (in module `awswrangler.quicksight`), 101
[get_dashboard_ids\(\)](#) (in module `awswrangler.quicksight`), 101
[get_data_source_arn\(\)](#) (in module `awswrangler.quicksight`), 102
[get_data_source_arns\(\)](#) (in module `awswrangler.quicksight`), 102
[get_data_source_id\(\)](#) (in module `awswrangler.quicksight`), 103
[get_data_source_ids\(\)](#) (in module `awswrangler.quicksight`), 103
[get_databases\(\)](#) (in module `awswrangler.catalog`), 46
[get_dataset_id\(\)](#) (in module `awswrangler.quicksight`), 104
[get_dataset_ids\(\)](#) (in module `awswrangler.quicksight`), 104
[get_engine\(\)](#) (in module `awswrangler.catalog`), 46
[get_engine\(\)](#) (in module `awswrangler.db`), 66
[get_parquet_partitions\(\)](#) (in module `awswrangler.catalog`), 47
[get_query_columns_types\(\)](#) (in module `awswrangler.athena`), 56
[get_redshift_temp_engine\(\)](#) (in module `awswrangler.db`), 67
[get_step_state\(\)](#) (in module `awswrangler.emr`), 82
[get_table_description\(\)](#) (in module `awswrangler.catalog`), 48
[get_table_location\(\)](#) (in module `awswrangler.catalog`), 48
[get_table_parameters\(\)](#) (in module `awswrangler.catalog`), 49
[get_table_types\(\)](#) (in module `awswrangler.catalog`), 49
[get_tables\(\)](#) (in module `awswrangler.catalog`), 50
[get_template_id\(\)](#) (in module `awswrangler.quicksight`), 105
[get_template_ids\(\)](#) (in module `awswrangler.quicksight`), 105
[get_work_group\(\)](#) (in module `awswrangler.athena`), 56
- L**
- [list_dashboards\(\)](#) (in module `awswrangler.quicksight`), 106
[list_data_sources\(\)](#) (in module `awswrangler.quicksight`), 106
- [list_datasets\(\)](#) (in module `awswrangler.quicksight`), 107
[list_directories\(\)](#) (in module `awswrangler.s3`), 10
[list_group_memberships\(\)](#) (in module `awswrangler.quicksight`), 108
[list_groups\(\)](#) (in module `awswrangler.quicksight`), 107
[list_iam_policy_assignments\(\)](#) (in module `awswrangler.quicksight`), 108
[list_iam_policy_assignments_for_user\(\)](#) (in module `awswrangler.quicksight`), 109
[list_ingestions\(\)](#) (in module `awswrangler.quicksight`), 110
[list_objects\(\)](#) (in module `awswrangler.s3`), 10
[list_templates\(\)](#) (in module `awswrangler.quicksight`), 110
[list_user_groups\(\)](#) (in module `awswrangler.quicksight`), 111
[list_users\(\)](#) (in module `awswrangler.quicksight`), 111
- M**
- [merge_datasets\(\)](#) (in module `awswrangler.s3`), 11
- O**
- [overwrite_table_parameters\(\)](#) (in module `awswrangler.catalog`), 50
- R**
- [read_csv\(\)](#) (in module `awswrangler.s3`), 12
[read_fwf\(\)](#) (in module `awswrangler.s3`), 13
[read_json\(\)](#) (in module `awswrangler.s3`), 15
[read_logs\(\)](#) (in module `awswrangler.cloudwatch`), 85
[read_parquet\(\)](#) (in module `awswrangler.s3`), 16
[read_parquet_metadata\(\)](#) (in module `awswrangler.s3`), 18
[read_parquet_table\(\)](#) (in module `awswrangler.s3`), 19
[read_sql_query\(\)](#) (in module `awswrangler.athena`), 57
[read_sql_query\(\)](#) (in module `awswrangler.db`), 68
[read_sql_table\(\)](#) (in module `awswrangler.athena`), 59
[read_sql_table\(\)](#) (in module `awswrangler.db`), 69
[repair_table\(\)](#) (in module `awswrangler.athena`), 80
[run_query\(\)](#) (in module `awswrangler.cloudwatch`), 86
- S**
- [sanitize_column_name\(\)](#) (in module `awswrangler.catalog`), 51
[sanitize_dataframe_columns_names\(\)](#) (in module `awswrangler.catalog`), 52

[sanitize_table_name\(\)](#) (in module `aws wrangler.catalog`), 52
[search_tables\(\)](#) (in module `aws wrangler.catalog`), 53
[size_objects\(\)](#) (in module `aws wrangler.s3`), 21
[start_query\(\)](#) (in module `aws wrangler.cloudwatch`), 87
[start_query_execution\(\)](#) (in module `aws wrangler.athena`), 61
[stop_query_execution\(\)](#) (in module `aws wrangler.athena`), 62
[store_parquet_metadata\(\)](#) (in module `aws wrangler.s3`), 22
[submit_ecr_credentials_refresh\(\)](#) (in module `aws wrangler.emr`), 82
[submit_spark_step\(\)](#) (in module `aws wrangler.emr`), 83
[submit_step\(\)](#) (in module `aws wrangler.emr`), 84
[submit_steps\(\)](#) (in module `aws wrangler.emr`), 84

T

[table\(\)](#) (in module `aws wrangler.catalog`), 53
[tables\(\)](#) (in module `aws wrangler.catalog`), 54
[terminate_cluster\(\)](#) (in module `aws wrangler.emr`), 85
[to_csv\(\)](#) (in module `aws wrangler.s3`), 24
[to_json\(\)](#) (in module `aws wrangler.s3`), 28
[to_parquet\(\)](#) (in module `aws wrangler.s3`), 29
[to_sql\(\)](#) (in module `aws wrangler.db`), 70

U

[unload_redshift\(\)](#) (in module `aws wrangler.db`), 71
[unload_redshift_to_files\(\)](#) (in module `aws wrangler.db`), 73
[upsert_table_parameters\(\)](#) (in module `aws wrangler.catalog`), 54

W

[wait_objects_exist\(\)](#) (in module `aws wrangler.s3`), 32
[wait_objects_not_exist\(\)](#) (in module `aws wrangler.s3`), 33
[wait_query\(\)](#) (in module `aws wrangler.athena`), 62
[wait_query\(\)](#) (in module `aws wrangler.cloudwatch`), 88
[write_redshift_copy_manifest\(\)](#) (in module `aws wrangler.db`), 74